Class

# INSpeakableStringResolutionResult

A resolution result for a speakable string object associated with an intent.

iOS 10.0+ | iPadOS 10.0+ | Mac Catalyst 13.1+ | visionOS 1.0+ | watchOS 3.2+

```
class INSpeakableStringResolutionResult
```

## Overview

An INSpeakableStringResolutionResult object is what you return when resolving parameters containing an INSpeakableString object. Use the creation method that best reflects your ability to successfully resolve the parameter.

For additional resolution options, see INIntentResolutionResult.

## Topics

### Creating a Resolution Result Object

```
class func success(with: INSpeakableString) -> Self
```

Creates an object whose resolution involves the successful matching of the specified parameter.

```
class func confirmationRequired(with: INSpeakableString?) -> Self
```

Creates an object whose resolution requires that the user must confirm the value before proceeding.

```
class func disambiguation(with: [INSpeakableString]) -> Self
```
Creates an object whose resolution requires the user to select from among the specified objects.

# Relationships

## Inherits From

`INIntentResolutionResult`

## Conforms To

```
CVarArg
CustomDebugStringConvertible
CustomStringConvertible
Equatable
Hashable
NSObjectProtocol
```

# See Also

## Strings

```
class INStringResolutionResult
```
A resolution result for a string value associated with an intent.