

[Accelerate](#) / BNNSGraphCompileOptionsMakeDefault()

Function

BNNSGraphCompileOptionsMakeDefault()

Returns an allocated compilation options object with default values.

iOS 18.0+ | iPadOS 18.0+ | Mac Catalyst 18.0+ | macOS 15.0+ | tvOS 18.0+ | visionOS 2.0+ | watchOS 11.0+

```
func BNNSGraphCompileOptionsMakeDefault() -> bnns_graph_compile_options_t
```

Return Value

An allocated compilation options object with default values.

See Also

Specifying and querying compilation options

```
struct bnns_graph_compile_options_t
```

The compilation options that BNNS uses when compiling a source mlmodelc file to a graph object.

```
func BNNSGraphCompileOptionsDestroy(bnns_graph_compile_options_t)
```

Destroys the specified compilation options object.

```
func BNNSGraphCompileOptionsSetOutputPath(bnns_graph_compile_options_t,  
UnsafePointer<CChar>?)
```

Sets the option for graph compilation to generate the graph object directly to the specified file.

```
func BNNSGraphCompileOptionsGetOutputPath(bnns_graph_compile_options_t)
-> UnsafePointer<CChar>?
```

Returns the option for the compiled graph's output path.

```
func BNNSGraphCompileOptionsSetOutputFD(bnns_graph_compile_options_t,
Int32)
```

Sets the option for graph compilation to generate the graph object directly to the specified file descriptor.

```
func BNNSGraphCompileOptionsGetOutputFD(bnns_graph_compile_options_t) -
> Int32
```

Returns the option for the compiled graph's output file descriptor.

```
func BNNSGraphCompileOptionsSetTargetSingleThread(bnns_graph_compile
_options_t, Bool)
```

Sets the option for the compiled graph to execute on a single thread.

```
func BNNSGraphCompileOptionsGetTargetSingleThread(bnns_graph_compile
_options_t) -> Bool
```

Returns the option for the compiled graph to execute on a single thread.

```
func BNNSGraphCompileOptionsSetOptimizationPreference(bnns_graph
_compile_options_t, BNNSGraphOptimizationPreference)
```

Sets the option for the compiled graph to optimize for either size or performance.

```
func BNNSGraphCompileOptionsGetOptimizationPreference(bnns_graph
_compile_options_t) -> BNNSGraphOptimizationPreference
```

Returns the option for the compiled graph to optimize for either size or performance.

```
struct BNNSGraphOptimizationPreference
```

Constants that describe the compilation optimization preference.

```
func BNNSGraphCompileOptionsSetGenerateDebugInfo(bnns_graph_compile
_options_t, Bool)
```

Sets the option for the compiled graph to include debugging information.

```
func BNNSGraphCompileOptionsGetGenerateDebugInfo(bnns_graph_compile
_options_t) -> Bool
```

Returns the option for the compiled graph to include debugging information.

```
var BNNSTargetSystemGeneric: BNNSTargetSystem
```