

[Accelerate](#) / `bnns_graph_compile_message_fn_t`

Type Alias

`bnns_graph_compile_message_fn_t`

The graph compile-message logging callback function.

iOS 18.0+ | iPadOS 18.0+ | Mac Catalyst 18.0+ | macOS 15.0+ | tvOS 18.0+ | visionOS 2.0+ | watchOS 11.0+

```
typealias bnns_graph_compile_message_fn_t = (BNNSGraphMessageLevel, UnsafePointer<CChar>, UnsafePointer<CChar>?, UnsafeMutablePointer<bnns_user_message_data_t>?) -> Void
```

See Also

Specifying a graph's compile-time message callback

```
func BNNSGraphCompileOptionsSetMessageLogMask(bnns_graph_compile_options_t, UInt32)
```

Sets the mask for compile-time messages.

```
func BNNSGraphContextSetMessageLogMask(bnns_graph_context_t, UInt32) -> Int32
```

Sets mask for log messages that are logged (either via `os_log` or the user specified callback)

```
struct BNNSGraphMessageLevel
```

Constants that specify the mask for compile-time messages.

```
func BNNSGraphCompileOptionsSetMessageLogCallback(bnns_graph_compile_options_t, bnns_graph_compile_message_fn_t, UnsafeMutablePointer<bnns_user_message_data_t>?)
```

Specifies a customized callback function that reports compile-time messages.

```
struct bnns_user_message_data_t
```

Additional user-defined logging argument for message-logging callbacks.