

[Foundation](#) / Data Formatting

API Collection

Data Formatting

Convert numbers, dates, measurements, and other values to and from locale-aware string representations.

Overview

Foundation supports two approaches for data formatting:

- When working in Swift, use `formatted` methods directly on the types you want to format, optionally using [FormatStyle](#) and its subtypes to customize formatter output. This approach supports dates, integers, floating-point numbers, measurements, sequences, and person name components. Foundation caches identically-configured formatter instances internally, allowing you to focus on your app's formatting needs.
- In Objective-C, create instances of [Formatter](#) and its subtypes, and use the [string\(for:\)](#) method to convert objects to formatted strings.

Topics

Data formatting in Swift



Language Introspector

Converts data into human-readable text using formatters and locales.

protocol `FormatStyle`

A type that converts a given data type into a representation in another type, such as a string.

struct `IntegerFormatStyle`

A structure that converts between integer values and their textual representations.

`struct FloatingPointFormatStyle`

A structure that converts between floating-point values and their textual representations.

`struct FormatStyle`

A structure that converts between decimal values and their textual representations.

`struct ListFormatStyle`

A type that formats lists of items with a separator and conjunction appropriate for a given locale.

`struct StringStyle`

`struct FormatStyle`

A structure that converts between URL instances and their textual representations.

`struct FormatStyleCapitalizationContext`

The capitalization formatting context used when formatting dates and times.

☰ `Format Style Configurations`

Behaviors for traits like numeric precision, rounding, and scale, used for formatting and parsing numeric values.

Data parsing in Swift

`protocol ParseableFormatStyle`

A type that can convert a given input data type into a representation in an output type.

`protocol ParseStrategy`

A type that parses an input representation, such as a formatted string, into a provided data type.

`struct IntegerParseStrategy`

A parse strategy for creating integer values from formatted strings.

`struct FloatingPointParseStrategy`

A parse strategy for creating floating-point values from formatted strings.

`struct ParseStrategy`

A parse strategy for creating decimal values from formatted strings.

Numbers and currency

`class` `NumberFormatter`

A formatter that converts between numeric values and their textual representations.

Names

`class` `PersonNameComponentsFormatter`

A formatter that provides localized representations of the components of a person's name.

`struct` `PersonNameComponents`

The separate parts of a person's name, allowing locale-aware formatting.

Dates and times

`class` `DateFormatter`

A formatter that converts between dates and their textual representations.

`class` `DateComponentsFormatter`

A formatter that creates string representations of quantities of time.

`class` `RelativeDateTimeFormatter`

A formatter that creates locale-aware string representations of a relative date or time.

`class` `DateIntervalFormatter`

A formatter that creates string representations of time intervals.

`class` `ISO8601DateFormatter`

A formatter that converts between dates and their ISO 8601 string representations.

Data sizes

`class` `ByteCountFormatter`

A formatter that converts a byte count value into a localized description that is formatted with the appropriate byte modifier (KB, MB, GB and so on).

Measurements

`class MeasurementFormatter`

A formatter that provides localized representations of units and measurements.

Lists

`class ListFormatter`

An object that provides locale-correct formatting of a list of items using the appropriate separator and conjunction.

Internationalization

`struct Locale`

Information about linguistic, cultural, and technological conventions for use in formatting data for presentation.

Custom formatters

`class Formatter`

An abstract class that declares an interface for objects that create, interpret, and validate the textual representation of values.

Automatic grammar agreement

`enum InflectionRule`

A rule that affects how an attributed string performs automatic grammatical agreement.

`struct Morphology`

A description of the grammatical properties of a string.

`struct TermOfAddress`

The type for representing grammatical gender in localized text.

`enum InflectionConcept`

An inflection method to use when localizing text.

`struct Pronoun`

A custom pronoun for referring to a third person.

Deprecated

`class LengthFormatter`

A formatter that provides localized descriptions of linear distances, such as length and height measurements.

`class MassFormatter`

A formatter that provides localized descriptions of mass and weight values.

`class EnergyFormatter`

A formatter that provides localized descriptions of energy values.

See Also

Fundamentals

☰ Numbers, Data, and Basic Values

Work with primitive values and other fundamental types used throughout Cocoa.

☰ Strings and Text

Create and process strings of Unicode characters, use regular expressions to find patterns, and perform natural language analysis of text.

☰ Collections

Use arrays, dictionaries, sets, and specialized collections to store and iterate groups of objects or values.

☰ Dates and Times

Compare dates and times, and perform calendar and time zone calculations.

☰ Units and Measurement

Label numeric quantities with physical dimensions to allow locale-aware formatting and conversion between related units.

☰ Filters and Sorting

Use predicates, expressions, and sort descriptors to examine elements in collections and other services.