

[ProximityReader](#) / MobileDocumentRequest

## Protocol

# MobileDocumentRequest

A type that represents a mobile document request.

iOS 17.0+ | iPadOS 17.0+ | Mac Catalyst 17.0+ | visionOS 1.0+

`protocol` MobileDocumentRequest : Hashable, Sendable

## Mentioned in

 Adopting the Verifier API in your iPhone app

## Topics

### Mobile driver's license display request

```
struct MobileDriversLicenseDisplayRequest
```

A mobile driver's license request that retrieves elements from the holder and displays the results onscreen for visual inspection.

```
static func displayDriversLicense([MobileDriversLicenseDisplayRequest.Element], options: MobileDriversLicenseDisplayRequest.Options) -> Self
```

A request that displays driver's license elements onscreen.

### Mobile driver's license data request

```
struct MobileDriversLicenseDataRequest
```

A mobile driver's license request that retrieves elements from the holder and returns the validated document elements.

```
static func driversLicenseData(retaining: [MobileDriversLicenseDataRequest.Element], notRetaining: [MobileDriversLicenseDataRequest.Element]) -> Self
```

A request which retrieves elements from the holder and returns the validated document elements.

## Mobile driver's license raw data request

```
struct MobileDriversLicenseRawDataRequest
```

A mobile driver's license request which retrieves elements from the holder and returns the raw response data for processing.

```
static func driversLicenseRawData(retaining: [MobileDriversLicenseRawDataRequest.Element], notRetaining: [MobileDriversLicenseRawDataRequest.Element]) -> Self
```

A request which retrieves mobile driver's license elements from the holder and returns the raw response data for processing.

## National ID card display request

```
struct MobileNationalIDCardDisplayRequest
```

A mobile national ID card request that retrieves elements from the holder and displays the results onscreen for visual inspection.

```
static func nationalIDCard(region: Locale.Region, [MobileNationalIDCardDisplayRequest.Element], options: MobileNationalIDCardDisplayRequest.Options) -> Self
```

A request that displays national ID card elements onscreen.

## National ID card license data request

```
struct MobileNationalIDCardDataRequest
```

A mobile national ID card request that retrieves elements from the holder and returns the validated document elements.

```
static func nationalIDCardData(region: Locale.Region, retaining: [MobileNationalIDCardDataRequest.Element], notRetaining: [MobileNationalIDCardDataRequest.Element]) -> Self
```

A request which retrieves elements from the holder and returns the validated document elements.

## National ID card license raw data request

`struct MobileNationalIDCardRawDataRequest`

A mobile national ID card request which retrieves elements from the holder and returns the raw response data for processing.

```
static func nationalIDCardRawData(region: Locale.Region, retaining: [MobileNationalIDCardRawDataRequest.Element], notRetaining: [MobileNationalIDCardRawDataRequest.Element]) -> Self
```

A request which retrieves mobile national ID card elements from the holder and returns the raw response data for processing.

## Associated Types

`associatedtype Response : Hashable, Sendable`

A type that represents the response type of the request.

Required

## Type Methods

```
static func displayDocument([MobileDocumentDisplayRequest.Element], options: MobileDocumentDisplayRequest.Options) -> Self
```

A request that displays document elements onscreen.

```
static func photoIDData(retaining: [MobilePhotoIDDataRequest.Element], notRetaining: [MobilePhotoIDDataRequest.Element]) -> Self
```

A request which retrieves elements from the holder and returns the validated document elements.

```
static func photoIDRawData(retaining: [MobilePhotoIDRawDataRequest.Element], notRetaining: [MobilePhotoIDRawDataRequest.Element]) -> Self
```

A request which retrieves photo ID elements from the holder and returns the raw response data for processing.

---

## Relationships

## Inherits From

Equatable  
Hashable  
Sendable  
SendableMetatype

## Inherited By

MobileDocumentDataRequest, MobileDocumentRawDataRequest

## Conforming Types

MobileDocumentAnyOfDataRequest  
MobileDocumentAnyOfRawDataRequest  
MobileDocumentDisplayRequest  
MobileDriversLicenseDataRequest  
MobileDriversLicenseDisplayRequest  
MobileDriversLicenseRawDataRequest  
MobileNationalIDCardDataRequest  
MobileNationalIDCardDisplayRequest  
MobileNationalIDCardRawDataRequest  
MobilePhotoIDDataRequest  
MobilePhotoIDRawDataRequest

---

## See Also

### Mobile document requests

**struct** MobileDriversLicenseDisplayRequest

A mobile driver's license request that retrieves elements from the holder and displays the results onscreen for visual inspection.

**struct** MobileDriversLicenseDataRequest

A mobile driver's license request that retrieves elements from the holder and returns the validated document elements.

**struct** MobileDriversLicenseRawDataRequest

A mobile driver's license request which retrieves elements from the holder and returns the raw response data for processing.

`struct MobileNationalIDCardDisplayRequest`

A mobile national ID card request that retrieves elements from the holder and displays the results onscreen for visual inspection.

`struct MobileNationalIDCardDataRequest`

A mobile national ID card request that retrieves elements from the holder and returns the validated document elements.

`struct MobileNationalIDCardRawDataRequest`

A mobile national ID card request which retrieves elements from the holder and returns the raw response data for processing.

`struct MobileDocumentDisplayRequest`

A mobile document request that retrieves elements from the holder and displays the results onscreen for visual inspection.

`protocol MobileDocumentDataRequest`

A type that represents a mobile document data request.

`protocol MobileDocumentRawDataRequest`

A type that represents a mobile document raw data request.

`struct MobilePhotoIDDataRequest`

A photo ID request that retrieves elements from the holder and returns the validated document elements.

`struct MobilePhotoIDRawDataRequest`

A photo ID request which retrieves elements from the holder and returns the raw response data for processing.

`struct MobileDocumentAnyOfDataRequest`

A type that describes a data request for any mobile document from a group of requests.

`struct MobileDocumentAnyOfRawDataRequest`

A type that describes a raw data request for any mobile document from a group of requests.