API Collection

Table View

Display custom data in rows and columns.

Topics

Views

class `NSTableView`

A set of related records, displayed in rows that represent individual records and columns that represent the attributes of those records.

class `NSTableCellView`

A reusable container view shown for a particular cell in a table view that uses rows for content.

Management

protocol `NSTableViewDataSource`

A set of methods that a table view uses to provide data to a table view and to allow the editing of the table view's data source object.

protocol `NSTableViewDelegate`

A set of optional methods you implement in a table view delegate to customize the behavior of the table view.

class `NSTableViewDiffableDataSource`

The object you use to manage data and provide items for a table view.

Rows and Columns

class `NSTableHeaderView`

An object that draws headers over a table view's columns and handles mouse events in those headers.

class `NSTableHeaderCell`

An object that a table header view uses to draw the content of the column headers.

class `NSTableRowView`

The view shown for a row in a table view.

class `NSTableColumn`

The display characteristics and identifier for a column in a table view.

class `NSTableViewRowAction`

A single action to present when the user swipes horizontally on a table row.

struct `ResizingOptions`

See Also

Content views

☰ Browser View

Provide a column-based interface for viewing and navigating hierarchical information.

☰ Collection View

Display one or more subviews in a highly configurable arrangement.

☰ Outline View

Display a list-based interface for hierarchical data, where each level of hierarchy is indented from the previous one.

class `NSTextView`

A view that draws text and handles user interactions with that text.