Class

CNChangeHistoryUpdateContactEvent

An object that represents a user updating a contact.

iOS 13.0+ | iPadOS 13.0+ | Mac Catalyst 13.1+ | macOS 10.15+ | visionOS 1.0+ | watchOS 6.0+

```
class CNChangeHistoryUpdateContactEvent
```

Topics

Getting event details

var contact: CNContact

The contact that the user updated.

Relationships

Inherits From

CNChangeHistoryEvent

Conforms To

CVarArg
CustomDebugStringConvertible
CustomStringConvertible

```
Equatable
Hashable
NSCoding
NSCopying
NSObjectProtocol
NSSecureCoding
```

See Also

Change history data

class **CNChangeHistoryAddContactEvent**

An object that represents a user adding a contact.

class **CNChangeHistoryAddGroupEvent**

An object that represents a user adding a group.

class **CNChangeHistoryAddMemberToGroupEvent**

An object that represents a user adding a contact to a group.

class **CNChangeHistoryAddSubgroupToGroupEvent**

An object that represents a user adding a subgroup to a group.

class **CNChangeHistoryDeleteContactEvent**

An object that represents a user deleting a contact.

class **CNChangeHistoryDeleteGroupEvent**

An object that represents a user deleting a group.

class **CNChangeHistoryDropEverythingEvent**

An object that indicates the delegate should drop all contacts and groups before handling change events.

class **CNChangeHistoryEvent**

An object that represents the user adding, updating, or deleting a contact or group.

class **CNChangeHistoryFetchRequest**

An object that specifies the criteria for fetching change history.

class `CNChangeHistoryRemoveMemberFromGroupEvent`

An object that represents a user removing a contact from a group.

class `CNChangeHistoryRemoveSubgroupFromGroupEvent`

An object that represents a user removing a subgroup from a group.

class `CNChangeHistoryUpdateGroupEvent`

An object that represents an updated group event.

protocol `CNChangeHistoryEventVisitor`

An interface for receiving notice of changes to contacts and groups.