Article

Creating a Core Graphics Image from a vImage Buffer

Create displayable representations of vImage buffers.

Overview

vImage provides a function for creating Core Graphics images from vImage buffers. This function allows you to display the results of a vImage operation to your user.

Create the Image

You create a Core Graphics image from the buffer, and initialize a `UIImage` instance from that. The `createCGImage(format:flags:)` function returns a `CGImage` instance based on the supplied Core Graphics image format (for more information, see Converting bitmap data between Core Graphics images and vImage buffers).

The following example shows how to create a Core Graphics image from a vImage buffer:

```
let result = try? destinationBuffer.createCGImage(format: format)

if let result = result {
    // Assumes `imageView` is a `UIImageView`
    imageView.image = UIImage(cgImage: result)
}
```

See Also

Image Processing Essentials

- Converting bitmap data between Core Graphics images and vImage buffers
  Pass image data between Core Graphics and vImage to create and manipulate images.
- Creating and Populating Buffers from Core Graphics Images
  Initialize vImage buffers from Core Graphics images.
- Building a Basic Image-Processing Workflow
  Resize an image with vImage.
- Applying geometric transforms to images
  Reflect, shear, rotate, and scale image buffers using vImage.
- Compositing images with alpha blending
  Combine two images by using alpha blending to create a single output.
- Compositing images with vImage blend modes
  Combine two images by using blend modes to create a single output.
- Applying vImage operations to regions of interest
  Limit the effect of vImage operations to rectangular regions of interest.
- Optimizing image-processing performance
  Improve your app's performance by converting image buffer formats from interleaved to planar.

- vImage
  Manipulate large images using the CPU's vector processor.