

[Metal](#) / [Shader libraries](#) / Customizing shaders using function pointers and stitching

Sample Code

Customizing shaders using function pointers and stitching

Define custom shader behavior at runtime by creating functions from existing ones and preferentially linking to others in a dynamic library.

[Download](#)

iOS 15.0+ | iPadOS 15.0+ | macOS 12.0+ | Xcode 13.4+

Overview

Note

This sample code project is associated with WWDC2021 session [10229: Discover compilation workflows in Metal](#) and WWDC2022 session [6596: Target and optimize GPU binaries with Metal 3](#).

See Also

Stitched function libraries

`class MTLStitchedLibraryDescriptor`

A description of a new library of procedurally generated functions.

`class MTLFunctionStitchingGraph`

A description of a new stitched function.

`class MTLFunctionStitchingInputNode`

A call graph node that describes an input to the call graph.

`class MTLFunctionStitchingFunctionNode`

A call graph node that describes a function call and its inputs.

`protocol MTLFunctionStitchingNode`

A protocol to identify call graph nodes.

`class MTLFunctionStitchingAttributeAlwaysInline`

An attribute to specify that Metal needs to inline all of the function calls when generating the stitched function.

`protocol MTLFunctionStitchingAttribute`

A protocol to identify types that customize how the Metal compiler stitches a function together.