

[Account Data Transfer](#) / Resubmit request

Web Service Endpoint

# Resubmit request

Enqueue the next instance of a recurring request.

Account Data Transfer 1.0+

---

## URL

**POST** <https://accountdatatransfer.apple.com/api/transfer/accountdata/resubmit>

## HTTP Body

[ResubmissionRequest](#)

The recurring request for which you submit a new instance.

Content-Type: application/json

## Response Codes

**200**

**OK**

[ResubmissionResponse](#)

Content-Type: application/json

**400**

**Bad Request**

**401**

**Unauthorized**

**403**

**Forbidden**

**500**

**Internal Server Error**

## Overview

The `requestId` you pass must be the most recent instance of the series identified by the `parentRequestId`.

Request      Response

---

```
% curl -X POST \  
-H "Authorization: Bearer [ACCESS_TOKEN]" \  
-H "X-Apple-Transaction-Id: E3857B28-7FC4-41C8-AC54-08E121E26F59" \  
-H "Content-Type: application/json" \  
-d '{ "parentRequestId": "EABD06C0-9210-47FF-83C4-318CF8520644", "requestId": "7BE" }' \  
https://accountdatatransfer.apple.com/api/transfer/accountdata/resubmit
```

## See Also

### Request creation

#### Submit request

Starts preparing someone's data for download.

#### object JobSubmission

An object that describes a submission that requests someone's data.

#### object CreatedJob

An object that represents a newly created download request.

#### object ResubmissionRequest

An object that describes a request to resubmit a recurring download request.

#### object ResubmissionResponse

An object that represents a resubmitted recurring download request.