

[Apple Music API](#) / Get the user's replay data

Web Service Endpoint

Get the user's replay data

Fetch the user's replay data for the latest eligible year.

Apple Music 1.0+

URL

GET `https://api.music.apple.com/v1/me/music-summaries`

Query Parameters

extend [string]	A list of attribute extensions applied to resources in the response.
filter[year] [string]	(Required) A filter applied to the request. The value is always <code>latest</code> .
include [string]	A list of relationship names to include for resources in the response.
l string	The localization specified by a language tag. The possible values are in the <code>supportedLanguageTags</code> array belonging to the <code>Storefront</code> object specified by the storefront. Otherwise, the storefront's <code>defaultLanguageTag</code> is used.
views [string]	The views to activate for the music summaries resource. Possible Values: <code>top-artists</code> , <code>top-albums</code> , <code>top-songs</code>

Response Codes

200 MusicSummariesResponse	OK The request was successful. Content-Type: application/json
401 UnauthorizedResponse	Unauthorized A response indicating an incorrect Authorization header. Content-Type: application/json
403 ForbiddenResponse	Forbidden A response indicating invalid or insufficient authentication. Content-Type: application/json
500 ErrorsResponse	Internal Server Error A response indicating an error occurred on the server. Content-Type: application/json

Discussion

A successful HTTP request returns music summaries for the most recent year that the user has enough listening history. If unsuccessful, the HTTP status code indicates the error, and the details are in the errors array. For more information, see [Handling Requests and Responses](#).