

[App Intents](#) / EntityProperty

## Class

# EntityProperty

A property wrapper that exposes the associated property to the system.

iOS 16.0+ | iPadOS 16.0+ | Mac Catalyst | macOS 13.0+ | tvOS 16.0+ | visionOS | watchOS 9.0+

```
@propertyWrapper
final class EntityProperty<Value> where Value : _IntentValue, Value : Sendable
```

## Topics

### Initializers

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

`convenience init()`

Creates an app intent entity property.

```
convenience init()
```

Creates an app intent entity property.

```
convenience init()
```

Creates an app intent entity property.

```
convenience init()
```

Creates an app intent entity property.

```
convenience init()
```

Creates an app intent entity property.

```
convenience init()
```

```
convenience init()
```

Creates an app intent entity property.

```
convenience init()
```

Creates an app intent entity property.

```
convenience init(customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`



Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)  
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, asyncGetter: (Entity)
async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustom
AttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustom
AttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustom
AttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustom
AttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty



```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:  
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty



```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty



```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, customIndexingKey:
CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath
<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath
<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath
<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath
<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```



Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty



```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```



Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, indexingKey: PartialKeyPath<
CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,
Value>)
```

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty



```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty



```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity,  
Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, indexingKey: PartialKey  
Path<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

[illegible]

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`

`convenience init(identifier: String, title: LocalizedStringResource)`



Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

`convenience init(identifier: String, title: LocalizedStringResource)`

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty



`convenience init(identifier: String, title: LocalizedStringResource)`  
Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`  
Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`  
Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`  
Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init(identifier: String, title: LocalizedStringResource)`  
Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)`  
Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)`

`convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)`  
Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

`convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)`  
Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, asyncGetter: (Entity) async throws -> Value)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey)
```

```
convenience init(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```



Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty



```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
customIndexingKey: CSCustomAttributeKey)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getSetter: Writable  
KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```



Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```



Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, customIndexingKey: CSCustomAttributeKey, getter: KeyPath<  
Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```



```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```



Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```



Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use `@ComputedProperty` or `@DeferredProperty`



```
convenience init(identifier: String, title: LocalizedStringResource,
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,  
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(identifier: String, title: LocalizedStringResource,
indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```



Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getSetter: WritableKeyPath<Entity, Value>)
```



Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getSetter: WritableKeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedString  
Resource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>,  
getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init<Entity>(identifier: String, title: LocalizedStringResource, indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>, getter: KeyPath<Entity, Value>)
```

Creates an app intent entity property. Do not call this directly, use @ComputedProperty or @DeferredProperty

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.



```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```



Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(indexingKey: PartialKeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource)
```

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource)`

Creates an app intent entity property.

`convenience init(title: LocalizedStringResource, customIndexingKey: CSCustomAttributeKey)`

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.



```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, customIndexingKey:
CSCustomAttributeKey)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

```
convenience init(title: LocalizedStringResource, indexingKey: Partial  
KeyPath<CSSearchableItemAttributeSet>)
```

Creates an app intent entity property.

## Instance Properties

```
var projectedValue: EntityProperty<Value>
```

```
var wrappedValue: Value
```

---

# Relationships

## Conforms To

AnyIntentValue

Copyable

CustomStringConvertible

Decodable

Encodable

Sendable

SendableMetatype

---

## See Also

## Entity content

`protocol AppValue`

An interface that describes conceptual types you use in app intents.

`protocol AnyIntentValue`

A type the system uses to access a parameter or property value.

`protocol AppEnum`

An interface to express that a custom type has a predefined, static set of valid values to display.

`protocol URLRepresentableEnum`

An app enum with a URL representation.