

[Account Data Transfer](#) / Cancel request

Web Service Endpoint

Cancel request

Tells the server to stop processing an active request.

Account Data Transfer 1.0+

URL

POST `https://accountdatatransfer.apple.com/api/transfer/accountdata/cancel`

HTTP Body

[CancellationRequest](#)

An object that identifies the request to cancel.

Content-Type: application/json

Response Codes

200

OK

[CancellationResponse](#)

Content-Type: application/json

400

Bad Request

401

Unauthorized

403

Forbidden

500

Internal Server Error

Overview

A cancellation request only succeeds if the request is currently in progress.

Cancel a one-time download

Request Response

```
% curl -X POST \  
-H "Authorization: Bearer [ACCESS_TOKEN]" \  
-H "X-Apple-Transaction-Id: E3857B28-7FC4-41C8-AC54-08E121E26F59" \  
-H "Content-Type: application/json" \  
-d '{ "requestId": "11619695-72C0-4FFD-858A-1E152DCF0838" }' \  
https://accountdatatransfer.apple.com/api/transfer/accountdata/cancel
```

Cancel a recurring download

Request Response

```
% curl -X POST \  
-H "Authorization: Bearer [ACCESS_TOKEN]" \  
-H "X-Apple-Transaction-Id: E3857B28-7FC4-41C8-AC54-08E121E26F59" \  
-H "Content-Type: application/json" \  
-d '{ "requestId": "7BBBD45D-638B-4DB5-8B02-F23FDB15EDA7" }' \  
https://accountdatatransfer.apple.com/api/transfer/accountdata/cancel
```

See Also

Cancellation

object CancellationRequest

An object that identifies a one-time request, or an individual instance of a recurring request, to cancel.

object CancellationResponse

An object that describes the outcome of canceling a download request.