

[Intents](#) / `INPersonResolutionResult`

## Class

# INPersonResolutionResult

A resolution result for a user as a parameter of an intent.

iOS 10.0+ | iPadOS 10.0+ | Mac Catalyst 13.1+ | macOS 11.0+ | visionOS 1.0+ | watchOS 3.2+

```
class INPersonResolutionResult
```

## Mentioned in

 Improving interactions between Siri and your messaging app

## Overview

An `INPersonResolutionResult` object is what you return when resolving parameters containing an `INPerson` object. Use the creation method that best reflects your ability to successfully resolve the parameter.

For additional resolution options, see `INIntentResolutionResult`.

## Topics

### Creating a Resolution Result Object

```
class func success(with: INPerson) -> Self
```

Creates an object whose resolution involves the successful matching of the specified parameter.

```
class func confirmationRequired(with: INPerson?) -> Self
```

Creates an object whose resolution requires that the user must confirm the value before proceeding.

```
class func disambiguation(with: [INPerson]) -> Self
```

Creates an object whose resolution requires the user to select from among the specified objects.

---

## Relationships

### Inherits From

INIntentResolutionResult

### Inherited By

INRequestPaymentPayerResolutionResult  
INSendMessageRecipientResolutionResult  
INSendPaymentPayeeResolutionResult  
INStartCallContactResolutionResult

### Conforms To

CVarArg  
CustomDebugStringConvertible  
CustomStringConvertible  
Equatable  
Hashable  
NSObjectProtocol

---

## See Also

### Providing Resolution Results

```
class INMessageAttributeResolutionResult
```

A resolution result for assorted attributes of a message.

```
class INMessageAttributeOptionsResolutionResult
```

A resolution result for a search parameter that filters by message status.

```
class INDateComponentsRangeResolutionResult
```

A resolution result for a range of dates in a parameter of an intent.

```
class INSendMessageRecipientResolutionResult
```

A resolution result for the recipient of a message.

```
class INOutgoingMessageTypeResolutionResult
```

A resolution result for the message's format.