Web Service Endpoint

Read report request information

Get details for and the state of a specific analytics report request.

App Store Connect API 3.4+

URL

`GET https://api.appstoreconnect.apple.com/v1/analyticsReportRequests/{id}`

Path Parameters

id string	**(Required)** The opaque resource ID that uniquely identifies the Apps resource. Obtain the app resource ID from the <u>Read report requests</u> response.

Query Parameters

fields[analytics ReportRequests] [string]	Possible Values: `accessType`, `stoppedDueToInactivity`, `reports`
fields[analytics Reports] [string]	Possible Values: `name`, `category`, `instances`
include [string]	Value: `reports`
limit[reports] integer	Maximum: 50

Response Codes

200   **OK**
AnalyticsReport   Content-Type: application/json
RequestResponse

400   **Bad Request**
ErrorResponse   Content-Type: application/json

401   **Unauthorized**
ErrorResponse   Content-Type: application/json

403   **Forbidden**
ErrorResponse   Content-Type: application/json

404   **Not Found**
ErrorResponse   Content-Type: application/json

429   ErrorResponse
Content-Type: application/json

Mentioned in

📄 Downloading Analytics Reports

Discussion

> **Note**
>
> If you don't retrieve data for a long time, a report request changes to `stoppedDueTo Inactivity`. You need to make a new request to resume getting reports.

Examples Request and Response

Request   Response

```
GET https://api.appstoreconnect.apple.com/v1/analyticsReportRequests/d48c69c5-9bcb-4
```

See Also

Making, Reading, and Deleting Requests

`Request reports`

Request analytics reports for your apps.

`Read report requests`

Read analytics report requests for a specific app.

`Read reports for a specific request`

Get a list of reports generated from a specific analytics report request.

`Read reports Ids for a specific request`

Get a list of reports Ids from a specific analytics report request.

`Delete a report request`

Remove a specific analytics report request.