

[Accelerate](#) / BNNSGraphContextMake(\_:)

## Function

# BNNSGraphContextMake(\_:)

Returns an allocated and initialized graph context from the specified graph.

iOS 18.0+ | iPadOS 18.0+ | Mac Catalyst 18.0+ | macOS 15.0+ | tvOS 18.0+ | visionOS 2.0+ | watchOS 11.0+

```
func BNNSGraphContextMake(_ graph: bnns_graph_t) -> bnns_graph_context_t
```

## Parameters

### graph

The compiled graph object.

## Return Value

A compiled graph context object. If the operation fails, the graph object's [data](#) property is `nil`.

## Discussion

To prevent memory leaks, call [BNNSGraphContextDestroy\(\\_:\)](#) when you're finished using the graph context.

## See Also

Creating and destroying a context

```
struct bnns_graph_context_t
```

An object that wraps a compiled graph object.

```
func BNNSGraphContextMakeStreaming(bnns_graph_t, UnsafePointer<CChar>?,  
Int, UnsafePointer<BNNSTensor>?) -> bnns_graph_context_t
```

Returns an allocated and initialized graph context with streaming support from the specified graph.

```
func BNNSGraphContextDestroy(bnns_graph_context_t)
```

Destroys the specified graph context.