

[SwiftUI](#) / [ScrollView](#)

Structure




ScrollView

A scrollable view.

iOS 13.0+ | iPadOS 13.0+ | Mac Catalyst 13.0+ | macOS 10.15+ | tvOS 13.0+ | visionOS 1.0+ | watchOS 6.0+

```
struct ScrollView<Content> where Content : View
```

Mentioned in

-  Picking container views for your content
-  Creating performant scrollable stacks
-  Grouping data with lazy stack views

Overview

The scroll view displays its content within the scrollable content region. As the user performs platform-appropriate scroll gestures, the scroll view adjusts what portion of the underlying content is visible. `ScrollView` can scroll horizontally, vertically, or both, but does not provide zooming functionality.

In the following example, a `ScrollView` allows the user to scroll through a [VStack](#) containing 100 [Text](#) views. The image after the listing shows the scroll view's temporarily visible scrollbar at the right; you can disable it with the `showsIndicators` parameter of the `ScrollView` initializer.

```
var body: some View {
    ScrollView {
        VStack(alignment: .leading) {
            ForEach(0..<100) {
                Text("Row \($0)")
            }
        }
    }
}
```

```
}  
  }  
}
```

```
Row 0  
Row 1  
Row 2  
Row 3  
Row 4  
Row 5  
Row 6  
Row 7  
Row 8  
Row 9  
Row 10  
Row 11  
Row 12  
Row 13  
Row 14  
Row 15  
Row 16  
Row 17
```

Controlling Scroll Position

You can influence where a scroll view is initially scrolled by using the `defaultScrollAnchor(_:)` view modifier.

Provide a value of ``UnitPoint/center`` to have the scroll view start in the center of its content when a scroll view is scrollable in both axes.

```
ScrollView([.horizontal, .vertical]) {  
    // initially centered content  
}  
  
.defaultScrollAnchor(.center)
```

Or provide an alignment of ``UnitPoint/bottom`` to have the scroll view start at the bottom of its content when a scroll view is scrollable in its vertical axes.

```
ScrollView {  
    // initially bottom aligned content  
}  
  
.defaultScrollAnchor(.bottom)
```

After the scroll view initially renders, the user may scroll the content of the scroll view.

To perform programmatic scrolling, wrap one or more scroll views with a [ScrollViewReader](#).

Topics

Creating a scroll view

~~`init(Axis.Set, showsIndicators: Bool, content: () -> Content)`~~

Creates a new instance that's scrollable in the direction of the given axis and can show indicators while scrolling.

Deprecated

`init(Axis.Set, content: () -> Content)`

Creates a new instance that's scrollable in the direction of the given axis and can show indicators while scrolling.

Configuring a scroll view

`var content: Content`

The scroll view's content.

`var axes: Axis.Set`

The scrollable axes of the scroll view.

`var showsIndicators: Bool`

A value that indicates whether the scroll view displays the scrollable component of the content offset, in a way that's suitable for the platform.

Supporting types

`var body: some View`

The content and behavior of the scroll view.

Relationships

Conforms To

View

See Also

Creating a scroll view

`struct ScrollViewReader`

A view that provides programmatic scrolling, by working with a proxy to scroll to known child views.

`struct ScrollViewProxy`

A proxy value that supports programmatic scrolling of the scrollable views within a view hierarchy.