

[ProximityReader](#) / PaymentCardVerificationRequest

Structure

PaymentCardVerificationRequest

A request to verify details for a contactless payment card.

iOS 15.4+ | iPadOS 15.4+ | Mac Catalyst 17.0+

```
struct PaymentCardVerificationRequest
```

Overview

Create a `PaymentCardVerificationRequest` object to verify details of a person's payment card before performing a transaction with that card. For example, you might use a verification request to make sure the person's card supports a specific currency. After creating a request object, pass it to the `readPaymentCard\(_:\)` or `readPaymentCard\(_:vasRequest:stopOnVASResult:\)` method of your session to read the card details.

Topics

Creating the verification request

```
init(currencyCode: String, for: PaymentCardVerificationRequest.Reason)
```

Creates a new verification request using the specified currency and reason information.

Getting the request details

```
let currencyCode: String
```

The ISO 4217 code that indicates the currency type.

```
let verificationReason: PaymentCardVerificationRequest.Reason
```

The reason you asked to verify someone's card.

```
enum Reason
```

The reason for the verification request.

Setting the user interface language

```
var userInterfaceLanguage: Locale.Language?
```

The language to use when localizing the user interface.

Relationships

Conforms To

Sendable, SendableMetatype

See Also

Payment requests

```
struct PaymentCardTransactionRequest
```

A request for a contactless purchase or refund that includes the purchase amount and currency information.

```
struct PaymentCardReadResult
```

The result of a payment card read operation.