

## □ Documentation

---

[App Data Transfer](#) / Get recurring request download URLs

Web Service Endpoint

# Get recurring request download URLs

Get URLs to download a snapshot of someone's data specific to your app from a recurring series.

App Data Transfer 1.0+

---

## URL

**GET** `https://appdatatransfer.apple.com/api/transfer/appdata/fetch/{parentRequestId}/`

## Path Parameters

**requestId**     **(Required)** A UUID that identifies the individual download request in the recurring sequence.  
string

**parentRequestId**     **(Required)** A UUID that identifies the recurring sequence of download requests.  
string

## Response Codes

**200**     **OK**  
[DownloadLinks](#)     Content-Type: application/json

**400**     **Bad Request**  
[DownloadError](#)     Content-Type: application/json

**401**     **Unauthorized**

**403**     **Forbidden**

# Overview

Request Response

---

```
% curl -X GET \  
-H "Authorization: Bearer [ACCESS_TOKEN]" \  
-H "X-Apple-Transaction-Id: E3857B28-7FC4-41C8-AC54-08E121E26F59" \  
-H "Accept: application/json" \  
https://appdatatransfer.apple.com/api/transfer/appdata/fetch/EABD06C0-9210-47FF-83
```

---

## See Also

### Downloads

[Get one-time request download URLs](#)

Get URLs to retrieve someone's data.

[object DownloadLinks](#)

An object that contains URLs to download someone's data specific to your app.

[object DownloadError](#)

An object that describes an error the server encounters while preparing download URLs for a request.