

[AccessorySetupKit](#) / [ASMigrationDisplayItem](#)

## Class

# ASMigrationDisplayItem

A previously-discovered accessory as presented by the discovery picker, for use when migrating it to `AccessorySetupKit`.

iOS 18.0+ | iPadOS 18.0+

```
class ASMigrationDisplayItem
```

## Mentioned in

 [Discovering and configuring accessories](#)

## Overview

Create instances of `ASMigrationDisplayItem` by calling the superclass's initializer `init(name:productImage:descriptor:)`, then specify the Bluetooth peripheral Identifier, the Wi-Fi hotspotSSID, or both, for the specific accessory you want to migrate.

## Topics

### Accessory identifiers

```
var peripheralIdentifier: UUID?
```

The Bluetooth identifier of the accessory to migrate.

```
var hotspotSSID: String?
```

The Wi-Fi hotspot SSID of the accessory to migrate.

```
var wifiAwarePairedDeviceID: ASAccessory.WiFiAwarePairedDeviceID
```

The Wi-Fi Aware paired device identifier of the accessory to migrate.

---

## Relationships

### Inherits From

`ASPickerDisplayItem`

### Conforms To

`CVarArg`

`CustomDebugStringConvertible`

`CustomStringConvertible`

`Equatable`

`Hashable`

`NSObjectProtocol`

`Sendable`

`SendableMetatype`

---

## See Also

### Displaying picker items

```
class ASPickerDisplayItem
```

An accessory as presented by the discovery picker.

```
class ASDiscoveredDisplayItem
```

A picker display item created from customizing a discovered accessory.