

□ Documentation

[Apple Music API](#) / Get Multiple Library Resources Using Resource-Typed ID Parameters

Web Service Endpoint

Get Multiple Library Resources Using Resource-Typed ID Parameters

Fetch one or more library resources by using their identifiers.

Apple Music 1.0+

URL

GET `https://api.music.apple.com/v1/me/library`

Query Parameters

include [string]	Additional relationships to include in the fetch.
l string	The localization to use, specified by a language tag. The possible values are in the supportedLanguageTags array belonging to the Storefront object specified by storefront. Otherwise, the default is defaultLanguageTag in Storefront.
extend [string]	A list of attribute extensions to apply to resources in the response.
ids[library-songs] [string]	The unique identifiers for the library songs.
ids[library-playlists] [string]	The unique identifiers for the library playlists.

ids[library-playlist-folders] [string]	The unique identifiers for the library playlist folders.
ids[library-music-videos] [string]	The unique identifiers for the library music videos.
ids[library-artists] [string]	The unique identifiers for the library artists.
ids[library-albums] [string]	The unique identifiers for the library albums.

Response Codes

200 ResourceCollection Response	OK The request was successful. Content-Type: application/json
401 UnauthorizedResponse	Unauthorized A response indicating an incorrect Authorization header. Content-Type: application/json
403 ForbiddenResponse	Forbidden A response indicating invalid or insufficient authentication. Content-Type: application/json
500 ErrorsResponse	Internal Server Error A response indicating an error occurred on the server. Content-Type: application/json

Discussion

If successful, the HTTP status code is 200 (OK) and the data array contains the requested resource object. If unsuccessful, the HTTP status code indicates the error and the details are in the `errors` array.

This endpoint requires a music user token. For more information, see [User Authentication for MusicKit](#).

Example

```
https://api.music.apple.com/v1/me/library?ids[library-songs]=i.gelNOzPuL41Lxo
```

See Also

Related Documentation

object Resource

A resource—such as an album, song, or playlist.

Fetching Multiple Resource Types

Get Multiple Catalog Resources Using Resource-Typed ID Parameters

Fetch one or more catalog resources by using their identifiers.