

[Accelerate](#) / [...](#) / [vImage Operations](#) / Applying projective transformations to images

API Collection

Applying projective transformations to images

Warp images in three dimensions.

Topics

Computing a projective transformation from source and destination quadrilaterals

 Transforming an image in three dimensions

Create and use a projective transformation to apply a perspective warp to an image.

```
func vImageGetPerspectiveWarp(UnsafePointer<(Float, Float)>, UnsafePointer<(Float, Float)>, UnsafeMutablePointer<vImage_PerpsectiveTransform>, vImage_Flags) -> vImage_Error
```

Returns a projective-transformation structure that defines the mapping between a source quadrilateral and a destination quadrilateral.

```
struct vImage_PerpsectiveTransform
```

A projective-transformation matrix.

Warping planar buffers

```
func vImagePerspectiveWarp_Planar8(UnsafePointer<vImage_Buffer>, UnsafePointer<vImage_Buffer>, UnsafeMutableRawPointer!, UnsafePointer<vImage_PerpsectiveTransform>, vImage_WarpInterpolation, Pixel_8, vImage_Flags) -> vImage_Error
```

Applies a perspective warp to an 8-bit planar image.

```
func vImagePerspectiveWarp_Planar16F(UnsafePointer<vImage_Buffer>,
UnsafePointer<vImage_Buffer>, UnsafeMutableRawPointer!, UnsafePointer<v
Image_PerpsectiveTransform>, vImage_WarpInterpolation, Pixel_16F, v
Image_Flags) -> vImage_Error
```

Applies a perspective warp to a floating-point 16-bit planar image.

```
func vImagePerspectiveWarp_Planar16U(UnsafePointer<vImage_Buffer>,
UnsafePointer<vImage_Buffer>, UnsafeMutableRawPointer!, UnsafePointer<v
Image_PerpsectiveTransform>, vImage_WarpInterpolation, Pixel_16U, v
Image_Flags) -> vImage_Error
```

Applies a perspective warp to a unsigned 16-bit planar image.

Warping interleaved buffers

```
func vImagePerspectiveWarp_ARGB8888(UnsafePointer<vImage_Buffer>,
UnsafePointer<vImage_Buffer>, UnsafeMutableRawPointer!, UnsafePointer<v
Image_PerpsectiveTransform>, vImage_WarpInterpolation, UnsafeMutable
Pointer<UInt8>!, vImage_Flags) -> vImage_Error
```

Applies a perspective warp to an 8-bit-per-channel, four-channel interleaved image.

```
func vImagePerspectiveWarp_ARGB16F(UnsafePointer<vImage_Buffer>, Unsafe
Pointer<vImage_Buffer>, UnsafeMutableRawPointer!, UnsafePointer<vImage
_PerpsectiveTransform>, vImage_WarpInterpolation, UnsafeMutablePointer<
UInt16>!, vImage_Flags) -> vImage_Error
```

Applies a perspective warp to a floating-point 16-bit , four-channel interleaved image.

```
func vImagePerspectiveWarp_ARGB16U(UnsafePointer<vImage_Buffer>, Unsafe
Pointer<vImage_Buffer>, UnsafeMutableRawPointer!, UnsafePointer<vImage
_PerpsectiveTransform>, vImage_WarpInterpolation, UnsafeMutablePointer<
UInt16>!, vImage_Flags) -> vImage_Error
```

Applies a perspective warp to an unsigned 16-bit , four-channel interleaved image.

See Also

Applying geometric transforms to image buffers



Resampling in vImage

Learn how vImage resamples image data during geometric operations.

☰ Applying affine transformations to images

Translate, rotate, and scale images.

☰ Image reflection

Reflect images horizontally and vertically.

☰ Image shearing

Shear images horizontally and vertically.

☰ Image rotation

Rotate images by arbitrary angles or by multiples of 90 degrees.

☰ Image scaling

Scale interlaced and planar images.

☰ Getting the Buffer Size

Calculate the size of the temporary buffer needed by a high-level geometry functions.