

## □ Documentation

---

[Account Data Transfer](#) / Get recurring request download URLs

Web Service Endpoint

# Get recurring request download URLs

Get URLs to download a snapshot of someone's data from a recurring series.

Account Data Transfer 1.0+

---

## URL

```
GET https://accountdatatransfer.apple.com/api/transfer/accountdata/fetch/{parentReq
```

## Path Parameters

**requestId** **string** **(Required)** A UUID that identifies the individual download request in the recurring sequence.

**parentRequestId** **string** **(Required)** A UUID that identifies the recurring sequence of download requests.

## Response Codes

**200** **OK**  
[DownloadLinks](#) Content-Type: application/json

**400** **Bad Request**  
[DownloadError](#) Content-Type: application/json

**401** **Unauthorized**

**403** **Forbidden**

**500** **Internal Server Error**

# Overview

Request      Response

---

```
% curl -X GET \  
-H "Authorization: Bearer [ACCESS_TOKEN]" \  
-H "X-Apple-Transaction-Id: E3857B28-7FC4-41C8-AC54-08E121E26F59" \  
-H "Accept: application/json" \  
https://accountdatatransfer.apple.com/api/transfer/accountdata/fetch/EABD06C0-9216
```

---

## See Also

### Downloads

[Get one-time request download URLs](#)

Get URLs to retrieve someone's data.

[object DownloadLinks](#)

An object that contains URLs to download someone's account data.

[object DownloadError](#)

An object that describes an error the server encounters preparing download URLs for a request.