

[Account & Organization...](#) / ErrorResponse

Dictionary

ErrorResponse

The error object returned after an unsuccessful request.

AccountOrganizationalDataSharing 1.0+

object ErrorResponse

Properties

error string	A string that describes the reason for the unsuccessful request. The string is one of the allowed values, listed below. Possible Values: <code>invalid_request</code> , <code>invalid_client</code> , <code>invalid_grant</code> , <code>unauthorized_client</code> , <code>unsupported_grant_type</code> , <code>invalid_scope</code>
------------------------	---

Attributes

Possible types:

Overview

The error property is one of the following values:

`invalid_request`

A malformed request, typically because it's missing a parameter, contains an unsupported parameter, includes multiple credentials, or uses more than one mechanism for authenticating the client.

`invalid_client`

The client authentication failed, typically due to a mismatched or invalid client identifier, invalid client secret (expired token, malformed claims, or invalid signature), or mismatched or invalid redirect URL.

`invalid_grant`

The authorization grant or refresh token is invalid, typically due to a mismatched or invalid client identifier, invalid code (expired or previously used authorization code), or invalid refresh token.

`unauthorized_client`

The client isn't authorized to use this authorization grant type.

`unsupported_grant_type`

The authenticated client isn't authorized to use this grant type.

`invalid_scope`

The requested scope is invalid.

See Also

Common objects

`object` JWKSet

A set of JSON web keys.

`object` TokenResponse

The response token object returned on a successful request.