

[GameKit](#) / Encourage progress and competition with leaderboards

Article

Encourage progress and competition with leaderboards

Let players measure their own progress and compare their skills with friends and others.

Overview

Use leaderboards to record player scores, which they can view in their Game Center account and directly in your game using built-in Game Center or custom interfaces. Game Center even encourages engagement by notifying players when their friends pass their scores.



You configure a classic or recurring leaderboard in Xcode and submit scores from your code. A *classic leaderboard* retains the scores until you delete the leaderboard. A *recurring leaderboard* automatically resets the board on the intervals you specify. For example, use a classic leaderboard for the best all-time scores and a recurring leaderboard for periodic competitions.


You can also combine individual leaderboards into sets, creating a hierarchy of leaderboards. For example, use leaderboard sets to aggregate the scores from different levels and configurations in your game. However, once you add a leaderboard set, you need to organize all other individual leaderboards into sets.

For design guidance on all types of leaderboards, see [Human Interface Guidelines > Technologies > Game Center > Leaderboards](#). For additional information on recurring leaderboards, see [Creating recurring leaderboards](#).

Configure and test leaderboards and leaderboard sets

Configure leaderboards in Xcode before accessing them in your code and testing locally with Game Progress Manager. When you're ready to deploy your configuration, sync your updates with App Store Connect. For more information about configuring and testing Game Center features, see [Initializing and configuring Game Center](#).

For each leaderboard you configure, you specify details like the score format, submission type, and whether the data resets and starts again after a period of time. Decide on a style for your leaderboard identifiers, because you won't be able to change them at a later time. Before you begin, have at least one localized name and image, which Game Center presents to the player, ready to upload for a language.



A leaderboard set organizes many leaderboards into a single unit. For example, for a game with many levels, use a leaderboard set to organize the leaderboards for each level. You can have up to 100 leaderboards without using leaderboard sets. When you use leaderboard sets, you can have up to 500 leaderboards across 100 leaderboard sets.

Important

You must have at least one leaderboard for your app before you can create a leaderboard set. If you choose to use leaderboard sets, you must include all future leaderboards in a leaderboard set.


If you add a leaderboard to an unreleased version of your game or sign the game with a development certificate, Game Center annotates the leaderboard with a prerelease indicator. To change a leaderboard's app version, see [Add leaderboards to an app version](#).

Note

If you've already pushed your configuration changes to App Store Connect, removing a leaderboard or leaderboard set from the local configuration file doesn't remove the leaderboard or leaderboard set from App Store Connect.

Use the Game Progress Manager to test leaderboards on your local device before you push the configuration update to App Store Connect. After selecting a leaderboard, you can add players to

the leaderboard with score value. You can also test deep-linking behavior that you associate with a leaderboard.



For more information about the leaderboard properties you can configure, see [Leaderboard properties](#).

Choose a score format

Game Center formats the scores that you submit as integer values depending on the leaderboard configuration you enter in Xcode. On the Add Leaderboard page, choose a score format — such as fixed points, elapsed time, or money — that makes sense for your game. For example, if you choose these formats, Game Center formats the values as follows:

Score format type	Score value	Format result
Fixed Point - To 1 Decimal	1234	123.4
Fixed Point - To 2 Decimals	5678	56.78
Fixed Point - To 3 Decimals	10,000	10.000
Elapsed Time - To the Minute	3623 (seconds)	60:23
Elapsed Time - To the Second	10,000 (seconds)	2:46:40

Add a unit to the score format or choose a currency symbol

You can further format the scores when you add a language to the leaderboard configuration in Xcode. You need to add at least one language to save the leaderboard configuration.

On the Add Language page, append a unit to the score that Game Center formats, such as pts, lbs, or meters, by entering the localized strings for the units in the Score Format Suffix text fields. For money values, you can choose a localized currency symbol from the Score Format menu.

Submit scores to leaderboards

To submit a score to one or more leaderboards, use the `GKLeaderboard` [`submitScore\(_:context:player:leaderboardIDs:completionHandler:\)`](#) class method. Pass one or more leaderboard IDs, as well as the score, context, and player.

```
// Submit a score to one or more leaderboards.
try await GKLeaderboard.submitScore(points,
                                     context: 0,
                                     player: GKLocalPlayer.local,
                                     leaderboardIDs: ["my.leaderboard.id"])
```

If you load all leaderboards using the `GKLeaderboard` [`loadLeaderboards\(IDs:completionHandler:\)`](#) class method, as the next section describes, you can submit the score to specific leaderboards using the [`submitScore\(_:context:player:completionHandler:\)`](#) instance method.

Optionally, use the `context` parameter in both of these methods to store game-specific information. For example, pass a flag that contains information about how the player earned the score, such as the vehicle they drive in a racing game.

If you prefer to submit scores through your own server, see [Game Center leaderboards scores](#).

Fetch leaderboards and leaderboard sets

To fetch one or more individual leaderboards, pass the leaderboard IDs to the `GKLeaderboard` [`loadLeaderboards\(IDs:completionHandler:\)`](#) class method.

```
// Fetch the leaderboards.  
let leaderboards = try await GKLeaderboard.loadLeaderboards(IDs: ["my.leaderboard.id"])
```

To fetch specific occurrences of a recurring leaderboard, use the loadPreviousOccurrence(completionHandler:) instance method.

To fetch leaderboard sets, use the GKLeaderboardSet loadLeaderboardSets(completionHandler:) class method. Then to fetch individual leaderboards in a set, use the loadLeaderboards(handler:) instance method.

Get the scores from leaderboards

To load the scores that the local player and others earn from a leaderboard, use the GKLeaderboard loadEntries(for:timeScope:range:completionHandler:) method.

Filter the scores using the playerScope, timeScope, and range parameters you pass to this method. For example, to get scores that friends of the local player earned in the past week, pass GKLeaderboard.PlayerScope.friendsOnly as the for parameter and GKLeaderboard.TimeScope.week as the timeScope parameter.

```
// Fetch the friend scores.  
let result = try await leaderboard.loadEntries(for: GKLeaderboard.PlayerScope.friendsOnly,  
                                              timeScope: GKLeaderboard.TimeScope.week,  
                                              range: NSMakeRange(1, 100))
```

To get all player scores in that time period, pass GKLeaderboard.PlayerScope.global as the for parameter instead.

Then use the properties of the GKLeaderboard.Entry instances that this method returns to get details about the individual scores, including the players who earned them.

Display leaderboards

To display a leaderboard or leaderboard set in your custom game interface, load the leaderboard or leaderboard set and use the title property to get the localized name. To get the image representation that you upload to App Store Connect, use the loadImage(completionHandler:) method.

```
// Load the leaderboard image.  
let image = try await leaderboard.loadImage()
```

Alternatively, display the leaderboard in the familiar Game Center interface. To learn more, see [Display a single leaderboard](#).

Set the default leaderboard

You can set the default leaderboard for an individual player during your game. For example, change the default leaderboard when the player advances to a different level in your game.

To change the local player's default leaderboard, use the `GKLocalPlayer` [`setDefaultLeaderboardIdentifier\(_:completionHandler:\)`](#) method. To get the identifier for the default leaderboard in your code, use the [`loadDefaultLeaderboardIdentifier\(completionHandler:\)`](#) method.

Otherwise, you set the default leaderboard for all players in App Store Connect when you configure leaderboards. Xcode doesn't support setting a default leaderboard. For the steps to change the default leaderboard in App Store Connect, see [Configure leaderboards and achievements > Set a default leaderboard](#).

See Also

Leaderboards



Creating recurring leaderboards

Create a leaderboard for your game that ranks player scores based on a schedule.



Adding Recurring Leaderboards to Your Game

Encourage competition in your games by adding leaderboards that have a duration and repeat.

`class` `GKLeaderboard`

A leaderboard for a game that Game Center stores.

`class` `GKLeaderboardSet`

Organizes leaderboards into logical and coherent groups.

`class` `GKLeaderboardScore`

Information about a player's score on a leaderboard.