

[Accelerate](#) / Integrating vImage pixel buffers into a Core Image workflow

Sample Code

Integrating vImage pixel buffers into a Core Image workflow

Share image data between Core Video pixel buffers and vImage buffers to integrate vImage operations into a Core Image workflow.

Download

macOS 13.0+ | Xcode 14.3+

Overview

vImage supports reading from and writing to Core Video pixel buffers. This sample implements ends-in contrast stretching using vImage and makes that operation available to Core Image workflows by subclassing `CIImageProcessorKernel`. An image processor kernel uses Core Video pixel buffers for input and output, so the app creates vImage pixel buffers that share data with `CVPixelBuffer` instances.

The example below shows a photograph before (left) and after (right) the app has applied ends-in contrast stretching:



To learn more about ends-in contrast stretching, see [Enhancing image contrast with histogram manipulation](#).

Before exploring the code, try building and running the app to familiarize yourself with the effect of the different parameters on the image.

Define an ends-in contrast-stretch image processor kernel

The `ContrastStretchImageProcessorKernel` inherits from the Core Image `CIIImageProcessorKernel` class.

The sample code defines a `vImage_CGImageFormat` structure that represents a four-channel, 8-bit-per-channel interleaved image format. The image processor kernel supports `kCIFORMatR8`, `kCIFORMatBGRA8`, `kCIFORMatRGBA8`, and `kCIFORMatRGBA8` input and output formats. For this sample project, the code overrides `outputFormat` and `formatForInput(at:)` to return a BGRA8 that's the same as the `bitmapInfo` property of the `vImage_CGImageFormat` structure.

```
static var cgImageFormat = vImage_CGImageFormat(
    bitsPerComponent: 8,
    bitsPerPixel: 32,
    colorSpace: nil,
    bitmapInfo: CGBitmapInfo(rawValue: CGImageAlphaInfo.last.rawValue),
    version: 0,
    decode: nil,
    renderingIntent: .defaultIntent)

override class var outputFormat: CIFORMat {
    return CIFORMat.BGRA8
}

override class func formatForInput(at input: Int32) -> CIFORMat {
    return CIFORMat.BGRA8
}
```

Create the source pixel buffer

When the app applies ends-in contrast stretching, Core Image calls the processor kernel's `process(with:arguments:output:)` function. The following code ensures that the input and output `CVPixelBuffer` instances are available:

```
guard
    let input = inputs?.first,
    let inputPixelFormat = input.pixelBuffer,
    let outputPixelFormat = output.pixelBuffer else {
        return
    }
```

The source `vImage.PixelBuffer` shares its memory with the input `CVPixelFormat`. The following code creates a `vImageConverter` that allows the pixel buffer to reference the Core Video buffer's memory:

```
CVPixelFormatLockBaseAddress(inputPixelFormat,
                             CVPixelFormatLockFlags.readOnly)

defer {
    CVPixelFormatUnlockBaseAddress(inputPixelFormat,
                                   CVPixelFormatLockFlags.readOnly)
}

guard let cvImageFormat = vImageCVImageFormat.make(buffer: inputPixelFormat) else {
    throw ContrastStretchImageProcessorKernelError.unableToDeriveImageFormat
}

if cvImageFormat.colorSpace == nil {
    cvImageFormat.colorSpace = CGColorSpaceCreateDeviceRGB()
}

guard let converter = try? vImageConverter.make(
    sourceFormat: cvImageFormat,
    destinationFormat: cgImageFormat) else {
    throw ContrastStretchImageProcessorKernelError.vImageConverterCreationFailed
}

let sourcePixelFormat = vImage.PixelBuffer<vImage.Interleaved8x4>(
    referencing: inputPixelFormat,
    converter: converter)
```

Create the destination pixel buffer

The sample code app uses the same `vImageConverter` to create the destination pixel buffer, which shares memory with the output Core Video buffer's memory.

```

CVPixelBufferLockBaseAddress(outputPixelBuffer,
                              CVPixelBufferLockFlags.readOnly)

defer {
    CVPixelBufferUnlockBaseAddress(outputPixelBuffer,
                                   CVPixelBufferLockFlags.readOnly)
}

let destinationPixelBuffer = vImage.PixelBuffer<vImage.Interleaved8x4>(
    referencing: outputPixelBuffer,
    converter: converter)

```

Apply ends-in contrast stretching

The `vImageEndsInContrastStretch_ARGB8888(_:_:_:_:_)` function applies an ends-in contrast-stretch operation to the source pixel buffer and writes the result to the destination pixel buffer. This function works equally well on all channel orderings; for example, RGBA or BGRA.

```

let error = sourcePixelBuffer.withUnsafePointerToVImageBuffer { src in
    destinationPixelBuffer.withUnsafePointerToVImageBuffer { dst in

        return vImageEndsInContrastStretch_ARGB8888(
            src,
            dst,
            [UInt32](repeating: UInt32(percentLow), count: 4),
            [UInt32](repeating: UInt32(percentHigh), count: 4),
            vImage_Flags(kvImageNoFlags))

    }
}

```

Because the destination pixel buffer shares memory with the output Core Video pixel buffer, the operation is complete after the `vImageEndsInContrastStretch_ARGB8888(_:_:_:_:_)` returns.

Apply the ends-in contrast stretching operation to an image

The `apply(withExtent:inputs:arguments:)` method generates a `CIIImage` instance based on the output of the processor's `process(with:arguments:output:)` function.

```
let ciResult = try? ContrastStretchImageProcessorKernel.apply(  
    withExtent: ciImage.extent,  
    inputs: [ciImage],  
    arguments: ["percentLow": Int(percentLow),  
               "percentHigh": Int(percentHigh)])
```

See Also

Core Video Interoperation

- { } Using vImage pixel buffers to generate video effects
Render real-time video effects with the vImage Pixel Buffer.
- { } Applying vImage operations to video sample buffers
Use the vImage convert-any-to-any functionality to perform real-time image processing of video frames streamed from your device's camera.
- { } Improving the quality of quantized images with dithering
Apply dithering to simulate colors that are unavailable in reduced bit depths.
- ☰ Core Video interoperability
Pass image data between Core Video and vImage.