

[ProximityReader](#) / [MobileDriversLicenseRawDataRequest](#)

## Structure

# MobileDriversLicenseRawDataRequest

A mobile driver's license request which retrieves elements from the holder and returns the raw response data for processing.

iOS 17.0+ | iPadOS 17.0+ | Mac Catalyst 17.0+ | visionOS 1.0+

```
struct MobileDriversLicenseRawDataRequest
```

## Topics

### Creating a raw data request

```
init(retainedElements: [MobileDriversLicenseRawDataRequest.Element],  
nonRetainedElements: [MobileDriversLicenseRawDataRequest.Element])
```

Returns a mobile driver's license raw data request.

```
var retainedElements: [MobileDriversLicenseRawDataRequest.Element]
```

The document elements you're requesting and intend to retain for an indefinite period of time.

```
var nonRetainedElements: [MobileDriversLicenseRawDataRequest.Element]
```

The document elements you're requesting and intend to retain no longer than is necessary to process the result in realtime.

```
struct Element
```

A type representing an element that you can request from a mobile driver's license.

### Handling the response

```
struct Response
```

A type that contains the response information from a successful mobile driver's license raw data request.

## Default Implementations

≡ MobileDocumentRequest Implementations

---

## Relationships

### Conforms To

Copyable  
Equatable  
Hashable  
MobileDocumentRawDataRequest  
MobileDocumentRequest  
Sendable  
SendableMetatype

---

## See Also

### Mobile document requests

```
struct MobileDriversLicenseDisplayRequest
```

A mobile driver's license request that retrieves elements from the holder and displays the results onscreen for visual inspection.

```
struct MobileDriversLicenseDataRequest
```

A mobile driver's license request that retrieves elements from the holder and returns the validated document elements.

```
struct MobileNationalIDCardDisplayRequest
```

A mobile national ID card request that retrieves elements from the holder and displays the results onscreen for visual inspection.

```
struct MobileNationalIDCardDataRequest
```

A mobile national ID card request that retrieves elements from the holder and returns the validated document elements.

```
struct MobileNationalIDCardRawDataRequest
```

A mobile national ID card request which retrieves elements from the holder and returns the raw response data for processing.

```
struct MobileDocumentDisplayRequest
```

A mobile document request that retrieves elements from the holder and displays the results onscreen for visual inspection.

```
protocol MobileDocumentRequest
```

A type that represents a mobile document request.

```
protocol MobileDocumentDataRequest
```

A type that represents a mobile document data request.

```
protocol MobileDocumentRawDataRequest
```

A type that represents a mobile document raw data request.

```
struct MobilePhotoIDDataRequest
```

A photo ID request that retrieves elements from the holder and returns the validated document elements.

```
struct MobilePhotoIDRawDataRequest
```

A photo ID request which retrieves elements from the holder and returns the raw response data for processing.

```
struct MobileDocumentAnyOfDataRequest
```

A type that describes a data request for any mobile document from a group of requests.

```
struct MobileDocumentAnyOfRawDataRequest
```

A type that describes a raw data request for any mobile document from a group of requests.