

[XCUIAutomation](#) / XCUISiriService

Class

XCUISiriService

A proxy that simulates a device's Siri interface.

iOS 10.3+ | iPadOS 10.3+ | Mac Catalyst 10.3+ | Xcode 16.3+

```
@MainActor
class XCUISiriService
```

Overview

This class allows issuing textual queries and producing element queries for UI shown by Siri.

Topics

Siri activation

```
func activate(voiceRecognitionText: String)
```

Presents the Siri UI, if it's not currently active, and accepts a string that is then processed as if it's recognized speech.

Siri proxy state

```
var debugDescription: String
```

Provides debugging information about the element representing the root of the Siri UI.

Relationships

Inherits From

NSObject

Conforms To

CVarArg

Copyable

CustomDebugStringConvertible

CustomStringConvertible

Equatable

Hashable

NSObjectProtocol

Sendable

XCUIElementTypeQueryProvider

See Also

Related Documentation

```
var siriService: XCUISiriService
```

An object that represents the Siri interface on the device.

Device simulation

```
class XCUIDevice
```

A proxy that can simulate physical buttons, device orientation, and Siri interaction for an iOS, watchOS, or tvOS device.

```
class XCUISystem
```

A proxy that provides an interface to OS-specific properties and actions.