GET

Get the list

Method	Request URL			
GET ▾	http://localhost:8012/mihailrest/	▾	**SEND**	⋮

Parameters ^

Headers	Variables

⧉ ‹ › Toggle source mode   + Insert headers set

Header name	Header value			
Content-Type	application/json	✕	✏	❓

ADD HEADER

A✓   Headers size: 30 bytes

200 OK 8.60 ms   DETAILS ⌄

⧉ ⬇ ‹ › 👁

```
<!DOCTYPE html>

[
    {
        "id":"11",
        "name":"Prepare the lab1 for march23",
        "completed": false
    },
    {
        "id":"21",
        "name":"Submit the test for Programming languages next week",
        "completed": false
    },
    {
```

POST

```
{"id":"41","name":"Pay the bills"}
```

☰ **Request**

Method
POST ▾

Request URL
http://localhost:8012/mihailrest/   ▾   **SEND**   ⋮

Parameters ∧

Headers	Body	Variables

Body content type
application/json ▾

Editor view
Raw input ▾

FORMAT JSON   MINIFY JSON

```
{"id":"41","name":"Pay the bills"}
```

200 OK 7.10 ms   DETAILS ∨

🗐 ⬇ <> 👁

```
<!DOCTYPE html>
```

PUT

Add / Replace

`{"id":"41","name":"Pay the bills"}`

Method	Request URL		
POST ▾	http://localhost:8012/mihailrest/	▾	SEND ⋮

Parameters ∧

Headers	Body	Variables

Body content type	Editor view
application/json ▾	Raw input ▾

FORMAT JSON   MINIFY JSON

```
{"id":51,"name":"Pay the bills"}
```

200 OK 5.90 ms   DETAILS ∨

DELETE

Method	Request URL		
DELETE ▾	http://localhost:8012/mihailrest	▾	SEND ⋮

Parameters ∧

Headers	Body	Variables

⟨⟩ Toggle source mode   + Insert headers set

Header name	Header value		
Content-Type	application/json	× ✎ ❓

ADD HEADER

A↗   Headers size: 30 bytes

301 Moved Permanently 3.60 ms   DETAILS ∨

```
<!DOCTYPE HTML PUBLIC "-//IETF//DTD HTML 2.0//EN">
<html><head>
<title>301 Moved Permanently</title>
</head><body>
<h1>Moved Permanently</h1>
<p>The document has moved <a href="http://localhost:8012/mihailrest/">here</a>.</p>
<hr>
<address>Apache/2.4.51 (Win64) OpenSSL/1.1.11 PHP/7.4.25 Server at localhost Port 8012</address>
</body></html>
```