Odsek Visoka ICT škola, Akademija tehničko-umetničkih strukovnih studija, Beograd

Furnishop

Smer: Internet tehnologije

Modul: Web programiranje

Predmet: Web programiranje PHP 2

Mihailo Ilić 41/19

Sadržaj

1. Uvod	7
1.1 Korišćeni programski jezici/tehnologije	7
1.2 Opis funkcionalnosti	7
1.2 Template	9
2. Organizacija	9
2.1 Šema baze podataka	10
2.2 Struktura projekta	11
2.2.1 app	11
2.2.2 database	12
2.2.3 public	13
2.2.4 resources	14
2.2.5 Ostatak projekta	15
2.3 Slike stranica i opisi funkcionalnosti	16
2.3.1 Home	16
2.3.2 Shop	17
2.3.3 Product	18
2.3.4 Lookbook	19
2.3.5 Sign In	20
2.3.6 Registration	20
2.3.7 Contact	21
2.3.8 About Author	21
2.3.9 cart.php	22
2.3.10 Admin panel - Dashboard	23
2.3.11 Admin panel Logs	23
2.3.12 Admin panel Users	24
2.3.13 Admin panel Lookbook	25
2.3.14 Admin panel – Products	26
2.3.15 Admin panel - Subcategories	27
2.3.16 Admin panel – Collections & Colors	27
3. Kodovi	28

3.1 app/Exceptions	28
3.1.1 Handler.php	28
3.2 app/Http/Controllers	29
3.2.1 AdminCollectionColorController.php	29
3.2.2 AdminController.php	33
3.2.3 AdminDashboardController.php	34
3.2.4 AdminLookbookController.php	35
3.2.5 AdminProductController.php	41
3.2.6 AdminSubcategoryController.php	48
3.2.7 AdminUserController.php	53
3.2.8 BaseController.php	57
3.2.9 CartController.php	58
3.2.10 ContactController.php	62
3.2.11 Controller.php	63
3.2.12 ErrorController.php	63
3.2.13 HomeController.php	64
3.2.14 LogController.php	65
3.2.15 LoginController.php	66
3.2.16 LookbookController.php	68
3.2.17 ProductController.php	68
3.2.18 RegisterController.php	72
3.3 app/Http/Middleware	74
3.3.1 IsAdmin.php	74
3.3.2 IsGuest.php	74
3.3.3 IsUser.php	75
3.3.4 UserLinks.php	76
3.4 app/Http/Requests	77
3.4.1 AdminCreateCollectionCategoryRequest.php	77
3.4.2 AdminCreateLookbookIdeaRequest.php	78
3.4.3 AdminCreatePorductRequest.php	79
3.4.4 AdminCreateSubcateogryRequest.php	80
3.4.5 AdminEditFeaturedCateogry.php	80
3.4.6 AdminEditLookbookIdeaRequest.php	81
3.4.7 AdminEditProductRequest.php	82

3.4.8 AdminEditUserRequest.php	83
3.4.9 LoginRequest.php	84
3.4.10. RegisterRequest.php	85
3.4.11. SendMessageRequest.php	86
3.5 app/Http/Mail	87
3.5.1 ContactForm.php	87
3.6 app/Http/Models	88
3.6.1 Cart	88
3.6.2 Category	89
3.6.3 CategoryProduct	90
3.6.4 Collection	90
3.6.5 Color	90
3.6.6 ColorProduct	91
3.6.7 Image	91
3.6.8 Log	91
3.6.9 LogCategory	92
3.6.10 Lookbook	92
3.6.11 LookbookItem	93
3.6.12 Menu	93
3.6.13 Product	94
3.6.14 Productimage	95
3.6.15 Role	95
3.6.16 SliderImage	95
3.6.17 User	96
3.7 App/Http/View/Components/Product.php	96
3.8 public/js	97
3.8.1 custom.js	97
3.8.2 cart.js	101
3.8.3 product.js	103
3.8.4 shop.js	105
3.9 public/admin-assets/js	110
3.9.1 product.js	110
3.9.2 lookbook.js	114
3.10 resources/views/components/product	117

3.11 resources/views/errors/error	117
3.12 resources/views/main/contact-form	118
3.13 views/resources/admin/layout	119
3.14 views/resources/admin/fixed	119
3.14.1 footer	119
3.14.2 head	120
3.14.3 nav	120
3.14.4 scripts	121
3.14.5 sidebar	121
3.15 views/resources/admin/pages	122
3.15.1 dashboard	122
3.15.2 log	123
3.16 views/resources/admin/pages/collections_colors	126
3.16.1 collections_colors	126
3.16.2 collectoins_colors_create	128
3.17 views/resources/admin/pages/lookbook	130
3.17.1 lookbook	130
3.17.2 lookbook_create_idea	133
3.17.3 lookbook_edit_idea	135
3.18 views/resources/admin/pages/products	138
3.18.1 product_create	138
3.18.2 product_edit	
3.18.3 products	145
3.19 views/resources/admin/pages/subcategories	149
3.19.1 subcategories	149
3.19.2 subcategory_create	152
3.20 views/resources/admin/pages/users	154
3.20.1 user_edit	154
3.20.2 users	155
3.21 views/resources/front/layout	158
3.22 views/resources/front/fixed	159
3.22.1 floating	159
3.22.2 footer	162
3.22.3 head	165

3.22.4 header	166
3.22.5 ie	169
3.22.6 scripts	169
3.23 views/resources/front/pages	169
3.23.1 author	169
3.23.2 contact	171
3.23.3 home	173
3.24 views/resources/front/pages/auth	180
3.24.1 login	180
3.24.2 register	181
3.25 views/resources/front/pages/products	183
3.25.1 lookbook	183
3.25.2 product	186
3.25.3 shop	190
3.26 views/resources/front/pages/user/cart	195
3.27 routes/web.php	199

1. Uvod

1.1 Korišćeni programski jezici/tehnologije

Za potrebe sajta korišćene su sledeće tehnologije:

- HTML, CSS
- Bootstrap
- JavaScript + jQuery
- PHP, Laravel 8
- Apache + MySQL
- PhpStorm

1.2 Opis funkcionalnosti

Domen koji aplikacija pokušava da reši je **onlajn prodavnica nameštaja**. Korisnici mogu da pretražuju i razgledaju proizvode i dodaju ih u korpu. Takođe, mogu da pristupe odeljku sa pripremljenim idejama za uređenje doma gde su označeni svi proizvode koji mogu da se kupe. Administratori su posebni korisnici koji imaju pristup admin panelu, odnosno kompletan pristup unosu, izmeni, brisanju korisnika, proizvoda, potkategorija itd.

Funkcionalnosti sajta se mogu svrstati u sledeće kategorije:

- Organizacija i struktura projekta u skladu sa MVC arhitekturom, koristi se front layout za glavni deo sajta, a potpuno drugi layout za admin panel
- Galerija proizvoda sa dinamičkom stranicom o pojedinačnom proizvodu, a sadržaj se preuzima iz baze
- Filtriranje, pretraga, sortiranje i straničenje proizvoda u galeriji proizvoda, sve se obavlja jednim upitom na osnovu izabranih kriterijuma bez osvežavanja stranice
- Korpa koja je povezana sa korisničkim nalogom, sa ukupnom sumom i opcijama za brisanje i izmenu količine
- Lookbook (odeljak sa idejama za uređenje) za svaku ideju korisniku su označeni proizvodi koje je moguće kupiti i linkovi ka istim
- Registracija i logovanje od strane korisnika, sve se proverava regularnim izrazima, a sve stranice za korisnike/administratore su zaštićene od neautorizovanih posetilaca
- Kontakt forma prosleđivanje poruka na definisanu imejl adresu web aplikacije

- Administratorske funkcionalnosti, obuhvataju stranice gde administratori mogu dodavati i brisati proizvode, potkategorije itd., a takođe imaju uvid i opcije vezane za korisničke naloge i logove
- **Zapisivanje ključnih događaja** poput grešaka u aplikaciji, logovanja i registracije korisnika, kao i dodavanja proizvoda u korpu
- Forme za dodavanje i izmenjivanje proizvoda i ostalih resursa, uključujući i uploadovanje više slika, a unos se proverava i na klijentu i na serveru regularnim izrazima

1.2 Template

Za izradu front dela sajta je korišćen templejt koji se može videti na linku:


Furnitica- Minimalist Furniture HTML Template Preview- ThemeForest

Za izradu admin panela korišćen je templejt koji se može videti na linku:

Light Bootstrap Dashboard: Free Bootstrap 4 Admin Template @ Creative Tim (creativetim.com)


2. Organizacija

2.1 Šema baze podataka




2.2 Struktura projekta


2.2.1 app




2.2.2 database




2.2.3 public



2.2.4 resources




2.2.5 Ostatak projekta




2.3 Slike stranica i opisi funkcionalnosti

2.3.1 Home




Na ovoj stranici se nalazi slajder, za koji su slajdovi dinamički učitani iz baze. Takođe, ovde se nalaze linkovi ka kategorijama i potkategorijama.

Navigacija se učitanava iz baze, a tu su i korisnički linkovi u zavisnosti od toga da li je korisnik administrator, korisnik ili samo posetilac. Za sve stranice namenjene koristnicima ili administratoru vrši se provera u middlewareu i vrši se redirekcija za neautorizovan pristup.



Administrator može izabrati glavnu kategoriju koja će se nalaziti na početnoj stranici, zajedno sa proizvodima i lookbook linkovima, ukoliko ih ima.



Na ovoj stranici se mogu videti svi proizvodi. Sve kategorije, kolekcije, boje i sami proizvodi se čitaju iz baze. Ovo se realizuje preko AJAX-a.


Moguće je filtriranje po kategorijama, kolekcijama i bojama. Tu je i mogućnost sortiranja, pretrage, kao i straničenje.

Za sve ove kriterijume serveru se šalje ajax zahtev i tako dobijaju svi željeni podaci, a lista se osvežava prilikom svake interakcije korisnika sa ovim poljima.

Klikom na drugu kategoriju URL adresa se dinamički pomoću JS prepravlja u onu u skladu sa izabranom kategorijom ali se stranica ne osvežava.


Klikom na proizvod odlazi se na stranicu za više informacija o tom proizvodu.

2.3.3 Product



Ova stranica se dinamički popunjava u zavisnosti od toga koji je proizvod izabran.


Postoji i opcija za dodavanje u korpu zajedno sa količinom, a ako korisnik nije ulogovan onda će klikom na taster doći do redirekcije ka stranici za logovanje.



Na ovoj stranici korisniku se prikazuju ideje u uređenju doma, zajedno sa pinovima. Prelaskom miša preko obeleženg mesta prikazuje se proizvod koji se može kupiti.


Moguće je filtrirati ideje po kategoriji.

2.3.5 Sign In




Na ovoj stranici posetioci se mogu ulogovati, a kredencijali se proveravaju i na klijentu i na serveru.

2.3.6 Registration




Ovde se vrši registracija novih korisnika, sva polja se proveravaju na oba kraja (na serverskoj strani postoji klasa za custom request). Takođe ne mogu se registrovati dva naloga sa istom imejl adresom, a krajnji korisnik će biti obavešten o ishodu registracije.

2.3.7 Contact




Na ovoj stranici moguće je kontaktirati administratore. Sva polja se prvo proveravaju i na klijentskoj i na serverskoj strani. Poruka se šalje mejlom na predefinisanu imejl adresu web aplikacije. Korišćen je Google smtp server.

2.3.8 About Author




2.3.9 cart.php




Na ovoj stranici se vidi sadržaj korpe korisnika (ako nema proizvoda u korpi onda se izdaje takva poruka). Ukupna vrednost se izračunava u JS-u i prikazuje. Preko AJAX-a se realizuje brisanje ili izmena količine.

2.3.10 Admin panel - Dashboard




Ova stranica, kao i sve naredne, namenjena je administratoru. Svaki neautorizovani pristup preko URL adrese sprečava se redirekcijom ka stranici index.php.

2.3.11 Admin panel Logs




2.3.12 Admin panel Users

Ovde se mogu videti korisnici, a moguće je i brisanje i izmena.




2.3.13 Admin panel Lookbook

Ovde se mogu dodavati i brisati nove ideje, a moguća je i izmena pinova.




2.3.14 Admin panel – Products




Ovde se mogu dodavati i izmenjivati proizvodi.

2.3.15 Admin panel - Subcategories



2.3.16 Admin panel – Collections & Colors



3. Kodovi

3.1 app/Exceptions

3.1.1 Handler.php

```
namespace App\Exceptions;
use Illuminate\Foundation\Exceptions\Handler as ExceptionHandler;
use Throwable;
class Handler extends ExceptionHandler
    * @var array<int, class-string<Throwable>>
   protected $dontReport = [
    * @var array<int, string>
   protected $dontFlash = [
    * @return void
   public function register()
        $this->reportable(function (Throwable $e) {
        });
   public function render($request, \Throwable $exception)
        if ($this->isHttpException($exception)) {
           if ($exception->getStatusCode() == 404) {
                return redirect()->route("error", ["code"=>404]);
```

```
return parent::render($request, $exception);
}
```

3.2 app/Http/Controllers

3.2.1 AdminCollectionColorController.php

```
<?php
namespace App\Http\Controllers;
use App\Http\Requests\AdminCreateCollectionCategoryRequest;
use App\Models\Collection;
use App\Models\Color;
use App\Models\Log;
use App\Models\Product;
use Illuminate\Http\Request;
class AdminCollectionColorController extends AdminController
  * Display a listing of the resource.
  * @return \Illuminate\Http\Response
  public function index(Request $request)
    $show = $request->show ?? "collection";
    $items = null;
    if($show == "collection"){
      $items = Collection::query();
    else {
      $items = Color::query();
    $column = "name";
    $order = "asc";
    $sort = request("sort");
    if($sort){
```

```
$column = explode("-", $sort)[0];
    $order = explode("-", $sort)[1];
  $items = $items->orderBy($column, $order);
  $this->data["items"] = $items->paginate(10);
  $this->data["show"] = $show;
  return view("admin.pages.collections_colors.collections_colors", $this->data);
* Show the form for creating a new resource.
* @return \Illuminate\Http\Response
public function create()
  return view("admin.pages.collections colors.collections colors create", $this->data);
* Store a newly created resource in storage.
* @param \Illuminate\Http\Request $request
* @return \Illuminate\Http\Response
public function store(AdminCreateCollectionCategoryRequest $request)
  $table = $request->table;
  $name = $request->name;
  $msg = "Item created successfully";
  $class = "info";
  try {
    if($table == "collections") {
      Collection::create(["name"=>$name]);
    else {
      Color::create(["name"=>$name]);
```

```
catch(\Throwable $ex){
      Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
      $msg = "Internal error";
      $class = "danger";
  return redirect()->route("admin_collection_color.index")->with([
    "message" => $msg,
    "class" => "$class"
 ]);
* Display the specified resource.
* @param int $id
* @return \IIIuminate\Http\Response
public function show($id)
* Show the form for editing the specified resource.
* @param int $id
* @return \Illuminate\Http\Response
public function edit($id)
* Update the specified resource in storage.
* @param \Illuminate\Http\Request $request
* @param int $id
* @return \Illuminate\Http\Response
```

```
public function update(Request $request, $id)
* Remove the specified resource from storage.
* @param int $id
* @return \Illuminate\Http\Response
public function destroy($id)
  $table = request("table");
  if(!$table){
    return redirect()->route("admin_collection_color.index")->with([
      "message" => "Bad parameters",
      "class" => "danger"
    ]);
  $msg = "The item has been successfully removed";
  $class = "info";
  try {
    if($table == "collection"){
      $item = Collection::find($id);
    else {
      $item = Color::find($id);
    if(!$item){
      $msg = "Item not found";
      $class = "danger";
    else {
      $existingProducts = Product::whereHas($table, function($q) use ($item ,$table){
        $q->where(trim($table, "s")."_id", $item->id);
      })->count();
      if($existingProducts) {
```

```
$msg = "There are products assigned to this item";
$class = "danger";
}
else {
    $item->delete();
}

catch(\Throwable $ex){

Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);

$msg = "Internal error";
$class = "danger";
}

return redirect()->route("admin_collection_color.index")->with([
    "message" => $msg,
    "class" => "$class"
]);
}
```

3.2.2 AdminController.php

```
"icon" => "pe-7s-note2",
    "name"=>"Logs",
    "route"=>"admin.log"
 ],
    "icon" => "pe-7s-users",
    "name"=>"Users",
    "route"=>"admin_user.index"
    "icon" => "pe-7s-notebook",
    "name"=>"Lookbook",
    "route"=>"admin_lookbook.index"
  ],
    "icon" => "pe-7s-box2",
    "name"=>"Products",
    "route"=>"admin_product.index"
    "icon" => "pe-7s-folder",
    "name"=>"Subcategories",
    "route"=>"admin_subcategory.index"
 ],
    "icon" => "pe-7s-keypad",
    "name"=>"Collections & Colors",
    "route"=>"admin_collection_color.index"
 ],
];
```

3.2.3 AdminDashboardController.php

```
<?php

namespace App\Http\Controllers;

use App\Http\Requests\AdminEditFeaturedCategory;
use App\Models\Cart;
use App\Models\Category;
</pre>
```

```
use App\Models\Product;
use App\Models\User;
use Illuminate\Support\Facades\Storage;
class AdminDashboardController extends AdminController
  public function index(){
    $this->data["featuredCategory"] = Storage::get("featured_category.txt");
    $this->data["categories"] = Category::whereNull("parent id")
      ->get();
    $this->data["productCount"] = Product::where("active", true)->count();
    $this->data["userCount"] = User::where("role_id", 1)->count();
    $this->data["inCart"] = Cart::sum("quantity");
    return view("admin.pages.dashboard", $this->data);
  public function changeFeaturedCategory(AdminEditFeaturedCategory $request){
    Storage::put("featured_category.txt", "{$request->category}");
    return redirect()->route("admin")->with([
      "message" => "Featured category has been successfully changed",
      "class" => "info"
    ]);
```

3.2.4 AdminLookbookController.php

```
<?php

namespace App\Http\Controllers;

use App\Http\Requests\AdminCreateLookbookIdeaRequest;
use App\Http\Requests\AdminEditLookbookIdeaRequest;
use App\Models\Category;
use App\Models\Log;</pre>
```

```
use App\Models\Lookbook;
use App\Models\Product;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Storage;
class AdminLookbookController extends AdminController
  public function index(Request $request){
    $this->data["categories"] = Category::whereNull("parent_id")
      ->get();
    $lookbook = Lookbook::with("category");
    $category= $request->category;
    if($category){
      $lookbook = $lookbook->where("category_id", $category);
    $column = "created at";
    $order = "desc";
    $sort = request("sort");
    if($sort){
      $column = explode("-", $sort)[0];
      $order = explode("-", $sort)[1];
    $lookbook = $lookbook->orderBy($column, $order);
    $this->data["lookbook"] = $lookbook->paginate(10);
    return view("admin.pages.lookbook.lookbook", $this->data);
  public function create()
    $this->data["categories"] = Category::whereNull("parent_id")
      ->get();
```

```
return view("admin.pages.lookbook.lookbook_create_idea", $this->data);
public function store(AdminCreateLookbookIdeaRequest $request){
  $newIdea = [
    "category_id" => $request->category,
    "name" => $request->name
  ];
  try {
    $image = $request->file("image");
    $newIdea["image"] = $image->store("", ["disk"=>"lookbook"]);
    $ideaObj = Lookbook::create($newIdea);
    return redirect()->route("admin lookbook.edit", ["admin lookbook"=>$ideaObj->id]);
  catch(\Throwable $ex){
    Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
    $msg = "Internal error";
    $class = "danger";
    $route = "admin_lookbook.index";
    return redirect()->route($route)->with([
      "message" => $msg,
      "class" => "$class"
    ]);
public function destroy($id){
```

```
$msg = "The lookbook idea has been successfully removed";
  $class = "info";
  try {
    $idea = Lookbook::find($id);
    if(!$idea){
      $msg = "Lookbook idea not found";
      $class = "danger";
    else {
      $filename = $idea->image;
      $idea->items()->delete();
      $idea->delete();
      Storage::disk("lookbook")->delete($filename);
  catch(\Throwable $ex){
    Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
    $msg = "Internal error";
    $class = "danger";
  return redirect()->route("admin_lookbook.index")->with([
    "message" => $msg,
    "class" => "$class"
 ]);
public function edit($id){
  $idea = Lookbook::where("id", $id)
    ->with("items")
    ->first();
```

```
if(!$idea){
    $msg = "Lookbook idea not found";
    $class = "danger";
    return redirect()->route("admin_lookbook.index")->with([
      "message" => $msg,
      "class" => "$class"
    ]);
  $this->data["idea"] = $idea;
  return view("admin.pages.lookbook.lookbook_edit_idea", $this->data);
public function update(AdminEditLookbookIdeaRequest $request, $id){
  $idea = Lookbook::where("id", $id)
    ->first();
 if(!$idea){
    $msg = "Lookbook idea not found";
    $class = "danger";
    return redirect()->route("admin_lookbook.index")->with([
      "message" => $msg,
      "class" => "$class"
    ]);
  $msg = "Lookbook idea updated successfully";
  $class = "info";
  try {
    $pins = $request->pins ?? [];
    $values = [];
```

```
foreach($pins as $pin){
    $product_id = explode(",", $pin)[2];
    if(!Product::where("id", $product_id)->exists()){
      return redirect()->route("admin_lookbook.edit", ["admin_lookbook"=>$id])->with([
         "message" => "Product ID $product_id doesn't exist",
         "class" => "danger"
      ]);
    $values[] = [
      "lookbook id"=>$idea->id,
      "position_x"=>explode(",", $pin)[0],
      "position_y"=>explode(",", $pin)[1],
      "product_id"=>$product_id
    ];
  $idea->items()->delete();
  $idea->items()->createMany($values);
catch(\Throwable $ex){
  Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
  $msg = "Internal error";
  $class = "danger";
return redirect()->route("admin_lookbook.index")->with([
  "message" => $msg,
  "class" => "$class"
]);
```

```
<?php
namespace App\Http\Controllers;
use App\Http\Requests\AdminCreateProductRequest;
use App\Http\Requests\AdminCreateSubcategoryRequest;
use App\Http\Requests\AdminEditProductRequest;
use App\Models\Category;
use App\Models\Collection;
use App\Models\Color;
use App\Models\Image;
use App\Models\Log;
use App\Models\Product;
use App\Models\ProductImage;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
class AdminProductController extends AdminController
  * Display a listing of the resource.
  * @return \Illuminate\Http\Response
  public function index()
    $this->data["categories"] = Category::whereNull("parent_id")
      ->with("subcategories")
      ->get();
    $products = Product::where("active", true)
      ->with("images")
      ->with("colors")
      ->with("collection")
      ->with("categories");
    $category_id = request("category");
    if($category_id){
```

```
$products = $products->whereHas("categories", function($q) use ($category_id){
      $q->where("category_id", $category_id)
      ->orWhere("parent_id", $category_id);
   });
 $keywords = request("keywords");
 if($keywords){
    $products = $products->where("name", "like", "%$keywords%");
 $column = "created_at";
 $order = "desc";
 $sort = request("sort");
 if($sort){
    $column = explode("-", $sort)[0];
    $order = explode("-", $sort)[1];
 $products = $products->orderBy($column, $order);
 $this->data["products"] = $products->paginate(10);
 return view("admin.pages.products.products", $this->data);
* Show the form for creating a new resource.
* @return \Illuminate\Http\Response
public function create()
 $this->data["categories"] = Category::whereNull("parent_id")
    ->with("subcategories")
    ->get();
 $this->data["colors"] = Color::all();
  $this->data["collections"] = Collection::all();
 return view("admin.pages.products.product_create", $this->data);
```

```
* Store a newly created resource in storage.
  * @param \Illuminate\Http\Request $request
  * @return \Illuminate\Http\Response
 public function store(AdminCreateProductRequest $request)
   $newProduct = [
      "name"=>$request->name,
      "price" => $request->price,
      "description" => $request->description,
      "collection id" => $request->collection
   ];
   $subcats = $request->subcategories;
   $colors = $request->colors;
    $msg = "Successfully created product";
   $class = "info";
   try {
      DB::beginTransaction();
      $product = Product::create($newProduct);
      $product->categories()->sync($subcats);
      $product->colors()->sync($colors);
      foreach($request->file("images") as $i=>$image){
        if(!$image){
          if($i == 0){
            DB::rollBack();
            return redirect()->route("admin_product.create")->with(["message"=>"First image must not be
empty", "class" => "danger"]);
        $filename = $image->store("", ["disk"=>"products"]);
```

```
$image = Image::create([
        "filename"=>$filename,
       "thumbnail_filename"=>$filename
      ]);
      ProductImage::create([
        "product_id"=>$product->id,
        "image_id"=>$image->id
      ]);
    DB::commit();
  catch(\Throwable $ex){
    DB::rollBack();
    Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
    $msg = "Internal error";
    $class = "danger";
 return redirect()->route("admin_product.index")->with([
    "message" => $msg,
    "class" => "$class"
  ]);
* Display the specified resource.
* @param int $id
* @return \Illuminate\Http\Response
public function show($id)
```

```
* Show the form for editing the specified resource.
 * @param int $id
 * @return \Illuminate\Http\Response
 public function edit($id)
   $product = Product::where("id", $id)
     ->with("categories")
     ->with("colors")
     ->with("collection")
     ->first();
   if(!$product){
     return redirect()->route("admin_product.index")->with(["message"=>"Product not found", "class" =>
'danger"]);
   $this->data["product"] = $product;
   $this->data["categories"] = Category::whereNull("parent_id")
     ->with("subcategories")
     ->get();
   $this->data["colors"] = Color::all();
   $this->data["collections"] = Collection::all();
   return view("admin.pages.products.product_edit", $this->data);
 * Update the specified resource in storage.
 * @param \Illuminate\Http\Request $request
 * @param int $id
 * @return \Illuminate\Http\Response
 public function update(AdminEditProductRequest $request, $id)
   $newProduct = [
     "name"=>$request->name,
```

```
"price" => $request->price,
      "description" => $request->description,
      "collection_id" => $request->collection
    ];
    $subcats = $request->subcategories;
    $colors = $request->colors;
    $msg = "Successfully edited product";
    $class = "info";
    try {
      $product = Product::find($id);
      if(!$product){
        return redirect()->route("admin_product.index")->with(["message"=>"Product not found", "class" =>
'danger"]);
      DB::beginTransaction();
      $product->update($newProduct);
      $product->categories()->sync($subcats);
      $product->colors()->sync($colors);
      if($request->change_images){
        $images = $request->file("images");
        if(!$images){
          DB::rollBack();
          return redirect()->route("admin_product.edit", ["admin_product"=>$id])-
>with(["message"=>"First image must not be empty", "class" => "danger"])
             ->withInput();
        $newImages = [];
        foreach($images as $image){
```

```
if(!$image){
        $filename = $image->store("", ["disk"=>"products"]);
        $image = Image::create([
          "filename"=>$filename,
          "thumbnail_filename"=>$filename
        ]);
        $newImages[] = [
          "product_id"=>$product->id,
          "image_id"=>$image->id
       ];
     $product->images()->sync($newImages);
   DB::commit();
 catch(\Throwable $ex){
   DB::rollBack();
   Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
   $msg = "Internal error";
   $class = "danger";
 return redirect()->route("admin_product.index")->with([
   "message" => $msg,
   "class" => "$class"
 ]);
* Remove the specified resource from storage.
* @param int $id
* @return \Illuminate\Http\Response
```

```
public function destroy($id)
  $msg = "The product has been successfully set inactive";
  $class = "info";
  try {
    $product = Product::find($id);
    if(!$product){
      $msg = "Product not found";
      $class = "danger";
    else{
      $product->active = false;
      $product->save();
  catch(\Throwable $ex){
    Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
    $msg = "Internal error";
    $class = "danger";
  return redirect()->route("admin_product.index")->with([
    "message" => $msg,
    "class" => "$class"
 ]);
```

3.2.6 AdminSubcategoryController.php

```
<?php

namespace App\Http\Controllers;

use App\Http\Requests\AdminCreateSubcategoryRequest;
use App\Models\Category;</pre>
```

```
use App\Models\Log;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
class AdminSubcategoryController extends AdminController
  * Display a listing of the resource.
  * @return \Illuminate\Http\Response
  public function index()
    $this->data["mainCategories"] =
      Category::whereNull("parent_id")
      ->get();
    $categories = Category::whereNotNull("parent_id");
    $main = request("main-category");
    if($main){
      $categories = $categories->where("parent_id", $main);
    $keywords = request("keywords");
    if($keywords){
      $categories = $categories->where("name", "like", "%$keywords%");
    $column = "created_at";
    $order = "desc";
    $sort = request("sort");
    if($sort){
      $column = explode("-", $sort)[0];
      $order = explode("-", $sort)[1];
    $categories = $categories->orderBy($column, $order);
    $this->data["subcategories"] =
      $categories
        ->with("mainCategory")
```

```
->paginate(10);
  return view("admin.pages.subcategories.subcategories", $this->data);
* Show the form for creating a new resource.
* @return \Illuminate\Http\Response
public function create()
  $this->data["mainCategories"] =
    Category::whereNull("parent_id")
      ->get();
  return view("admin.pages.subcategories.subcategory_create", $this->data);
* Store a newly created resource in storage.
* @param \Illuminate\Http\Request $request
* @return \Illuminate\Http\Response
public function store(AdminCreateSubcategoryRequest $request)
  $msg = "Successfully created subcategory";
  $class = "info";
  try {
    Category::create([
      "parent_id"=>$request->main,
      "name"=>$request->name
    ]);
  catch(\Throwable $ex){
    Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
```

```
$msg = "Internal error";
    $class = "danger";
  return redirect()->route("admin_subcategory.index")->with([
    "message" => $msg,
    "class" => "$class"
 ]);
* Display the specified resource.
* @param int $id
* @return \Illuminate\Http\Response
public function show($id)
* Show the form for editing the specified resource.
* @param int $id
* @return \Illuminate\Http\Response
public function edit($id)
* Update the specified resource in storage.
* @param \Illuminate\Http\Request $request
* @param int $id
* @return \Illuminate\Http\Response
public function update(Request $request, $id)
```

```
* Remove the specified resource from storage.
* @param int $id
* @return \Illuminate\Http\Response
public function destroy($id)
  $msg = "Category successfully removed";
  $class = "info";
 $cat = Category::whereNotNull("parent_id")
    ->find($id);
  if(!$cat){
    $msg = "Category not found";
    $class = "danger";
  else if(count($cat->products)){
    $msg = "There are products assigned to this category";
    $class = "danger";
  else {
    try {
      $cat->delete();
    catch(\Throwable $ex){
      Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
      $msg = "Internal error";
      $class = "danger";
  return redirect()->route("admin_subcategory.index")->with([
```

3.2.7 AdminUserController.php

```
<?php
namespace App\Http\Controllers;
use App\Http\Requests\AdminEditUserRequest;
use App\Models\Log;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;
class AdminUserController extends AdminController
  public function index()
    $users = User::where("role_id", 1);
    $keywords = request("keywords");
    if($keywords){
      $users = $users->where(function($q) use($keywords){
       $q->where(DB::raw("concat(first_name, '', last_name)"), "like", "%$keywords%")
          ->orWhere("email", "like", "%$keywords%");
      });
    $column = "created_at";
    $order = "desc";
    $sort = request("sort");
    if($sort){
      $column = explode("-", $sort)[0];
```

```
$order = explode("-", $sort)[1];
  $users = $users->orderBy($column, $order);
  $this->data["users"] = $users->paginate("10");
  return view("admin.pages.users.users", $this->data);
public function create()
public function store(Request $request)
public function show($id)
public function edit($id)
  $user = User::find($id);
  if(!$user){
    $msg = "User not found";
    $class = "danger";
```

```
return redirect()->route("admin_user.index")->with([
      "message" => $msg,
      "class" => "$class"
    ]);
 $this->data["user"] = $user;
  return view("admin.pages.users.user_edit", $this->data);
public function update(AdminEditUserRequest $request, $id)
  $email = $request->email;
  $newInfo = [
    "email" => $email,
    "first_name"=>$request->first,
    "last_name"=>$request->last,
 ];
  $msg = "User successfully updated";
  $class = "info";
  try {
    $user = User::find($id);
    if(!$user){
      $msg = "User not found";
      $class = "danger";
    else {
      $user->fill($newInfo);
      $user->save();
```

```
catch(\Throwable $ex){
    Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
    $msg = "Internal error";
    $class = "danger";
  return redirect()->route("admin_user.index")->with([
    "message" => $msg,
    "class" => "$class"
  ]);
public function destroy($id)
  $msg = "User successfully removed";
  $class = "info";
  $user = User::find($id);
  if(!$user){
    $msg = "User not found";
    $class = "danger";
  else {
    try {
      $user->delete();
```

```
}
catch(\Throwable \\exists \){
    Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>\\exists ex->getMessage()]);

    \left\rightarrow mss = "Internal error";
    \left\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\right\ri
```

3.2.8 BaseController.php

```
<?php
namespace App\Http\Controllers;
use App\Models\Category;
use App\Models\Menu;
use Illuminate\Http\Request;

class BaseController extends Controller
{
   public $data = [];

   public function __construct()
   {

    $this->data["menu"] =
        Menu::whereNull("parent")
        ->with("menus")
        ->get();
}
```

```
$this->data["categories"] = Category::whereNull("parent_id")
    ->with("subcategories")
    ->get();

}

public function author(){
    return view("front.pages.author", $this->data);
}
```

3.2.9 CartController.php

```
<?php
namespace App\Http\Controllers;
use App\Models\Cart;
use App\Models\Log;
use Illuminate\Http\Request;
class CartController extends BaseController
  public function index()
    $user = session()->get("user");
    if(!$user) {
      return redirect()->route("home");
    $cart =
      Cart::where("user_id", $user->id)
        ->with("product.images")
        ->whereHas("product",function($q){
           $q->where("active", true);
        })
        ->get();
    $totalPerProduct = [];
```

```
$total = 0;
  foreach($cart as $item){
    $totalPerProduct[] = $item->product->price * $item->quantity;
    $total += $item->product->price * $item->quantity;
  $this->data["totalPerProduct"] = $totalPerProduct;
  $this->data["total"] = $total;
  $this->data["cart"] = $cart;
  return view("front.pages.user.cart", $this->data);
public function create()
public function store(Request $request)
  $user = session()->get("user");
  if(!$user){
    return response()->json(["success"=>false, "message"=>"Session expired."]);
  $productId = request("product_id");
  $quantity = request("quantity");
  try {
    $existingItem = Cart::where("product_id", $productId)
      ->where("user_id", $user->id)
      ->first();
    if($existingItem) {
      $existingItem->quantity = $existingItem->quantity + $quantity;
      $existingItem->save();
    else {
      Cart::create([
        "product_id"=>$productId,
```

```
"user_id"=>$user->id,
         "quantity" => $quantity
      ]);
    Log::create(["ip"=>request()->ip(), "log_category_id"=>4, "message"=>$user->email." has added
    product ID $productId to cart."]);
  catch(\Throwable $ex){
    Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
    return response()->json(["success"=>false, "message"=>"Internal error. Try again later."]);
  return response()->json(["success"=>true, "message"=>"Successfully added to cart."]);
public function show($id)
public function edit($id)
public function update(Request $request, $id)
  $user = session()->get("user");
  $quantity = request("quantity");
  try {
    $cart = Cart::find($id);
```

```
if(!$cart || $cart->user_id != $user->id){
      return response()->json(["success"=>false, "message"=>"Error. Item not found."]);
    $cart->quantity = $quantity;
    $cart->save();
    return response()->json(["success"=>true, "message"=>"Success."]);
  catch(\Throwable $ex){
    return response()->json(["success"=>false, "message"=>"Internal error. Try again later."]);
public function destroy($id)
  $user = session()->get("user");
  try {
    $cart = Cart::find($id);
    if(!$cart || $cart->user_id != $user->id){
      return response()->json(["success"=>false, "message"=>"Error. Item not found."]);
    $cart->delete();
    return response()->json(["success"=>true, "message"=>"Success."]);
  catch(\Throwable $ex){
    return response()->json(["success"=>false, "message"=>"Internal error. Try again later."]);
```

```
<?php
namespace App\Http\Controllers;
use App\Http\Requests\SendMessageRequest;
use App\Mail\ContactForm;
use App\Models\Log;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Mail;
class ContactController extends BaseController
  public function index(){
    return view("front.pages.contact", $this->data);
  public function sendMessage(SendMessageRequest $request){
    $name = $request->name;
    $email = $request->email;
    $subject = $request->subject;
    $message = $request->message;
    try {
      Mail::to("furnishopinfo@gmail.com")->send(new ContactForm($name, $email, $subject, $message));
      return redirect()->route("contact")->with([
        "msg"=>"Message successfully sent",
        "class" => "success"
      ]);
    catch(\Throwable $ex){
      Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>substr($ex->getMessage(),0,
250)]);
      return redirect()->route("contact")->with([
        "msg"=>"Internal error. Please try again later.",
        "class" => "danger"
```

3.2.11 Controller.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Foundation\Auth\Access\AuthorizesRequests;
use Illuminate\Foundation\Bus\DispatchesJobs;
use Illuminate\Foundation\Validation\ValidatesRequests;
use Illuminate\Routing\Controller as BaseController;

class Controller extends BaseController
{
    use AuthorizesRequests, DispatchesJobs, ValidatesRequests;
}
</pre>
```

3.2.12 ErrorController.php

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;

class ErrorController extends BaseController
{
   public function index($code){

   $this->data["code"] = $code;
   return view("errors.error", $this->data);
}
```

}

3.2.13 HomeController.php

```
<?php
namespace App\Http\Controllers;
use App\Models\Category;
use App\Models\Lookbook;
use App\Models\Product;
use App\Models\SliderImage;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Storage;
class HomeController extends BaseController
  public function index(){
    $this->data["sliderImages"] = SliderImage::all();
    $featuredCategoryId = Storage::get("featured_category.txt");;
    $this->data["featuredCategory"] =
      Category::find($featuredCategoryId);
    $this->data["featuredSubcategories"] = $this->data["categories"]
      ->where("id", $featuredCategoryId)->first()
      ->subcategories;
    $this->data["featuredCategoryLatest"] =
      Product::whereHas("categories", function($q)
        use($featuredCategoryId){
          $q->where("parent_id", $featuredCategoryId);
        })
        ->where("active", true)
        ->with("images")
        ->orderBy("created_at", "desc")
        ->take(6)
```

```
->get();
$this->data["featuredCategoryBest"] =
  Product::whereHas("categories", function($q)
    use($featuredCategoryId){
      $q->where("parent_id", $featuredCategoryId);
    ->where("active", true)
    ->with("images")
    ->take(6)
    ->get();
$this->data["featuredCategoryLookbook"] =
  Lookbook::where("category_id", $featuredCategoryId)
    ->take(2)
    ->get();
$this->data["featuredLookbook"] =
  Lookbook::take(4)
  ->get();
return view("front.pages.home", $this->data);
```

3.2.14 LogController.php

```
<?php

namespace App\Http\Controllers;

use App\Models\Log;
use App\Models\LogCategory;</pre>
```

```
use Illuminate\Http\Request;
class LogController extends AdminController
  public function index(){
    $category_id = request("category");
    $this->data["logCategories"] = LogCategory::all();
    $log = Log::with("category");
    if($category_id){
      $log = $log->where("log_category_id", $category_id);
    $column = "created_at";
    $order = "desc";
    $sort = request("sort");
    if($sort){
      $column = explode("-", $sort)[0];
      $order = explode("-", $sort)[1];
    $log = $log->orderBy($column, $order);
    $this->data["log"]=$log->paginate(10);
    return view("admin.pages.log", $this->data);
```

3.2.15 LoginController.php

```
<?php
```

```
namespace App\Http\Controllers;
use App\Http\Requests\LoginRequest;
use App\Models\Log;
use App\Models\User;
use Illuminate\Http\Request;
class LoginController extends BaseController
  public function index(){
    return view("front.pages.auth.login", $this->data);
  public function auth(LoginRequest $request){
    $user = User::where("email", request("email"))
      ->where("password", md5(request("password")))
      ->with("role")
      ->first();
    if(!$user){
      return redirect()->back()->with("error", "Wrong username and/or password.");
    session()->put("user", $user);
    Log::create(["ip"=>request()->ip(), "log_category_id"=>2, "message"=>$user->email." has logged in."]);
    return redirect()->back();
  public function logout(){
    $user = session()->get("user");
    Log::create(["ip"=>request()->ip(), "log_category_id"=>3, "message"=>$user->email." has logged out."]);
    session()->remove("user");
    return redirect()->back();
```

3.2.16 LookbookController.php

```
namespace App\Http\Controllers;
use App\Models\Category;
use App\Models\Lookbook;
use Illuminate\Http\Request;

class LookbookController extends BaseController
{
  public function index(Category $category = null){
    $lookbook = Lookbook::with("items.product.images");

    if($category){
        $lookbook = $lookbook->where("category_id", $category->id);
    }

    $this->data["lookbook"] = $lookbook->get();
    $this->data["selectedCategory"] = $category;
    $this->data["categories"] = Category::whereHas("lookbooks")->get();
    return view("front.pages.products.lookbook", $this->data);
    }
}
```

3.2.17 ProductController.php

```
namespace App\Http\Controllers;

use App\Models\Category;
use App\Models\Collection;
use App\Models\Color;
use App\Models\Product;
use App\Models\Product;
use http\Env\Response;
use Illuminate\Http\Request;

class ProductController extends BaseController
```

```
public function index(Category $category = null, Request $request)
  if($request->ajax()){
    $products = Product::where("active", true);
    if($category){
      $products = $products->whereHas("categories", function($q)
      use ($category)
        $q->where("parent_id", $category->id)
           ->orWhere("category_id", $category->id);
      });
    $keywords = request("keywords");
    if($keywords){
      $products = $products
        ->where("name", "LIKE", "%$keywords%");
    $collections = request("collections");
    if($collections){
      $products = $products
        ->whereIn("collection_id", $collections);
    $colors = request("colors");
    if($colors){
      $products = $products
        ->whereHas("colors", function($q) use($colors){
           $q->whereIn("color_id", $colors);
        });
    $sort = request("sort");
    if($sort){
      $column = explode("-", $sort)[0];
      $order = explode("-", $sort)[1];
      $products = $products
```

```
->orderBy($column, $order);
    $products = $products
      ->with("colors")
      ->with("images")
      ->paginate(6);
    return response()
      ->json($products)
      ->header("Vary", "Accept");
  $this->data["collections"] = Collection::all();
  $this->data["colors"] = Color::all();
  $this->data["category"] = $category;
 return view("front.pages.products.shop", $this->data);
* Show the form for creating a new resource.
* @return \Illuminate\Http\Response
public function create()
* Store a newly created resource in storage.
* @param \Illuminate\Http\Request $request
* @return \Illuminate\Http\Response
public function store(Request $request)
```

```
* Display the specified resource.
* @param int $id
* @return \Illuminate\Http\Response
public function show($id)
 $product =
    Product::find($id);
  if(!$product){
    return redirect()->route("error", ["code"=>404]);
 $this->data["active"] = $product->active;
 $product =
    Product::where("id", $id)
    ->with("images")
    ->with("categories")
    ->with("collection")
    ->with("colors")
    ->first();
  $mainCategory = $product
    ->categories
    ->first()
    ->mainCategory()
    ->first();
  $this->data["related"] =
    Product::whereHas("categories", function($q) use($mainCategory){
        $q->where("parent_id", $mainCategory->id);
      })
      ->where("id", "<>", $id)
      ->with("images")
      ->take(3)
      ->get();
```

```
$this->data["main_category"] = $mainCategory;
  $this->data["product"] = $product;
 return view("front.pages.products.product", $this->data);
* Show the form for editing the specified resource.
* @param int $id
* @return \Illuminate\Http\Response
public function edit($id)
* Update the specified resource in storage.
* @param \Illuminate\Http\Request $request
* @param int $id
* @return \Illuminate\Http\Response
public function update(Request $request, $id)
* Remove the specified resource from storage.
* @param int $id
* @return \Illuminate\Http\Response
public function destroy($id)
```

3.2.18 RegisterController.php

```
<?php
namespace App\Http\Controllers;
use App\Http\Requests\RegisterRequest;
use App\Models\Log;
use App\Models\User;
use Illuminate\Http\Request;
class RegisterController extends BaseController
  public function index(){
    return view("front.pages.auth.register", $this->data);
  public function store(RegisterRequest $request)
    try {
    User::create([
      "first_name"=>request("firstname"),
      "last name"=>request("lastname"),
      "email"=>request("email"),
      "password"=>md5(request("password"))
    ]);
    $email = request("email");
    Log::create(["ip"=>request()->ip(), "log_category_id"=>1, "message"=>$email." has registered."]);
    return redirect()->route("login")->with("message", "Successful registration, you can sign in.");
    catch(\Throwable $ex){
      Log::create(["ip"=>request()->ip(), "log_category_id"=>5, "message"=>$ex->getMessage()]);
      return redirect()->route("register")->with("message","Internal error");
```

3.3 app/Http/Middleware

3.3.1 IsAdmin.php

```
<?php
namespace App\Http\Middleware;
use Closure;
use Illuminate\Http\Request;
class IsAdmin
   * Handle an incoming request.
  * @param \Illuminate\Http\Request $request
  * @param \Closure(\Illuminate\Http\Request):
(\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse) $next
  * @return \Illuminate\Http\Response | \Illuminate\Http\RedirectResponse
  public function handle(Request $request, Closure $next)
    $user = session()->get("user");
    if($user && $user->role->name == "Administrator"){
      return $next($request);
    return redirect()->route("home");
```

3.3.2 IsGuest.php

```
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;</pre>
```

```
class IsGuest
{
    /**
    * Handle an incoming request.
    *
    *@param \Illuminate\Http\Request $request
    *@param \Closure(\Illuminate\Http\Request):
(\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse) $next
    *@return \Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
    */
    public function handle(Request $request, Closure $next)
    {
        if(session()->has("user")){
            return redirect()->route("home");
        }
        return $next($request);
    }
}
```

3.3.3 IsUser.php

```
<?php
namespace App\Http\Middleware;
use Closure;
use Illuminate\Http\Request;
class IsUser
{
    /**
    * Handle an incoming request.
    *
    * @param \Illuminate\Http\Request $request
    * @param \Closure(\Illuminate\Http\Request):
(\Illuminate\Http\Response|\Illuminate\Http\RedirectResponse) $next
    * @return \Illuminate\Http\Response|\Illuminate\Http\RedirectResponse
    */
    public function handle(Request $request, Closure $next)
    {
        if(!session()->has("user")){
            return redirect()->route("login");
        }
    }
}
```

```
return $next($request);
}
```

3.3.4 UserLinks.php

```
<?php
namespace App\Http\Middleware;
use Closure;
use Illuminate\Http\Request;
class UserLinks
  public $authMenu = [
      "class"=>"fa fa-check",
      "name"=>"View Cart",
      "route"=>"cart.index"
      "class"=>"fa fa-sign-out",
      "name"=>"Sign Out",
      "route"=>"logout"
  ];
  public $noAuthMenu = [
      "class"=>"fa fa-sign-in",
      "name"=>"Sign In",
      "route"=>"login"
    ],
      "class"=>"fa fa-user",
      "name"=>"Register Account",
      "route"=>"register"
  ];
  public function handle(Request $request, Closure $next)
```

```
if(session()->has("user")){
  if(session()->get("user")->role->name == "Administrator"){
    $this->authMenu[] = [
      "class" => "fa fa-cogs",
      "name" => "Admin Panel",
      "route" => "admin"
    ];
  view()->share("accName", session()->get("user")->first_name);
  view()->share("accMenu", $this->authMenu);
else {
  view()->share("accName", "Guest");
  view()->share("accMenu", $this->noAuthMenu);
return $next($request);
```

3.4 app/Http/Requests

3.4.1 AdminCreateCollectionCategoryRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class AdminCreateCollectionCategoryRequest extends FormRequest
{
    /**
    * Determine if the user is authorized to make this request.
    *
    * @return bool
    */
    public function authorize()</pre>
```

3.4.2 AdminCreateLookbookIdeaRequest.php

```
<?php
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;

class AdminCreateLookbookIdeaRequest extends FormRequest
{
    /**
    * Determine if the user is authorized to make this request.
    *
    * @return bool
    */
    public function authorize()
    {
        return true;
    }

    /**
    * Get the validation rules that apply to the request.
    *
    * @return array
    */
    public function rules()
    {
        return true;
    }
}</pre>
```

```
return [
     "name"=>"required|string|min:4",
     "category"=>"required|integer|exists:categories,id",
     "image"=>"required|image|mimes:jpg,png,gif"
    ];
}
```

3.4.3 AdminCreatePorductRequest.php

```
<?php
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class AdminCreateProductRequest extends FormRequest
  * Determine if the user is authorized to make this request.
  * @return bool
  public function authorize()
    return true;
  * Get the validation rules that apply to the request.
  * @return array
  public function rules()
    return [
      "subcategories"=>"required|array|exists:categories,id",
      "name"=>"required|string|min:3",
      "images"=>"required|array|min:1",
      "images.*"=>"image|mimes:jpg,png,gif",
      "colors"=>"required|array|min:1|exists:colors,id",
      "price"=>"required|numeric",
```

```
"description"=>"required|string|min:10|max:300"

];
}
```

3.4.4 AdminCreateSubcateogryRequest.php

```
<?php
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class AdminCreateSubcategoryRequest extends FormRequest
  * Determine if the user is authorized to make this request.
  * @return bool
  public function authorize()
    return true;
  * Get the validation rules that apply to the request.
  * @return array
  public function rules()
    return [
      "main"=>"required|integer|exists:categories,id",
      "name"=>"required|string"
```

3.4.5 AdminEditFeaturedCateogry.php

```
<?php
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class AdminEditFeaturedCategory extends FormRequest
  * Determine if the user is authorized to make this request.
  * @return bool
 public function authorize()
    return true;
  * Get the validation rules that apply to the request.
  * @return array
  public function rules()
    return [
      "category"=>"required|integer|exists:categories,id"
    ];
```

3.4.6 AdminEditLookbookIdeaRequest.php

```
<?php
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class AdminEditLookbookIdeaRequest extends FormRequest
{
    /**
    * Determine if the user is authorized to make this request.
    *
    * @return bool
    */</pre>
```

```
public function authorize()
{
    return true;
}

/**
    * Get the validation rules that apply to the request.
    *
    * @return array
    */
public function rules()
{
    return [
        "pins."=>"array",
        "pins.*"=>"regex:/\d+\\\d+\\\d+/"
];
}

public function messages()
{
    return [
        "pins.*.regex" => "Fill in the fields correctly"
];
}
```

3.4.7 AdminEditProductRequest.php

```
<?php
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class AdminEditProductRequest extends FormRequest
{
    /**
    * Determine if the user is authorized to make this request.
    *
    * @return bool
    */
    public function authorize()
    {
        return true;
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    *
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    *
    **
    **
    **
    **
    **
    **
    **
    **
    *
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    **
    *
    **
    **
    **
    **
    **
    **
    **
    **
    **
```

```
/**

* Get the validation rules that apply to the request.

*

* @return array

*/

public function rules()

{

return [

"subcategories"=>"required|array|exists:categories,id",

"name"=>"required|string|min:3",

"colors"=>"required|array|min:1|exists:colors,id",

"price"=>"required|numeric",

"description"=>"required|string|min:10|max:300"

];

}

}
```

3.4.8 AdminEditUserRequest.php

```
<?php
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class AdminEditUserRequest extends FormRequest
{
    /**
    * Determine if the user is authorized to make this request.
    *
    * @return bool
    */
    public function authorize()
    {
        return true;
    }
    /**
    * Get the validation rules that apply to the request.
    *
    * @return array</pre>
```

```
*/
public function rules()
{
    return [
        "first"=>"required|string|regex:/\p{L}{\p{L}\s]+/u",
        "last"=>"required|string|regex:/\p{L}{\p{L}\s]+/u",
        "email"=>"required|email|unique:users,email,$this->id,id",
];
}

public function messages()
{
    return [
        "firstname.required" => "First name is required",
        "firstname.regex"=> "First name must contain only letters (and spaces if needed)",
        "lastname.required" => "Last name is required",
        "lastname.required" => "Last name is required",
        "lastname.regex"=> "Last name must contain only letters (and spaces if needed)",
        'email.required" => 'Email is required',
        'email.email' => 'Email is invalid',

];
}
```

3.4.9 LoginRequest.php

```
<?php
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class LoginRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }
}</pre>
```

```
public function rules()
{
    return [
        "email"=>"required|email",
        "password"=>[
            "required",
            "string",
            "min:6",
        ]
    ];
}

public function messages()
{
    return [
        'email.required' => 'Email is required',
        'email.email' => 'Email is invalid',
        'password.required' => 'Password is required',
        "password.min" => "Password must be at least 6 characters long",
    ];
}
```

3.4.10. RegisterRequest.php

```
<?php
namespace App\Http\Requests;
use Illuminate\Foundation\Http\FormRequest;
class RegisterRequest extends FormRequest
{
    public function authorize()
    {
        return true;
    }
    public function rules()
{</pre>
```

```
return [
      "firstname"=>"required|string|regex:/\p{L}[\p{L}\s]+/u",
      "lastname"=>"required|string|regex:/\p{L}[\p{L}\s]+/u",
      "email"=>"required|email|unique:users,email",
      "password"=>[
        "required",
        "string",
        "min:6",
        "regex:/\p{Lu}/u",
        "regex:/\p{Ll}/u",
        "regex:/\d/"
      ],
    ];
  public function messages()
    return [
      "firstname.required" => "First name is required",
      "firstname.regex"=> "First name must contain only letters (and spaces if needed)",
      "lastname.required" => "Last name is required",
      "lastname.regex"=> "Last name must contain only letters (and spaces if needed)",
      'email.required' => 'Email is required',
      'email.email' => 'Email is invalid',
      'password.required' => 'Password is required',
      "password.min" => "Password must be at least 6 characters long",
      "password.regex" => "Password must contain at least one uppercase letter, one lowercase letter and
one digit",
    ];
```

3.4.11. SendMessageRequest.php

```
<?php

namespace App\Http\Requests;

use Illuminate\Foundation\Http\FormRequest;

class SendMessageRequest extends FormRequest
{
    /**
    * Determine if the user is authorized to make this request.
    *
    * @return bool</pre>
```

```
*/
public function authorize()
{
    return true;
}

/**
    * Get the validation rules that apply to the request.
    *
    * @return array
    */
public function rules()
{
    return [
        "name" => "required|string|max:50",
        "email" => "required|email|max:50",
        "subject" => "required|string|max:50",
        "message" => "required|string|min:20|max:200",
    ];
}
```

3.5 app/Http/Mail

3.5.1 ContactForm.php

```
<?php
namespace App\Mail;
use Illuminate\Bus\Queueable;
use Illuminate\Contracts\Queue\ShouldQueue;
use Illuminate\Mail\Mailable;
use Illuminate\Queue\SerializesModels;

class ContactForm extends Mailable
{
    use Queueable, SerializesModels;

    public $name;
    public $email;
    public $subject;
    public $messageContent;

/**</pre>
```

```
* Create a new message instance.
* @return void
* @param $name
* @param $email
* @param $subject
* @param $message
public function __construct($name, $email, $subject, $message)
  $this->name = $name;
 $this->email = $email;
 $this->subject = $subject;
  $this->messageContent = $message;
* Build the message.
* @return $this
public function build()
  return $this->view('mail.contact-form');
```

3.6 app/Http/Models

3.6.1 Cart

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Cart extends Model
{
</pre>
```

```
protected $guarded = ["id"];

use HasFactory;

public function product(){
   return $this->belongsTo(Product::class);
}
```

3.6.2 Category

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
class Category extends Model
  use HasFactory;
  protected $guarded = ["id"];
  public function subcategories(){
    return $this->hasMany(Category::class, "parent_id", "id")
      ->orderBy("name");
  public function mainCategory(){
    return $this->belongsTo(Category::class, "parent_id", "id");
  public function products(){
    return $this->belongsToMany(Product::class, "category_product");
 public function lookbooks(){
    return $this->hasMany(Lookbook::class);
```

}

3.6.3 CategoryProduct

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Relations\Pivot;
class CategoryProduct extends Pivot
{
   protected $guarded = ["id"];
}</pre>
```

3.6.4 Collection

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Collection extends Model
{
    use HasFactory;
    protected $guarded = ["id"];
}</pre>
```

3.6.5 Color

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Color extends Model
{
    use HasFactory;
}</pre>
```

```
protected $guarded = ["id"];
}
```

3.6.6 ColorProduct

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Relations\Pivot;

class ColorProduct extends Pivot
{
    protected $guarded = ["id"];
}</pre>
```

3.6.7 Image

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Image extends Model
{
    use HasFactory;
    protected $guarded = ["id"];
}</pre>
```

3.6.8 Log

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;</pre>
```

```
class Log extends Model
{
  protected $guarded = ["id"];
  use HasFactory;

public function category(){
    return $this->belongsTo(LogCategory::class, "log_category_id", "id");
  }
}
```

3.6.9 LogCategory

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class LogCategory extends Model
{
    use HasFactory;
}</pre>
```

3.6.10 Lookbook

```
namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Lookbook extends Model
{
    protected $guarded = ["id"];
    use HasFactory;
}
```

```
function items(){
    return $this->hasMany(LookbookItem::class);
}

function category(){
    return $this->belongsTo(Category::class);
}
```

3.6.11 LookbookItem

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class LookbookItem extends Model
{
   protected $guarded = ["id"];
   use HasFactory;

   function product(){
      return $this->belongsTo(Product::class, "product_id", "id");
   }
}
```

3.6.12 Menu

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
class Menu extends Model
{
    use HasFactory;</pre>
```

```
protected $guarded = ["id"];

public function menus()
{
    return $this->hasMany(Menu::class, "parent", "id");
}
```

3.6.13 Product

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
class Product extends Model
  use HasFactory;
  protected $guarded = ["id"];
  public function colors(){
    return $this->belongsToMany(Color::class);
  public function collection(){
    return $this->belongsTo(Collection::class);
  public function images(){
    return $this->belongsToMany(Image::class, "product_image");
  public function firstImage(){
    return $this->belongsToMany(Image::class, "product_image")->first();
  public function categories(){
    return $this->belongsToMany(Category::class);
```

3.6.14 Productimage

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Relations\Pivot;

class ProductImage extends Pivot
{
    protected $guarded = ["id"];
}</pre>
```

3.6.15 Role

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class Role extends Model
{
   use HasFactory;
   protected $guarded = ["id"];
}</pre>
```

3.6.16 SliderImage

```
<?php
namespace App\Models;
use Illuminate\Database\Eloquent\Factories\HasFactory;</pre>
```

```
use Illuminate\Database\Eloquent\Model;

class SliderImage extends Model
{
   use HasFactory;
}
```

3.6.17 User

```
namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class User extends Model
{
    use HasFactory;
    protected $guarded = ["id"];

    public function role(){
        return $this->belongsTo(Role::class, "role_id", "id");
    }
}
```

3.7 App/Http/View/Components/Product.php

```
<?php
namespace App\View\Components;
use Illuminate\View\Component;

class Product extends Component
{
   public $id;
   public $name;
   public $price;</pre>
```

```
public $img1;
public $img2;
public $class;

public function __construct($product, $class="")
{
    $this->id = $product->id;
    $this->name = $product->price;
    $this->price = $product->price;
    $this->img1 = $product->images->get(0)->thumbnail_filename;
    $this->img2 = $product->images->has(1)?
    $product->images->pet(1)->thumbnail_filename
    : $this->img1;
    $this->class = $class;
}

public function render()
{
    return view('components.product');
}
```

3.8 public/js

3.8.1 custom.js

```
window.data = {
  forms: {}
}

function fetchData(url, method, data = {}){
  return new Promise((resolve,reject)=>{
    $.ajax({
      url: url,
      method: method,
      dataType: "json",
      data: data,
      success: resolve,
      error: reject,
      cache: false
```

```
})
  })
$.ajaxSetup({
  headers: {
    'X-CSRF-TOKEN': $('meta[name="csrf-token"]').attr('content')
});
$(document).ready(function(){
  $("#page-preloader").fadeOut({duration: 200, queue:false});
  loadRegularExpressions();
  $(".login-form").submit(validateLoginForm);
  $("#customer-form").submit(validateRegistrationForm);
  $("#contact-form").submit(validateContactForm);
})
function loadRegularExpressions(){
  data.forms.name = {
    "regex": /^\p{Uppercase_Letter}\p{Letter}{1,14}(\s\p{Uppercase_Letter}\p{Letter}{1,14}){0,2}$/u,
    "length": 20,
    "message": "All words must begin with a capital letter."
  data.forms.email = {
    "regex": /^[a-z]((\.|-|_)?[a-z0-9]){2,}@[a-z]((\.|-)?[a-z0-9]+){2,}\.[a-z]{2,6}$/i,
    "length": 50,
    "message": "Use only letters, numbers and symbols @.- "
  data.forms.password = {
    "regex": /^(?=.*\p{Uppercase_Letter})(?=.*\p{Lowercase_Letter})(?=.*\d)(?=.{6,})/u,
    "length": 50,
    "message": "Password should be at least 6 characters long and contain at least one uppercase letter, one
lowercase letter and one number"
  };
  data.forms.subject = {
    "regex": /^.{5,50}$/u,
    "length": 50,
    "message": "Subject should have at least 5 characters."
```

```
data.forms.message = {
    "regex": /^.{20,200}$/u,
    "length": 200,
    "message": "Message should have at least 20 characters."
  };
function validateString(string, validation){
  if(string == ""){
    return "empty";
  if(string.length > validation.length){
    return "long";
  if(!validation.regex.test(string)){
    return "incorrect";
  return "valid";
function validateElement(element, validation){
  let fieldName = $(element).attr("placeholder");
  let fieldValidation = validateString($(element).val(), validation);
  if(fieldValidation == "empty"){
    formError(element, `Please input ${fieldName.toLowerCase()}.`);
  if(fieldValidation == "long"){
    formError(element, `${fieldName} is too long. Maximum characters: ${validation.length}.`);
  else if(fieldValidation == "incorrect"){
    formError(element, `${fieldName} is invalid. ${validation.message}`);
function formError(element, message){
  $(`${message}`).insertAfter($(element));
  data.forms.error = true;
function resetFormMessages(){
  $(".form-error").remove();
  $(".form-success").remove();
function validateLoginForm(e){
```

```
data.forms.error = false;
 resetFormMessages();
 let email = $("[name=email]");
 let password = $("[name=password]");
 validateElement(email, data.forms.email);
 validateElement(password, data.forms.password);
 if(data.forms.error){
   e.preventDefault();
function validateRegistrationForm(e){
 data.forms.error = false;
 resetFormMessages();
 let first = $("[name=firstname]");
 let last = $("[name=lastname]");
 let email = $("[name=email]");
 let password = $("[name=password]");
 validateElement(first, data.forms.name);
 validateElement(last, data.forms.name);
 validateElement(email, data.forms.email);
 validateElement(password, data.forms.password);
 if(data.forms.error){
    e.preventDefault();
function validateContactForm(e){
 data.forms.error = false;
 resetFormMessages();
 let name = $("[name=name]");
 let email = $("[name=email]");
 let subject = $("[name=subject]");
 let message = $("[name=message]");
```

```
validateElement(name, data.forms.name);
validateElement(email, data.forms.email);
validateElement(subject, data.forms.subject);
validateElement(message, data.forms.message);

if(data.forms.error){
    e.preventDefault();
}
```

3.8.2 cart.js

```
$(document).ready(function(){
  $(".bootstrap-touchspin-up").click(function(){
    changeQuantity($(this).data("target"), 1);
  });
  $(".bootstrap-touchspin-down").click(function(){
    changeQuantity($(this).data("target"),-1);
  });
  $(".qty-input").on("input", function(){
    changeQuantity(`#${$(this).attr("id")}`);
  });
  $(".remove-from-cart").click(removeFromCart);
})
function changeQuantity(element, number = 0){
  let quantity = $(element).val();
  let oldQuantity = quantity;
  quantity = Number(quantity) + number;
  if( Number.isNaN(quantity) || quantity < 1){</pre>
    quantity = 1;
```

```
$(element).val(quantity);
 updateCart(element, quantity);
 updateTotal();
async function updateCart(element, quantity){
 let id = Number(element.split("-")[1]);
 let url = cartUpdateRoute.substr(0,cartUpdateRoute.length-1) + id;
 let dataObj = {
   id: id,
   quantity: quantity
 let result = await fetchData( url,"put", dataObj);
 if(!result.success){
   $(`${result.message}`)
     .insertAfter($(element).parent().parent());
async function removeFromCart(){
 let id = Number($(this).data("id"));
 let url = cartDestroyRoute.substr(0,cartDestroyRoute.length-1) + id;
 let result = await fetchData( url, "delete");
 if(!result.success){
   $(`${result.message}`)
     .insertAfter($(this).parent().parent());
 else {
   $(this).parents(".cart-item").remove();
   if($(".cart-items").html().trim() == ""){
     $(".cart-items").html(`Your cart is empty.`);
```

```
updateTotal()

function updateTotal(){

let total = 0;

$(".cart-item").each{function(){

    let price =Number($(this).find(".price-label").text().substr(1));
    let qty = Number($(this).find(".qty-input").val());
    let productTotal = price * qty;
    $(this).find(".product-price.total").text("$"+productTotal);
    total += productTotal;
})

$("#total-all").text("$"+total);
$("#total-products").text("$"+total);
$("#total-products").text("$"+total);
$("summary-label").text("There are " + $(".cart-item").length + " items in your cart");
}
```

3.8.3 product.js

```
$(document).ready(function(){
    $(".bootstrap-touchspin-up").click(function(){
        quantity(1);
    });

$(".bootstrap-touchspin-down").click(function(){
        quantity(-1);
    });

$(".add-to-cart").click(addToCart);

function quantity(number = 0){
```

```
let quantity = $("#quantity_wanted").val();
 quantity = Number(quantity) + number;
 if( Number.isNaN(quantity) | | quantity < 1 | | quantity > 100){
   quantity = 1;
 $("#quantity_wanted").val(quantity);
 return quantity;
async function addToCart(){
 let dataObj = {};
 dataObj.quantity = quantity();
 dataObj.product_id = $(this).data("id");
 let result = await fetchData(cartStoreUrl, "post", dataObj);
 if(result.success){
   $(""+ result.message +"")
      .insertAfter($(this).parent())
     .hide()
     .show(300)
      .delay(2000)
     .hide(300);
 else {
   $(""+ result.message +"")
      .insertAfter($(this).parent())
     .hide()
     .show(300)
      .delay(2000)
     .hide(300);
 quantity(-1000);
```

```
$(document).ready(function(){
  let initialCategory = $("#title-categories").data("initial-category");
  if(initialCategory){
    changeCategoryDisplay(initialCategory.id, initialCategory.parent_id)
  else {
    changeCategoryDisplay();
  getProducts()
  $(".cateItem").click(function(e){
    e.preventDefault()
    let categoryId = $(this).parent().attr("id").split("-")[1];
    let parentId = $(this).parent().data("parent") ?? null;
    changeCategoryDisplay(categoryId, parentId)
    getProducts()
  })
  $("#keywords, [name=collections], [name=colors], #sort-products").on("input", getProducts)
function changeCategoryDisplay(categoryId = "", parentCategoryId = null){
  $(".cateTitle").not(`[id=category-${parentCategoryId}]`).children(".arrow.collapse-icons[aria-
expanded=true]").click();
  if(!categoryId){
    window.history.pushState({}, "", "/shop");
  else{
    window.history.pushState({}, "", "/category/"+categoryId);
```

```
let elementId = `#category-${categoryId} > a`;
 if(parentCategoryId){
    $(`#category-${parentCategoryId} .arrow.collapse-icons[aria-expanded=false]`).click();
  $(".cateTitle .cateItem.active").removeClass("active");
 $(elementId).addClass("active");
function getFiltersObj(){
 let dataObj = {};
 let keywords = $("#keywords").val()
 if(keywords) { dataObj.keywords = keywords }
 let collections = $("[name=collections]:checked")
    .map(function(){
      return Number($(this).val())
    })
    .get()
  if(collections.length) { dataObj.collections = collections }
  let colors = $("[name=colors]:checked")
    .map(function(){
      return Number($(this).val())
    })
    .get()
  if(colors.length) { dataObj.colors = colors }
  let sort = $("#sort-products").val();
  if(sort){
    dataObj.sort = sort;
  return dataObj
```

```
async function getProducts(){
  let url = baseUrl + "/shop";
 let category = null;
  let activeCategoryLink = $(".cateTitle .cateItem.active");
  if(activeCategoryLink.length){
    let categoryIdAttr = $(activeCategoryLink).parent().attr("id");
    category = categoryIdAttr.split("-")[1];
    if(category){
      url = baseUrl + "/category/"+category;
 try {
    $("#product-grid").html("");
    $("#products-loader").show();
    $(".pagination").addClass("d-none");
    data.products = await fetchData(url, "get", getFiltersObj());
    $("#products-loader").hide();
    showProducts()
    createPageLinks()
    $(".total-products p").text(`THERE ARE ${data.products.total} PRODUCTS`);
  catch(ex){
    console.log(ex);
function showProducts(){
 let html = "";
 if(data.products.data.length == 0){
    html = "No products found  
=("
```

```
for(let product of data.products.data){
   let img1 = product.images[0].thumbnail_filename;
   let img2 = product.images[1] ? product.images[1].thumbnail_filename : img1;
   let productLink = productRoute.substr(0, productRoute.length-1) + product.id;
   html += `<div class="item text-center col-md-4">
          <div class="product-miniature js-product-miniature item-one first-item">
            <div class="thumbnail-container border">
              <a href="${productLink}">
                 <img class="img-fluid image-cover" src="${imgDir + img1}" alt="${product.name}">
                 <img class="img-fluid image-secondary" src="${imgDir + img2}" alt="${product.name}">
              </a>
            </div>
            <div class="product-description">
              <div class="product-groups">
                 <div class="product-title">
                   <a href="${productLink}">${product.name}</a>
                 <div class="product-group-price">
                   <div class="product-price-and-shipping">
                     <span class="price">$${product.price}</span>
                   </div>
                 </div>
              </div>
            </div>
          </div>
        </div>`;
 $("#product-grid").html(html);
function createPageLinks(){
 if(data.products.data.length == 0){
```

```
$(".pagination").addClass("d-none");
 let html = "";
 for(let i = 1; i<=data.products.last_page; i++){</pre>
   html += `
          <a rel="nofollow" href="#!" data-page="${i}" class="page-link-action disabled js-search-link ">
          </a>
        `;
 $(".pagination").removeClass("d-none");
 $(".page-list ul").html(html);
 $(".page-link-action").click(getPage);
async function getPage(){
 let pageNo = $(this).data("page");
 $("html").animate({
    scrollTop: $("header").offset().top
 }, 300);
 let dataObj = getFiltersObj()
 dataObj.page = pageNo
 $("#product-grid").html("");
 $("#products-loader").show();
 $(".pagination").addClass("d-none");
 data.products = await fetchData(data.products.path, "get", dataObj);
 $("#products-loader").hide();
 showProducts()
 createPageLinks()
```

3.9 public/admin-assets/js

3.9.1 product.js

```
const data = {
  forms: {}
$(document).ready(function(){
  loadRegularExpressions();
  $("form").submit(validateProductForm);
  $("#add-image").click(addImage);
  $(document).on("click", ".remove-image", removeImage);
  window.categories = $("#subcategories").data("categories");
  fillSubcategories();
  $("#add-subcat").click(addSubcategory);
  $(document).on("click", ".remove-subcat", removeSubcategory);
  $("#images-wrapper").hide();
  $("#change_images").change(function(){
   if(this.checked){
      $("#images-wrapper").stop().show(300);
   else{
      $("#images-wrapper").stop().hide(300);
  });
function addImage(){
  $(`
    <div class="js-image my-5">
      <input type="file" name="images[]">
      <a href="#!" class="ml-3 remove-image text-danger">
        <i class="pe-7s-less"></i>Remove image
      </a>
    </div>
  `).appendTo("#js-images");
```

```
function removeImage(){
  $(this).parent().remove();
function prepareSubcategoryHtml(selected = 0){
  let selectHtml = `<div><select name="subcategories[]" class="form-control mt-3">`;
  for(let cat of categories){
    selectHtml += `<optgroup label="${cat.name}">`;
      for(let sub of cat.subcategories){
        selectHtml += `<option value="${sub.id}"</pre>
               ${sub.id == selected ? "selected" : ""}>${sub.name}</option>`;
      selectHtml += `</optgroup>`;
  selectHtml += `</select>`;
  return selectHtml;
function addSubcategory(withRemove = true, selected = 0){
  let html = prepareSubcategoryHtml(selected);
  if(withRemove) {
    html += `<a href="#!" class="text-danger remove-subcat">
           <i class="pe-7s-less"></i>Remove subcategory
        </a>`;
  $(html + "</div>").appendTo("#subcategories");
function removeSubcategory(){
  $(this).parent().remove();
function fillSubcategories(){
  let subcats = $("#subcategories").data("selected").toString();
```

```
console.log(subcats)
  subcats = subcats.split(",");
  let first = true;
  for(let cat of subcats){
    if(first){
       addSubcategory(false, cat);
       first = false;
    else {
       addSubcategory(true, cat);
function loadRegularExpressions(){
  data.forms.name = {
    "regex": /^.{4,30}$/,
    "length": 30,
    "message": "Name must be at least 4 characters long."
  data.forms.description = {
    "regex": /^.{20,300}$/,
    "length": 300,
    "message": "Description must be at least 20 characters long."
  data.forms.price = {
    "regex":/^\d+$/,
    "length": 50,
    "message": "Use only digits."
  };
function validateString(string, validation){
  if(string == ""){
    return "empty";
  if(string.length > validation.length){
    return "long";
  if(!validation.regex.test(string)){
    return "incorrect";
```

```
return "valid";
function validateElement(element, validation){
  let fieldName = $(element).attr("placeholder");
  let fieldValidation = validateString($(element).val(), validation);
  if(fieldValidation == "empty"){
    formError(element, `Please input ${fieldName.toLowerCase()}.`);
  if(fieldValidation == "long"){
    formError(element, `${fieldName} is too long. Maximum characters: ${validation.length}.`);
  else if(fieldValidation == "incorrect"){
    formError(element, `${fieldName} is invalid. ${validation.message}`);
function formError(element, message){
  $(`${message}`).insertAfter($(element));
  data.forms.error = true;
function resetFormMessages(){
  $(".form-error").remove();
  $(".form-success").remove();
function validateProductForm(e){
  data.forms.error = false;
  resetFormMessages();
  let name = $("[name=name]");
  let price = $("[name=price]");
  let description = $("[name=description]");
  validateElement(name, data.forms.name);
  validateElement(price, data.forms.price);
  validateElement(description, data.forms.description);
  if(!$("#colors input:checked").length){
    formError($("#colors"), "You must check at least one color.");
  if(!$("#first-file")[0].files.length){
```

```
formError($("#first-file"), "First image field must not be empty.");
}

if(data.forms.error){
    e.preventDefault();
}
```

3.9.2 lookbook.js

```
$(document).ready(function(){
  prepareInput();
  $(".add-pin").click(addPin);
  $(".pin-circle").hide();
  $(document).on("click", ".check-pin", showPinCircle);
  $(document).on("click",".remove-pin", removePin);
  $(document).on("input",".product, .pos-x, .pos-y", prepareInput);
  $("#update-form").submit(function(e){
    validate(e);
  });
function showPinCircle(){
  let x = Number($(this).parents(".product-pin").find(".pos-x").val());
  let y = Number($(this).parents(".product-pin").find(".pos-y").val());
  $(".pin-circle")
    .css({
       "left": `${x}%`,
       "top": `${y}%`
    })
    .stop(true, true)
    .fadeIn("fast")
    .delay(3000)
    .fadeOut("fast");
  $("html").animate({
    scrollTop: $("#idea-image").offset().top
  }, 200);
```

```
function addPin(){
  let html = `
      <div class="product-pin col-md-12 mt-5">
        <input type="hidden" class="final-input" name="pins[]" value=""/>
        <div>
           <label>Left:</label>
           <input type="number" value="" min="1" max="99" class="pos-x form-control">
           <span class="text-muted h4">%</span>
           <label class="ml-5">Top:</label>
           <input type="number" value="" min="1" max="99" class="pos-y form-control">
           <span class="text-muted h4">%</span>
           <label class="ml-5">product id:</label>
           <input type="text" class="form-control product"/>
        </div>
        <div class="mt-3">
           <a href="#!" class="check-pin btn btn-fill btn-info">Check coordinates</a>
           <a href="#!" class="btn btn-fill btn-danger remove-pin ml-5">
             <i class="pe-7s-less"></i> Remove pin
           </a>
        </div>
        <div class="mt-3">
        </div>
      </div>`;
    $(html).appendTo($("#pins"));
function removePin(){
  $(this).parents(".product-pin").remove();
function prepareInput(){
  $(".product-pin").each(function(){
    let x = Number($(this).find(".pos-x").val());
    let y = Number($(this).find(".pos-y").val());
```

```
if(Number.isNaN(x)){
      $(this).find(".pos-x").val("");
    if(x < 0 \mid \mid x > 99){
      (this).find(".pos-x").val(x < 0 ? "1" : "99");
    if(Number.isNaN(y)){
       $(this).find(".pos-y").val("");
    if(y < 0 | y > 99){
      $(this).find(".pos-y").val(y < 0 ? "1" : "99");
    x = \frac{(this).find(".pos-x").val();}
    y = $(this).find(".pos-y").val();
    let product = $(this).find(".product").val();
    $(this).find(".final-input").val(`${x},${y},${product}`);
  });
function validate(e){
  $(".pos-x, .pos-y, .product").each(function(){
    if($(this).val() == "" || $(this).val() == "0"){
      e.preventDefault();
      $(this).addClass("form-error-border");
    else {
      $(this).removeClass("form-error-border");
 });
```

3.10 resources/views/components/product

```
<div class="{{ $class }}">
  <div class="item text-center">
    <div class="product-miniature first-item js-product-miniature item-one">
      <div class="thumbnail-container">
        <a href="{{ route("product", ["product"=>$id]) }}">
          <img class="img-fluid image-cover" src="{{ asset("img/product/$img1") }}" alt="{{ $name }}">
          <img class="img-fluid image-secondary" src="{{ asset("img/product/$img2") }}" alt="{{ $name }}">
      </div>
      <div class="product-description">
        <div class="product-groups">
          <div class="product-title">
             <a href="{{ route("product", ["product"=>$id]) }}">{{ $name }}</a>
          </div>
          <div class="product-group-price">
             <div class="product-price-and-shipping">
               <span class="price">$ {{ $price }}</span>
             </div>
          </div>
        </div>
      </div>
    </div>
  </div>
</div>
```

3.11 resources/views/errors/error

```
<div class="image">
                <img class="img-fluid" src="{{ asset("img/other/image-404.png") }}" alt="Image error">
              <h2 class="h4">We're sorry — something has gone wrong on our end.</h2>
              <div class="info">
                If difficulties persist, please contact the System Administrator of this site and report
                  the error below.
              </div>
              <a class="btn btn-default" href="{{ route("home") }}">
                <i class="fa fa-home" aria-hidden="true"></i>
                <span>Back to homepage
              </a>
            </div>
            <div class="content-right-404 col-lg-6 col-sm-6 text-center">
              <a href="#">
                <img class="img-fluid" src="{{ asset("img/other/background.jpg") }}" alt="image 404 right">
            </div>
          </div>
        </div>
      </section>
   </div>
 </div>
@endsection
```

3.12 resources/views/main/contact-form

```
<img src="{{ $message->embed(public_path()."/img/logo.png") }}" alt="furnishop">
<h2>New message from contact form</h2>
<h4>Name: {{ $name }}</h4>
<h4>E-mail: {{ $email }}</h4>
<h4>Subject: {{ $subject }}</h4>
<br/>
<h2>Message:</h4>
{{ $messageContent }}
```

3.13 views/resources/admin/layout

```
<!doctype html>
<html lang="en">
@include("admin.fixed.head")
<body>
@include("admin.fixed.sidebar")
<div class="wrapper">
 <div class="main-panel">
    @include("admin.fixed.nav")
    <div class="content">
      <div class="container-fluid">
        <div class="row">
          @yield("content")
        </div>
      </div>
    </div>
    @include("admin.fixed.footer")
  </div>
</div>
@include("admin.fixed.scripts")
</body>
</html>
```

3.14 views/resources/admin/fixed

3.14.1 footer

```
</div>
</footer>
```

3.14.2 head

```
<head>
  <meta charset="utf-8" />
  <link rel="icon" type="image/png" href="{{ asset("admin-assets/img/favicon.ico") }}">
  <meta http-equiv="X-UA-Compatible" content="IE=edge,chrome=1" />
  <title>@yield("title")</title>
  <meta content='width=device-width, initial-scale=1.0, maximum-scale=1.0, user-scalable=0'</pre>
name='viewport' />
  <meta name="viewport" content="width=device-width" />
  <!-- Bootstrap core CSS -->
  <link href="{{ asset("admin-assets/css/bootstrap.min.css") }}" rel="stylesheet" />
  <!-- Animation library for notifications -->
  <link href="{{ asset("admin-assets/css/animate.min.css") }}" rel="stylesheet"/>
  <!-- Light Bootstrap Table core CSS -->
  <link href="{{ asset("admin-assets/css/light-bootstrap-dashboard.css?v=1.4.0") }}" rel="stylesheet"/>
  <!-- Fonts and icons -->
  k href="http://maxcdn.bootstrapcdn.com/font-awesome/4.2.0/css/font-awesome.min.css"
rel="stylesheet">
  <link href='http://fonts.googleapis.com/css?family=Roboto:400,700,300' rel='stylesheet' type='text/css'>
  <link href="{{ asset("admin-assets/css/pe-icon-7-stroke.css") }}" rel="stylesheet" />
  <!-- My CSS -->
  <link href="{{ asset("admin-assets/css/custom.css") }}" rel="stylesheet"/>
</head>
```

3.14.3 nav

```
<span class="icon-bar"></span>
       <span class="icon-bar"></span>
       <span class="icon-bar"></span>
     </button>
     <a class="navbar-brand" href="{{ route("home") }}"><i class="pe-7s-angle-left"></i> Back to front</a>
   </div>
   <div class="collapse navbar-collapse">
     ul class="nav navbar-nav navbar-left">
     ul class="nav navbar-nav navbar-right">
         <a href="{{ route("logout") }}">
           Sign out
         </a>
       </div>
 </div>
</nav>
```

3.14.4 scripts

```
<!-- Core JS Files -->
<script src="{{ asset("admin-assets/js/jquery.3.2.1.min.js") }}" type="text/javascript"></script>
<script src="{{ asset("admin-assets/js/bootstrap.min.js") }}" type="text/javascript"></script>
<!-- Charts Plugin -->
<script src="{{ asset("admin-assets/js/chartist.min.js") }}"></script>
<!-- Notifications Plugin -->
<script src="{{ asset("admin-assets/js/bootstrap-notify.js") }}"></script>

<script src="{{ asset("admin-assets/js/bootstrap-notify.js") }}"></script>

@yield("page_script")
```

3.14.5 sidebar

```
<div class="sidebar" data-color="purple" data-image="{{ asset("admin-assets/img/sidebar-5.jpg") }}">
```

```
<div class="sidebar-wrapper">
   <div class="logo">
     <a href="{{ route("home") }}" class="simple-text">
       <img src="{{ asset("img/mobile-logo.png") }}" alt="furnishop"/>
     </a>
   </div>
   @foreach($menu as $link)
     routels($link["route"]))
       class="active"
       @endif>
       <a href="{{ route($link["route"]) }}">
         <i class="{{ $link["icon"] }}"></i>
         {{ $link["name"] }}
       </a>
     @endforeach
   </div>
</div>
```

3.15 views/resources/admin/pages

3.15.1 dashboard

```
@foreach($categories as $cat)
           <option value="{{ $cat->id }}"
                @if($featuredCategory == $cat->id) selected @endif>
              {{ $cat->name }}
           </option>
         @endforeach
       </select>
       <button type="submit" class="btn btn-info btn-fill mt-3">Change</button>
     </div>
   </div>
   @csrf
   @method("PUT")
 </form>
 @if($errors->any())
   @foreach($errors->all() as $error)
     {{ $error }}
   @endforeach
 @endif
 <div class="row mt-5 card stats">
   <h3 class="ml-3">Stats</h3>
   <div class="col-md-12">
     <label>Total products: </label> <span class="h5 ml-3">{{ $productCount }}</span> <br>
     <label>Total users: </label> <span class="h5 ml-3">{{ $userCount }}</span> <br>
     <label>Total items added to carts: </label> <span class="h5 ml-3">{{ $inCart }}</span>
   </div>
 </div>
@endsection
```

3.15.2 log

```
@extends("admin.layout")
@section("title", "Furnishop | Admin Panel | Logs")
@section("content")
 <h2 class="col-12"> Logs </h2>
 <br>
 <div class="col-12">
   <div class="card">
     <div class="header">
       <form action="{{ route("admin.log") }}" method="get">
          <div class="pull-left">
            Select category:
            <select class="form-control" name="category">
              <option value="">All categories
              @foreach($logCategories as $cat)
                <option value="{{$cat->id}}"
                @if(request("category") == $cat->id) selected @endif>{{ $cat->name }}</option>
              @endforeach
            </select>
          </div>
          <div class="ml-3 pull-left">
            Sort by:
            <select class="form-control" name="sort">
              <option value="created at-desc"</pre>
              @if(request("sort") == "created_at-desc") selected @endif>Latest</option>
              <option value="created at-asc"</pre>
              @if(request("sort") == "created at-asc") selected @endif>Oldest</option>
              <option value="message-asc"</pre>
              @if(request("sort") == "message-asc") selected @endif>Message ASC</option>
              <option value="message-desc"</pre>
              @if(request("sort") == "message-desc") selected @endif>Message DESC</option>
            </select>
          </div>
          <div class="ml-3 pull-left">
            <br>
            <button type="submit" class="btn btn-info btn-fill">Go</button>
          </div>
       </form>
     </div>
     <div class="content table-responsive table-full-width">
```

```
<thead>
      Created
      IP adress
      Category
      Message
      </thead>
      @forelse($log as $item)
       {{ $item->created_at }}
       {{ $item->ip }}
       {{ $item->category->name }}
       {{ $item->message }}
      @empty
       No log items to show.
      @endforelse
      </div>
 </div>
  <span class="mx-3">Total: {{ $log->total() }}</span>
  <div class="mx-3">
    {{ $log->links() }}
  </div>
 </div>
</div>
```

3.16 views/resources/admin/pages/collections colors

3.16.1 collections_colors

```
@extends("admin.layout")
@section("title", "Furnishop | Admin Panel | Collections & Colors")
@section("content")
  @if(session("message"))
    <div class="alert alert-{{ session("class") }}">
      <span>{{ session("message") }}</span>
  @endif
 <h2 class="col-12"> Collections & Colors </h2>
  <a href="{{ route("admin_collection_color.create") }}" class="btn btn-success btn-fill">Add new</a>
 <div class="col-12 mt-5">
    <div class="card">
      <div class="header">
        <form action="{{ route("admin_collection_color.index") }}" method="get">
          <div class="pull-left">
            Select:
             <select class="form-control" name="show">
               <option value="collection"</pre>
               @if(request("show") == "collection") selected @endif>Collections</option>
               <option value="colors"</pre>
               @if(request("show") == "colors") selected @endif>Colors</option>
            </select>
          </div>
          <div class="ml-3 pull-left">
            Sort by:
            <select class="form-control" name="sort">
               <option value="name-asc"</pre>
                   @if(request("sort") == "name-asc") selected @endif>Name ASC</option>
               <option value="name-desc"</pre>
                   @if(request("sort") == "name-desc") selected @endif>Name DESC</option>
```

```
</select>
        </div>
        <div class="ml-3 pull-left">
          <button type="submit" class="btn btn-info btn-fill">Go</button>
        </div>
      </form>
     </div>
     <div class="content table-responsive table-full-width">
      <thead>
        Name
        Delete
        </thead>
        @forelse($items as $item)
            {{ $item->name }}
              <form action="{{ route("admin_collection_color.destroy",</pre>
["admin_collection_color"=>$item->id]) }}" method="post">
               <input type="hidden" name="table" value="{{ $show }}"/>
               <button type="sumbit" class="small-btn btn btn-danger btn-fill">
                 <i class="big pe-7s-close"></i>
               </button>
               @method("DELETE")
               @csrf
             </form>
            @empty
            No items to show.
          @endforelse
```

```
</div>
</div>
<div>
<span class="mx-3">Total: {{ $items->total() }}</span>
<div class="mx-3">
{{ $items->links() }}
</div>
</div>
</div>
</div>
@endsection
```

3.16.2 collectoins colors create

```
<div class="row">
          <div class="col-md-12">
            <div class="form-group">
              <label>Select</label>
              <select name="table" class="form-control">
                <option value="collections" @if(old("table") == "collections") selected @endif</pre>
>Collection</option>
                <option value="colors" @if(old("table") == "colors") selected @endif >Color
              </select>
            </div>
          </div>
        </div>
        <div class="row">
          <div class="col-md-12">
            <div class="form-group">
              <label>Name</label>
              <input type="text" name="name" class="form-control" placeholder="Name" value="{{</pre>
old("name") ?? "" }}">
            </div>
          </div>
        </div>
        <button type="submit" class="btn btn-info btn-fill pull-left">Create</button>
        <div class="clearfix"></div>
        @csrf
      </form>
    </div>
  </div>
  <div class="offset-lg-4 offset-xl-6"></div>
  <div class="col-md-12">
    @if($errors->any())
      @foreach($errors->all() as $error)
        {{ $error }}
      @endforeach
    @endif
```

```
</div>
@endsection
```

3.17 views/resources/admin/pages/lookbook

3.17.1 lookbook

```
@extends("admin.layout")
@section("title", "Furnishop | Admin Panel | Lookbook")
@section("content")
  @if(session("message"))
    <div class="alert alert-{{ session("class") }}">
      <span>{{ session("message") }}</span>
    </div>
  @endif
  <h2 class="col-12"> Lookbook </h2>
  </div>
  <a href="{{ route("admin_lookbook.create") }}" class="btn btn-success btn-fill">Add new idea</a>
    <div class="col-12 mt-5">
      <div class="card">
        <div class="header">
          <form action="{{ route("admin_lookbook.index") }}" method="get">
             <div class="pull-left ml-3">
               Select category:
               <select class="form-control" name="category">
                 <option value="">All</option>
                 @foreach($categories as $cat)
                   <option value="{{ $cat->id }}"
                        @if(request("category") == $cat->id) selected @endif>
                     {{ $cat->name }}
                   </option>
                 @endforeach
```

```
</select>
   </div>
   <div class="ml-3 pull-left">
     Sort by:
     <select class="form-control" name="sort">
       <option value="created_at-desc"</pre>
           @if(request("sort") == "created_at-desc") selected @endif>Latest</option>
       <option value="created at-asc"</pre>
           @if(request("sort") == "created_at-asc") selected @endif>Oldest</option>
       <option value="name-asc"</pre>
           @if(request("sort") == "name-asc") selected @endif>Name ASC</option>
       <option value="name-desc"</pre>
           @if(request("sort") == "name-desc") selected @endif>Name DESC</option>
     </select>
   </div>
   <div class="ml-3 pull-left">
     <br>
     <button type="submit" class="btn btn-info btn-fill">Go</button>
   </div>
 </form>
</div>
<div class="content table-responsive table-full-width">
 <thead>
   Created
   Image
   Name
   Category
   View
   Remove
   pinned <br>products
   </thead>
   @forelse($lookbook as $item)
       {{ $item->created at }}
       <div class="product-image">
```

```
<img src="{{ asset("img/lookbook/".$item->image) }}" alt="{{ $item->name }}">
                 </div>
               {{ $item->name }}
                 {{ $item->category->name }}
               <a href="{{ route("lookbook.category", ["category" => $item->category_id])."#lookbook-
idea-".$item->id }}" class="small-btn btn btn-success btn-fill" target="_blank">
                   <i class="big pe-7s-look"></i>
                 </a>
               <form action="{{ route("admin_lookbook.destroy", ["admin_lookbook"=>$item->id]) }}"
method="post">
                   <button type="sumbit" class="small-btn btn btn-danger btn-fill">
                     <i class="big pe-7s-close"></i>
                   </button>
                   @method("DELETE")
                   @csrf
                 </form>
               <form action="{{ route("admin_lookbook.edit", ["admin_lookbook"=>$item->id]) }}"
method="get">
                   <button type="sumbit" class="small-btn btn btn-secondary btn-fill">
                     <i class="big pe-7s-photo-gallery"></i>
                   </button>
                 </form>
               @empty
               No items to show.
             @endforelse
```

```
</div>
</div>
<div>
<div>
<span class="mx-3">Total: {{ $lookbook->total() }}</span>
<div class="mx-3">

{{ $lookbook->links() }}

</div>
</div>
</div>
@endsection
```

3.17.2 lookbook_create_idea

```
<div class="row">
          <div class="col-md-12">
            <div class="form-group">
              <label>Main category</label>
              <select name="category" class="form-control">
                @foreach($categories as $cat)
                  <option value="{{ $cat->id }}"
                  @if(old("category") == $cat->id) selected @endif>
                    {{ $cat->name }}
                  </option>
                @endforeach
              </select>
            </div>
          </div>
        </div>
        <div class="row">
          <div class="col-md-12">
            <div class="form-group">
              <label>idea name</label>
              <input type="text" name="name" class="form-control" placeholder="Name" value="{{</pre>
old("name")}}">
            </div>
          </div>
        </div>
        <div class="row">
          <div class="col-md-12">
            <div class="form-group">
              <label>Image</label>
              <input type="file" name="image" class="form-control">
            </div>
          </div>
        </div>
        <br>
        <button type="submit" class="btn btn-info btn-fill pull-left">Create</button>
        <div class="clearfix"></div>
        In the next step you'll be offered to pin products
```

```
@csrf

</form>
<br/>
<br/>
</div>
<div class="offset-Ig-4 offset-xI-6"></div>

<div class="col-md-12">

@if($errors->any())

@foreach($errors->all() as $error)

{{ $error }}
@endforeach
@endif
</div>

@endsection
```

3.17.3 lookbook_edit_idea

```
<div class="card col-lg-8 col-xl-6">
    <div class="header">
      <h4 class="title">Edit Lookbook Idea</h4>
    </div>
    <div class="content">
      <form id="update-form" action="{{ route("admin_lookbook.update", ["admin_lookbook"=>$idea->id])
}}" method="post" >
        <div class="row">
          <div id="idea-image" class="col-md-12">
             <img class="img-responsive" src="{{ asset("img/lookbook/".$idea->image) }}" alt="{{ $idea-
>name }}">
            <span class="pin-circle"></span>
          </div>
             <label>{{ $idea->name }}</label>
          </div>
        </div>
        <div id="pins" class="row mt-5">
          @foreach($idea->items as $item)
             <div class="product-pin col-md-12 mt-5">
               <input type="hidden" class="final-input" name="pins[]" value=""/>
                 <label>Left:</label>
                 <input type="number" value="{{ $item->position_x }}" min="1" max="99" class="pos-x
form-control">
                 <span class="text-muted h4">%</span>
                 <label class="ml-5">Top:</label>
                 <input type="number" value="{{ $item->position_y }}" min="1" max="99" class="pos-y
form-control">
                 <span class="text-muted h4">%</span>
                 <label class="ml-5">product id:</label>
                 <input type="text" class="form-control product" value="{{ $item->product_id }}"/>
               </div>
               <div class="mt-3">
```

```
<a href="#!" class="check-pin btn btn-fill btn-info">Check coordinates</a>
              <a href="#!" class="btn btn-fill btn-danger remove-pin ml-5">
                <i class="pe-7s-less"></i> Remove pin
              </a>
            </div>
            <div class="mt-3">
            </div>
          </div>
          @endforeach
      </div>
      <div class="row">
        <div class="col-md-12 mt-5">
          <a href="#!" class="add-pin">
            <i class="pe-7s-plus"></i> Add product pin
          </a>
        </div>
      </div>
      <button type="submit" class="btn btn-info btn-fill pull-left">Done</button>
      <div class="clearfix"></div>
      @csrf
      @method("PUT")
    </form>
  </div>
</div>
<div class="offset-lg-4 offset-xl-6"></div>
<div class="col-md-12">
  @if($errors->any())
    @foreach($errors->all() as $error)
      {{ $error }}
    @endforeach
  @endif
</div>
```

```
@endsection
@section("page_script")
  <script src="{{ asset("admin-assets/js/lookbook.js") }}"></script>
@endsection
```

3.18 views/resources/admin/pages/products

3.18.1 product create

```
@extends("admin.layout")
@section("title", "Furnishop | Admin Panel | Create Product")
@section("content")
  @if(session("message"))
    <div class="alert alert-{{ session("class") }}">
      <span>{{ session("message") }}</span>
    </div>
  @endif
  <div class="col-12">
    <a href="{{ route("admin_product.index") }}">< Back to Products</a>
  </div>
  <div class="card col-lg-8 col-xl-6">
    <div class="header">
      <h4 class="title">Create Product</h4>
    </div>
    <div class="content">
      <form action="{{ route("admin_product.store") }}" method="post" enctype="multipart/form-data">
        <div class="row">
           <div class="col-md-12">
             <div class="form-group">
               <label>subcategories</label>
               <div id="subcategories" data-categories="{{ $categories }}" data-selected="{{ implode(",",</pre>
old("subcategories") ?? []) }}">
               </div>
```

```
<a href="#!" id="add-subcat">
                 <i class="pe-7s-plus"></i> Add subcategory
               </a>
             </div>
           </div>
        </div>
        <div class="row">
           <div class="col-md-12">
             <div class="form-group">
               <label>Name</label>
               <input type="text" name="name" class="form-control" placeholder="Name" value="{{</pre>
old("name") }}">
             </div>
           </div>
        </div>
        <div class="row">
           <div class="col-md-6">
             <div class="form-group">
               Colors
               <div id="colors" class="d-flex flex-wrap">
                 @foreach($colors as $color)
                   <div class="mx-3">
                   <input type="checkbox" id="color-{{ $color->id }}" name="colors[]" value="{{ $color->id
}}" @if(in_array($color->id, old("colors") ?? [])) checked @endif
                   > <label class="text-black" for="color-{{$color->id}}">{{ $color->name }}</label>
                     </div>
                 @endforeach
               </div>
             </div>
           </div>
           <div class="col-md-6">
             <div class="form-group">
               <label>Collection</label>
               <select name="collection" class="form-control">
                 <option value="">None</option>
                 @foreach($collections as $coll)
                   <option value="{{ $coll->id }}"
                   @if($coll->id == old("collection")) selected @endif >
                      {{ $coll->name }}</option>
                 @endforeach
```

```
</select>
             </div>
             <div class="form-group">
               <label>Price</label>
               <input type="number" class="form-control" min="0" name="price" placeholder="Price"
value="{{ old("price") }}">
             </div>
          </div>
        </div>
        <div class="row">
          <div class="col-md-12">
             <label>Description</label>
             <textarea class="form-control" placeholder="Description" name="description">{{
old("description") }}</textarea>
          </div>
        </div>
        <div class="row">
          <div class="col-md-12">
             <label >Images (Min. 1)</label>
               <input type="file" id="first-file" name="images[]">
             </div>
             <div id="js-images" class="my-3">
             </div>
             <a href="#!" id="add-image"><i class="pe-7s-plus"></i> Add image</a>
          </div>
        </div>
        <button type="submit" class="btn btn-info btn-fill pull-left mt-3">Create</button>
        <div class="clearfix"></div>
        @csrf
      </form>
```

3.18.2 product edit

```
<div class="content">
      <form action="{{ route("admin_product.update", ["admin_product"=>$product->id]) }}"
method="post" enctype="multipart/form-data">
        <div class="row">
          <div class="col-md-12">
             <div class="form-group">
               <label>subcategories</label>
               <div id="subcategories" data-categories="{{ $categories }}"</pre>
                  data-selected="{{ old("subcategories") ? implode(",", old("subcategories")) : implode(",",
$product->categories->map(function($item){return $item->id;})->toArray()) }}">
               </div>
               <a href="#!" id="add-subcat">
                 <i class="pe-7s-plus"></i> Add subcategory
               </a>
             </div>
          </div>
        </div>
        <div class="row">
          <div class="col-md-12">
             <div class="form-group">
               <label>Name</label>
               <input type="text" name="name" class="form-control" placeholder="Name" value="{{</pre>
old("name") ?? $product->name }}">
             </div>
          </div>
        </div>
        <div class="row">
          <div class="col-md-6">
             <div class="form-group">
               Colors
               <div class="d-flex flex-wrap">
                 @foreach($colors as $color)
                   <div class="mx-3">
                     <input type="checkbox" id="color-{{ $color->id }}" name="colors[]" value="{{ $color->id
}}"
                      @if(old("colors") ? in_array($color->id, old("colors")) : in_array($color->id, $product-
>colors->map(function($item){return $item->id;})->toArray())) checked @endif>
                     <label class="text-black" for="color-{{$color->id}}">{{ $color->name }}</label>
                   </div>
                 @endforeach
```

```
</div>
            </div>
          </div>
          <div class="col-md-6">
            <div class="form-group">
               <label>Collection</label>
               <select name="collection" class="form-control">
                 <option value="">None</option>
                 @foreach($collections as $coll)
                   <option value="{{ $coll->id }}"
                   @if(old("collection") ? old("collection") == $coll->id: ($product->collection? $product-
>collection->id: "") == $coll->id) selected @endif>{{ $coll->name }}</option>
                 @endforeach
               </select>
            </div>
             <div class="form-group">
               <label>Price</label>
               <input type="number" class="form-control" min="0" name="price" value="{{ old("price") ??</pre>
$product->price }}">
            </div>
          </div>
        </div>
        <div class="row">
          <div class="col-md-12">
            <label>Description</label>
            <textarea class="form-control" name="description" >{{ old("description") ?? $product-
>description }}</textarea>
          </div>
        </div>
        <div class="row mt-5">
          <input type="checkbox" id="change_images" name="change_images"/> <label
for="change_images">Replace images</label> <br>
        </div>
        <div id="images-wrapper" class="row mt-5 d-none">
          <div class="col-md-12">
             <label >Images (Min. 1)</label>
```

```
<input type="file" name="images[]">
            </div>
            <div id="js-images" class="my-3">
            </div>
            <a href="#!" id="add-image"><i class="pe-7s-plus"></i> Add image</a>
          </div>
       </div>
        <button type="submit" class="btn btn-info btn-fill pull-left mt-3">Done</button>
        <div class="clearfix"></div>
        @csrf
        @method("PUT")
     </form>
   </div>
 </div>
 <div class="offset-lg-4 offset-xl-6"></div>
 <div class="col-md-12">
   @if($errors->any())
     @foreach($errors->all() as $error)
       {{ $error }}
     @endforeach
    @endif
 </div>
@endsection
@section("page_script")
 <script src="{{ asset("admin-assets/js/product.js") }}"></script>
@endsection
```

```
@extends("admin.layout")
@section("title", "Furnishop | Admin Panel | Products")
@section("content")
 @if(session("message"))
   <div class="alert alert-{{ session("class") }}">
      <span>{{ session("message") }}</span>
   </div>
 @endif
 <h2 class="col-12"> Products </h2>
 </div>
 <a href="{{ route("admin_product.create") }}" class="btn btn-success btn-fill">Add new</a>
   <div class="col-12 mt-5">
      <div class="card">
        <div class="header">
          <form action="{{ route("admin_product.index") }}" method="get">
            <div class="pull-left">
               Keywords:
               <input type="text" class="form-control" name="keywords" value="{{ request("keywords") ??</pre>
"" }}"/>
            </div>
            <div class="pull-left ml-3">
               Select category:
               <select class="form-control" name="category">
                 <option value="">All</option>
                 @foreach($categories as $cat)
                   <option value="{{ $cat->id }}"
                        @if(request("category") == $cat->id) selected @endif>
                     {{ $cat->name }}
                   </option>
                   @foreach($cat->subcategories as $sub)
                     <option value="{{ $sub->id }}"
```

```
@if(request("category") == $sub->id) selected @endif>
                 {{ $sub->name }}
            </option>
          @endforeach
        @endforeach
      </select>
    </div>
    <div class="ml-3 pull-left">
      Sort by:
      <select class="form-control" name="sort">
        <option value="created at-desc"</pre>
            @if(request("sort") == "created_at-desc") selected @endif>Latest</option>
        <option value="created at-asc"</pre>
            @if(request("sort") == "created_at-asc") selected @endif>Oldest</option>
        <option value="name-asc"</pre>
            @if(request("sort") == "name-asc") selected @endif>Name ASC</option>
        <option value="name-desc"</pre>
            @if(request("sort") == "name-desc") selected @endif>Name DESC</option>
        <option value="price-asc"</pre>
            @if(request("sort") == "price-asc") selected @endif>Price ASC</option>
        <option value="price-desc"</pre>
            @if(request("sort") == "price-desc") selected @endif>Price DESC</option>
      </select>
    </div>
    <div class="ml-3 pull-left">
      <button type="submit" class="btn btn-info btn-fill">Go</button>
    </div>
  </form>
</div>
<div class="content table-responsive table-full-width">
  <thead>
     Created
      ID
     Image
      Name
     Price
     Categories
```

```
Colors
             Collection
             View
             Set <br>Inactive
             Edit
           </thead>
           @forelse($products as $item)
               {{ date("Y-m-d", strtotime($item->created_at)) }}
                 {{ $item->id }}
               <div class="product-image">
                  <img src="{{ asset("img/product/".$item->images->get(0)->thumbnail_filename) }}"
alt="{{ $item->name }}">
                 </div>
               {{ $item->name }}
               ${{ $item->price }}
                 @foreach($item->categories as $cat)
                   <span class="text-muted">{{$cat->mainCategory->name}}</span> - {{ $cat->name }}
                   @if(!$loop->last) <br> @endif
                 @endforeach
               @foreach($item->colors as $color)
                  <span>{{$color->name}}</span>
                   @if(!$loop->last) <br> @endif
                 @endforeach
               @if($item->collection)
                  {{ $item->collection->name }}
                 @else
                  <span class='text-muted'>None</span>
                 @endif
               <a href="{{ route("product", ["product" => $item->id]) }}" class="small-btn btn btn-
```

```
success btn-fill" target="_blank">
                   <i class="big pe-7s-look"></i>
               <form action="{{ route("admin_product.destroy", ["admin_product"=>$item->id]) }}"
method="post">
                   <button type="sumbit" class="small-btn btn btn-danger btn-fill">
                     <i class="big pe-7s-close"></i>
                   </button>
                   @method("DELETE")
                   @csrf
                 </form>
               <form action="{{ route("admin_product.edit", ["admin_product"=>$item->id]) }}"
method="get">
                   <button type="sumbit" class="small-btn btn btn-secondary btn-fill">
                     <i class="big pe-7s-note"></i>
                   </button>
                 </form>
               @empty
               No products to show.
             @endforelse
           </div>
     </div>
        <span class="mx-3">Total: {{ $products->total() }}</span>
```

```
<div class="mx-3">
     {{ $products->links() }}
     </div>
     </div>
     </div>
@endsection
```

3.19 views/resources/admin/pages/subcategories

3.19.1 subcategories

```
@extends("admin.layout")
@section("title", "Furnishop | Admin Panel | Subcategories")
@section("content")
  @if(session("message"))
    <div class="alert alert-{{ session("class") }}">
      <span>{{ session("message") }}</span>
    </div>
  @endif
  <h2 class="col-12"> Subcategories </h2>
  </div>
    <a href="{{ route("admin_subcategory.create") }}" class="btn btn-success btn-fill">Add new</a>
  <div class="col-12 mt-5">
    <div class="card">
      <div class="header">
         <form action="{{ route("admin_subcategory.index") }}" method="get">
           <div class="pull-left">
             Keywords:
             <input type="text" class="form-control" name="keywords" value="{{ request("keywords") ?? ""</pre>
}}"/>
```

```
</div>
    <div class="pull-left ml-3">
      Select main category:
      <select class="form-control" name="main-category">
        <option value="">All</option>
        @foreach($mainCategories as $cat)
          <option value="{{ $cat->id }}"
          @if(request("main-category") == $cat->id) selected @endif>
            {{ $cat->name }}
          </option>
        @endforeach
      </select>
    </div>
    <div class="ml-3 pull-left">
      Sort by:
      <select class="form-control" name="sort">
        <option value="name-asc"</pre>
            @if(request("sort") == "name-asc") selected @endif>Name ASC</option>
        <option value="name-desc"</pre>
            @if(request("sort") == "name-desc") selected @endif>Name DESC</option>
        <option value="created at-desc"</pre>
            @if(request("sort") == "created_at-desc") selected @endif>Latest</option>
        <option value="created at-asc"</pre>
            @if(request("sort") == "created_at-asc") selected @endif>Oldest</option>
      </select>
    </div>
    <div class="ml-3 pull-left">
      <button type="submit" class="btn btn-info btn-fill">Go</button>
    </div>
  </form>
</div>
<div class="content table-responsive table-full-width">
  <thead>
    Name
    Main Category
    Delete
```

```
</thead>
         @forelse($subcategories as $item)
            {{ $item->name }}
            {{ $item->mainCategory->name }}
              <form action="{{ route("admin_subcategory.destroy", ["admin_subcategory"=>$item->id])
}}" method="post">
                <button type="sumbit" class="small-btn btn btn-danger btn-fill">
                  <i class="big pe-7s-close"></i>
                </button>
                @method("DELETE")
                @csrf
              </form>
            @empty
            No categories to show.
          @endforelse
         </div>
   </div>
     <span class="mx-3">Total: {{ $subcategories->total() }}</span>
     <div class="mx-3">
       {{ $subcategories->links() }}
     </div>
```

```
</div>
</div>
@endsection
```

3.19.2 subcategory_create

```
@extends("admin.layout")
@section("title", "Furnishop | Admin Panel | Create Subcategory")
@section("content")
 <div class="col-12">
    <a href="{{ route("admin_subcategory.index") }}">< Back to Subcategories</a>
 </div>
 <div class="card col-lg-8 col-xl-6">
    <div class="header">
      <h4 class="title">Create Subcategory</h4>
    </div>
    <div class="content">
      <form action="{{ route("admin_subcategory.store") }}" method="post">
        <div class="row">
          <div class="col-md-12">
            <div class="form-group">
              <label>Main category</label>
              <select name="main" class="form-control">
                 @foreach($mainCategories as $cat)
                   <option value="{{ $cat->id }}">
                     {{ $cat->name }}
                   </option>
                 @endforeach
```

```
</select>
            </div>
          </div>
        </div>
        <div class="row">
          <div class="col-md-12">
            <div class="form-group">
              <label>Subcategory name</label>
              <input type="text" name="name" class="form-control" placeholder="Name" value="{{</pre>
session("name") ?? "" }}">
            </div>
          </div>
        </div>
        <button type="submit" class="btn btn-info btn-fill pull-left">Create</button>
        <div class="clearfix"></div>
        @csrf
      </form>
    </div>
  </div>
  <div class="offset-lg-4 offset-xl-6"></div>
  <div class="col-md-12">
    @if($errors->any())
      @foreach($errors->all() as $error)
        {{ $error }}
      @endforeach
    @endif
  </div>
@endsection
```

3.20 views/resources/admin/pages/users

3.20.1 user edit

```
@extends("admin.layout")
@section("title", "Furnishop | Admin Panel | Edit User")
@section("content")
  <div class="col-12">
    <a href="{{ route("admin_user.index") }}">< Back to Users</a>
  </div>
  <div class="card col-lg-8 col-xl-6">
    <div class="header">
      <h4 class="title">Edit User</h4>
    </div>
    <div class="content">
      <form action="{{ route("admin_user.update", ["admin_user"=>$user->id]) }}" method="post">
        <div class="row">
          <div class="col-md-12">
             <div class="form-group">
               <label for="exampleInputEmail1">Email address</label>
               <input type="email" name="email" class="form-control" placeholder="Email" value="{{ $user-</p>
>email }}">
             </div>
          </div>
        </div>
        <div class="row">
          <div class="col-md-6">
             <div class="form-group">
               <label>First Name</label>
               <input type="text" name="first" class="form-control" placeholder="Company" value="{{</pre>
$user->first_name }}">
             </div>
          </div>
          <div class="col-md-6">
             <div class="form-group">
               <label>Last Name</label>
               <input type="text" name="last" class="form-control" placeholder="Last Name" value="{{</pre>
```

```
$user->last_name }}">
            </div>
          </div>
        </div>
        <button type="submit" class="btn btn-info btn-fill pull-left">Update Profile</button>
        <div class="clearfix"></div>
        <input type="hidden" name="id" value="{{ $user->id }}">
        @method("PUT")
      </form>
      <br>
    </div>
  </div>
  <div class="offset-lg-4 offset-xl-6"></div>
  <div class="col-md-12">
   @if($errors->any())
      @foreach($errors->all() as $error)
        {{ $error }}
      @endforeach
    @endif
  </div>
@endsection
```

3.20.2 users

```
<div class="col-12">
    <div class="card">
      <div class="header">
        <form action="{{ route("admin_user.index") }}" method="get">
          <div class="pull-left">
            Keywords:
            <input type="text" class="form-control" name="keywords" value="{{ request("keywords") ?? ""</pre>
}}"/>
          </div>
          <div class="ml-3 pull-left">
            Sort by:
            <select class="form-control" name="sort">
              <option value="created at-desc"</pre>
                  @if(request("sort") == "created_at-desc") selected @endif>Latest</option>
              <option value="created_at-asc"</pre>
                  @if(request("sort") == "created at-asc") selected @endif>Oldest</option>
              <option value="email-asc"</pre>
                  @if(request("sort") == "email-asc") selected @endif>Email ASC</option>
              <option value="email-desc"</pre>
                  @if(request("sort") == "email-desc") selected @endif>Email DESC</option>
            </select>
          </div>
          <div class="ml-3 pull-left">
            <button type="submit" class="btn btn-info btn-fill">Go</button>
          </div>
        </form>
      </div>
      <div class="content table-responsive table-full-width">
        <thead>
          Created
          Email
          First Name
          Last Name
          Delete
          Edit
          </thead>
          @forelse($users as $user)
```

```
{{ $user->created_at }}
            {{ $user->email }}
            {{ $user->first name }}
            {{ $user->last_name }}
              <form action="{{ route("admin_user.destroy", ["admin_user"=>$user->id]) }}"
method="post">
                <button type="sumbit" class="small-btn btn btn-danger btn-fill">
                  <i class="big pe-7s-close"></i>
                </button>
                @method("DELETE")
                @csrf
              </form>
            <form action="{{ route("admin_user.edit", ["admin_user"=>$user->id]) }}" method="get">
                <button type="sumbit" class="small-btn btn btn-secondary btn-fill">
                  <i class="big pe-7s-id"></i>
                </button>
              </form>
            @empty
            No users to show.
          @endforelse
         </div>
   </div>
```

3.21 views/resources/front/layout

```
@include("front.fixed.ie")

<html lang="zxx">
@include("front.fixed.head")
<body id="@yield("body_id")" class="@yield("body_class")">

@include("front.fixed.floating.loading")
@include("front.fixed.floating.top")

@include("front.fixed.header")

<div class="main-content">
@yield("content")
</div>
@include("front.fixed.floating.menus")
@include("front.fixed.floating.menus")
@include("front.fixed.footer")
@include("front.fixed.scripts")
```

3.22 views/resources/front/fixed

3.22.1 floating

3.22.1.1 loading

3.22.1.2 menus

```
<!-- menu mobie left -->
<div class="mobile-top-menu d-md-none">
  <button type="button" class="close" aria-label="Close">
    <i class="zmdi zmdi-close"></i>
  </button>
  <div class="tiva-verticalmenu block" data-count_showmore="17">
    <div class="box-content block-content">
      <div class="verticalmenu" role="navigation">
        @foreach($categories as $cat)
          <a href="{{ route("category", ["category"=>$cat->id]) }}" class="hasicon">
              <img src="{{ asset("img/categories/$cat->image") }}" alt="{{ $cat->name }}">{{ $cat->name }}"
}}</a>
            <span class="arrow collapsed" data-toggle="collapse" data-target="#mobile-cat-{{$cat->id}}"
aria-expanded="false" role="status">
                <i class="zmdi zmdi-minus"></i>
                <i class="zmdi zmdi-plus"></i>
              </span>
            <div class="subCategory collapse" id="mobile-cat-{{$cat->id}}" aria-expanded="true"
role="status">
```

```
<div class="menu-items">
                 @foreach($cat->subcategories as $sub)
                 class="item">
                   <a href="{{ route("category", ["category"=>$sub->id]) }}">{{ $sub->name }}</a>
                 @endforeach
               </div>
           </div>
         @endforeach
       </div>
   </div>
 </div>
</div>
<!-- menu mobie right -->
<div id="mobile-pagemenu" class="mobile-boxpage d-flex hidden-md-up active d-md-none">
 <div class="content-boxpage col">
   <div class="box-header d-flex justify-content-between align-items-center">
     <div class="title-box">Menu</div>
     <div class="close-box">Close</div>
   </div>
   <div class="box-content">
       <!-- Brand and toggle get grouped for better mobile display -->
       <div id="megamenu" class="clearfix">
         @foreach($menu as $link)
           <a href="{{ $link->route ? route($link->route) : "#!" }}">
               {{ $link->name }}
             </a>
             @if(count($link->menus))
```

```
<span class="arrow collapsed" data-toggle="collapse" data-target="#megamenu-{{$link->id}}"
aria-expanded="true" role="status">
               <i class="zmdi zmdi-minus"></i>
               <i class="zmdi zmdi-plus"></i>
             </span>
             <div class="subCategory collapse" id="megamenu-{{ $link->id }}" aria-expanded="true"
role="status">
                 @foreach($link->menus as $sublink)
                 class="item">
                   <a href="{{ route($sublink->route) }}" >{{ $sublink->name }}</a>
                 @endforeach
               </div>
             @endif
           @endforeach
           id="mobile-menu-separator">
            
               <i class="fa fa-user" aria-hidden="true"></i>
               {{ $accName }}
           @foreach($accMenu as $link)
             <a href="{{ route($link["route"]) }}">{{ $link["name"] }}</a>
           @endforeach
         </div>
```

```
</div>
</div>
</div>
```

3.22.1.3 top

3.22.2 footer

```
<footer class="footer-one">
 <div class="inner-footer">
   <div class="container">
     <div class="footer-top col-lg-12 col-xs-12">
       <div class="row">
         <div class="tiva-html col-lg-4 col-md-12 col-xs-12">
          <div class="block">
             <div class="block-content">
              <img src="{{ asset("img/logo.png") }}" alt="furnishop logo">
              Tailored To Your Needs
             </div>
          </div>
          <div class="block">
            <div class="block-content">
              <img class="img-fluid" src="{{ asset("img/other/payment-footer.png") }}" alt="payment">
              </div>
          </div>
         </div>
         <div class="tiva-html col-lg-4 col-md-6">
          <div class="block m-top">
            <div class="title-block">
              Contact Us
            </div>
             <div class="block-content">
              <div class="contact-us">
```

```
<div class="title-content">
          <i class="fa fa-home" aria-hidden="true"></i>
          <span>Address :</span>
        </div>
       <div class="content-contact address-contact">
          Zdravka Celara 16
       </div>
     </div>
     <div class="contact-us">
       <div class="title-content">
         <i class="fa fa-envelope" aria-hidden="true"></i>
          <span>Email :</span>
       </div>
       <div class="content-contact mail-contact">
          support@furnishop.com
       </div>
     </div>
     <div class="contact-us">
       <div class="title-content">
         <i class="fa fa-clock-o" aria-hidden="true"></i>
          <span>Opening Hours :</span>
       </div>
       <div class="content-contact hours-contact">
          Monday - Sunday / 08.00AM - 19.00
          <span>(Except Holidays)</span>
       </div>
     </div>
    </div>
 </div>
</div>
<div class="tiva-modules col-lg-4 col-md-6">
  <div class="block m-top">
 </div>
 <div class="block m-top1">
    <div class="block-content">
     <div class="social-content">
       <div class="title-block">
         Follow us on
       </div>
       <div id="social-block">
         <div class="social">
           <a href="#!">
                 <i class="fa fa-facebook"></i>
               </a>
```

```
<a href="#!">
                        <i class="fa fa-twitter"></i>
                      </a>
                    <a href="#!" >
                        <i class="fa fa-google"></i>
                      </a>
                    <a href="#!">
                        <i class="fa fa-instagram"></i>
                      </a>
                  </div>
               </div>
             </div>
           </div>
         </div>
         <div class="block m-top1">
           <div class="block-content">
             <div class="payment-content">
               <div class="title-block">
                 Payment accept
               </div>
               <div class="payment-image">
                <img class="img-fluid" src="{{ asset("img/other/payment.png") }}" alt="payment">
              </div>
             </div>
             <!-- Popup newsletter -->
           </div>
         </div>
       </div>
     </div>
   </div>
 </div>
</div>
<div id="tiva-copyright">
 <div class="container">
   <div class="row">
     <div class="text-center col-lg-12">
       Copyright © 2018. Design by TivaTheme. All Rights Reserved.
```

```
</span>
</div>
</div>
</div>
</div>
</div>
</div>
</div>
```

3.22.3 head

```
<head>
  <meta name="csrf-token" content="{{ csrf_token() }}">
  <script>
    const baseUrl = "{{ route("home") }}"
  </script>
  <meta http-equiv="Content-Type" content="text/html; charset=utf-8">
  <!-- Basic Page Needs -->
  <meta http-equiv="X-UA-Compatible" content="IE=edge">
  <title>@yield("title")</title>
  <meta name="keywords" content="Furniture, Decor, Interior">
  <meta name="description" content="Furnishop - Imagine the feeling of a home designed to fit your</p>
lifestyle and reflect your personality">
  <meta name="author" content="Mihailo Ilic">
  <!-- Mobile Meta -->
  <meta name="viewport" content="width=device-width, initial-scale=1, maximum-scale=1">
  <!-- Google Fonts -->
  <link href="https://fonts.googleapis.com/css?family=Poppins:400,500,600,700" rel="stylesheet">
  <!-- Vendor CSS -->
  <link rel="stylesheet" href=" {{ asset("libs/bootstrap/css/bootstrap.min.css") }} ">
  <link rel="stylesheet" href=" {{ asset("libs/font-awesome/css/font-awesome.min.css") }} ">
  <link rel="stylesheet" href=" {{ asset("libs/font-material/css/material-design-iconic-font.min.css") }} ">
  <link rel="stylesheet" href=" {{ asset("libs/nivo-slider/css/nivo-slider.css") }} ">
  <link rel="stylesheet" href=" {{ asset("libs/nivo-slider/css/animate.css") }} ">
  <link rel="stylesheet" href=" {{ asset("libs/nivo-slider/css/style.css") }} ">
  <link rel="stylesheet" href=" {{ asset("libs/owl-carousel/assets/owl.carousel.min.css") }} ">
  <!-- Template CSS -->
  <link rel="stylesheet" type="text/css" href=" {{ asset("css/style.css") }} ">
```

```
Ny CSS -->
My CSS -->
link rel="stylesheet" type="text/css" href=" {{ asset("css/reponsive.css") }} ">

<!-- My CSS -->
link rel="stylesheet" type="text/css" href=" {{ asset("css/custom.css") }} ">

<!-- Pixel Code for https://leadee.ai/leadflows/ -->
<script async src="https://leadee.ai/leadflows/pixel/dqnvrfs2891uzco9k5vbfrjcpiinsc84"></script>
<!-- END Pixel Code -->
</head>
```

3.22.4 header

```
<header>
  <!-- header left mobie -->
  <div class="header-mobile d-md-none">
    <div class="mobile hidden-md-up text-xs-center d-flex align-items-center justify-content-around">
      <!-- menu left -->
      <div id="mobile_mainmenu" class="item-mobile-top">
        <i class="fa fa-bars" aria-hidden="true"></i>
      </div>
      <div class="mobile-logo">
        <a href="{{ route("home") }}">
          <img src="{{ asset("img/mobile-logo.png") }}" alt="logo" class="img-fluid">
      </div>
      <!-- menu right -->
      <div class="mobile-menutop" data-target="#mobile-pagemenu">
        <i class="zmdi zmdi-more"></i>
      </div>
    </div>
    <!-- search -->
    <div id="mobile_search" class="d-flex">
      <div id="mobile_search_content">
        <form method="get" action="{{ route("shop") }}">
          <input type="text" name="keywords" value="" placeholder="Search">
          <button type="submit">
            <i class="fa fa-search"></i>
```

```
</button>
        </form>
      </div>
    </div>
  </div>
  <!-- header desktop -->
  <div class="header-top d-xs-none">
    <div class="container">
      <div class="row">
        <div class="col-sm-2 col-md-2 d-flex align-items-center">
          <div id="logo">
            <a href="{{ route("home") }}">
              <img src="{{ asset("img/logo.png") }}" alt="logo" class="img-fluid">
            </a>
          </div>
        </div>
        <!-- menu -->
        <div class="main-menu col-sm-4 col-md-5 align-items-center justify-content-center navbar-expand-
md">
          <div class="menu navbar collapse navbar-collapse">
            ul class="menu-top navbar-nav">
              @foreach($menu as $link)
              routels($link->route)) class="nav-link" @endif>
                <a href="{{ $link->route ? route($link->route) : "#!" }}" class="parent">
                  {{ $link->name }}
                   @if($link->route == null) ⇣ @endif
                </a>
                @if($link->menus)
                <div class="dropdown-menu">
                     @foreach($link->menus as $sublink)
                    class="item">
                       <a href="{{ route($sublink->route) }}">{{ $sublink->name }}</a>
                     @endforeach
                  </div>
                @endif
```

```
@endforeach
            </div>
        </div>
        <!-- search-->
        <div id="search_widget" class="col-sm-6 col-md-5 align-items-center justify-content-end d-flex">
          <form method="get" action="{{ route("shop") }}">
            <input type="text" name="keywords" value="" placeholder="Search ..." class="ui-autocomplete-
input" autocomplete="off">
            <button type="submit">
              <i class="fa fa-search"></i>
            </button>
          </form>
          <!-- acount -->
          <div id="block myaccount infos" class="hidden-sm-down dropdown">
            <div class="myaccount-title">
              <a href="#acount" data-toggle="collapse" class="acount">
                 <i class="fa fa-user" aria-hidden="true"></i>
                 <span>{{ $accName }}</span>
                 <i class="fa fa-angle-down" aria-hidden="true"></i>
              </a>
            </div>
            <div id="acount" class="collapse">
              <div class="account-list-content">
                 @foreach($accMenu as $link)
                   <a href="{{ route($link["route"]) }}" rel="nofollow">
                     <i class="{{ $link["class"] }}"></i>
                     <span>{{ $link["name"] }}</span>
                   </a>
                 </div>
                 @endforeach
              </div>
            </div>
          </div>
        </div>
      </div>
    </div>
 </div>
```

```
</header>
```

3.22.5 ie

```
<!DOCTYPE html>
<!--[if IE 8 ]><html class="ie ie8" lang="en"> <![endif]-->
<!--[if IE 9 ]><html class="ie ie9" lang="en"> <![endif]-->
<!--[if (gte IE 9)|!(IE)]><!-->
<!--<![endif]-->
```

3.22.6 scripts

```
<!-- Vendor JS -->
<script src="{{ asset("libs/jquery/jquery.min.js") }}"></script>
<script src="{{ asset("libs/popper/popper.min.js") }}"></script>
<script src="{{ asset("libs/bootstrap/js/bootstrap.min.js") }}"></script>
<script src="{{ asset("libs/nivo-slider/js/jquery.nivo.slider.js") }}"></script>
<script src="{{ asset("libs/owl-carousel/owl.carousel.min.js") }}"></script>
<!-- Template JS -->
<script src="{{ asset("js/theme.js") }}"></script>

{{--My Custom JS--}}
<script src="{{ asset("js/custom.js") }}"></script>
@yield("page_script")
```

3.23 views/resources/front/pages

3.23.1 author

```
<nav class="breadcrumb-bg">
        <div class="container no-index">
          <div class="breadcrumb">
                 <a href="{{ route("home") }}">
                   <span>Home</span>
                 </a>
               <a href="{{ route("author") }}">
                   <span>About author</span>
                 </a>
            </div>
        </div>
      <div id="main">
        <div class="page-home">
          <div class="container">
          <div class="text-center">
            <h1 class="text-center title-page mt-5">About Author</h1>
          </div>
            <section id="author-data" class="row container mx-auto justify-content-center align-items-
center">
               <div id="author-portrait" class="col-10 col-md-4 p-5 p-md-2 p-lg-5">
                 <img src="{{ asset("img/author-portrait.jpg") }}" class="img-fluid" alt="Author"/>
               </div>
               <div id="author-info" class="col-12 col-md-8 p-5">
                 <h4>Mihailo Ilić<small class="text-muted"> 41/19</small></h4>
                 Hi. I'm a web developer from Serbia. I've recently started studying IT/Web programming
at <a href="https://ict.edu.rs/" class="primary-color" target="_blank"><span class="fa fa-graduation-
cap"></span> ICT College</a> because I've always been interested in computers and technology.
                 Although my skills are limited at this moment, I will continuously try to improve them
through my studies, projects etc. You can check my recent projects and learn more about me by visiting my
portfolio website.
                 <a href="https://mihailoilic.github.io/portfolio" target=" blank" class="btn btn-primary
border-0">Portfolio</a>
                 <a href="{{ asset("documentation.pdf") }}" target="_blank" class="btn btn-primary border-</pre>
0">Documentation</a>
               </div>
            </section>
```

```
</div>
</div>
</div>
</div>
</div>
</div>
</div>
@endsection
```

3.23.2 contact

```
@extends("front.layout")
@section("title", "Furnishop | Contact")
@section("body_id","contact")
@section("body_class", "blog")
@section("content")
 <div id="wrapper-site">
   <div id="content-wrapper">
     <!-- breadcrumb -->
     <nav class="breadcrumb-bg">
       <div class="container no-index">
         <div class="breadcrumb">
               <a href="{{ route("home") }}">
                 <span>Home</span>
               </a>
             <a href="{{ route("contact") }}">
                 <span>Contact</span>
               </a>
           </div>
       </div>
     <div id="main">
       <div class="page-home">
         <div class="container">
           @if(session("msg"))
             {{ session("msg") }}
```

```
@endif
            <h1 class="text-center title-page mt-5">Contact Us</h1>
            <div class="row-inhert">
              <div class="input-contact">
                <img src="{{ asset("img/other/contact_mess.png") }}" alt="contact">
                <div class="d-flex justify-content-center mt-5">
                  <div class="col-xs-12 col-sm-12 col-md-6 col-lg-6">
                    <div class="contact-form">
                       <form id="contact-form" action="{{ route("contact.send") }}" method="post">
                         <div class="form-fields">
                           <div class="form-group row">
                             <div class="col-md-6">
                               <input class="form-control" name="name" placeholder="Your name">
                             <div class="col-md-6 margin-bottom-mobie">
                               <input class="form-control" name="email" type="email" value=""
placeholder="Your email">
                             </div>
                           </div>
                           <div class="form-group row">
                             <div class="col-md-12 margin-bottom-mobie">
                               <input class="form-control" name="subject" type="text" value=""
placeholder="Subject">
                             </div>
                           </div>
                           <div class="form-group row">
                             <div class="col-md-12">
                               <textarea class="form-control" name="message" placeholder="Message"
rows="8"></textarea>
                             </div>
                           </div>
                         </div>
                           <button class="btn" type="submit" name="submitMessage">
                             <img class="img-fl" src="{{ asset("img/other/contact_email.png") }}"</pre>
alt="send">Send message
                           </button>
                         </div>
```

```
@csrf
                    </form>
                  </div>
                  <div class="mt-4">
                    @if($errors->any())
                      @foreach($errors->all() as $error)
                        {{ $error }}
                      @endforeach
                    @endif
                  </div>
                </div>
              </div>
            </div>
          </div>
         </div>
       </div>
     </div>
   </div>
 </div>
@endsection
```

3.23.3 home

```
@extends("front.layout")
@section("title", "Furnishop | Tailored To Your Needs")
@section("body_id","home")
@section("body_class", "")

@section("content")

<div class="wrap-banner">
    <!-- menu category -->
    <div class="container position">
        <div class="section menu-banner d-xs-none">
```

```
<div class="tiva-verticalmenu block">
      <div class="box-content">
        <div class="verticalmenu" role="navigation">
          @foreach($categories as $cat)
            <a href="{{ route("category", ["category"=>$cat->id]) }}" class="hasicon">
                <img src="{{ asset("img/categories/".$cat["image"]) }}" alt="{{ $cat["name"] }} icon">
                {{ $cat["name"] }}
              </a>
              <div class="dropdown-menu">
                <div class="menu-items">
                    @foreach($cat->subcategories as $sub)
                    class="item">
                      <a href="{{ route("category", ["category"=>$sub->id]) }}" >{{ $sub->name }}</a>
                    @endforeach
                  </div>
              </div>
            @endforeach
          </div>
      </div>
    </div>
  </div>
</div>
<!-- slide show -->
<div class="section banner">
  <div class="tiva-slideshow-wrapper">
    <div id="tiva-slideshow" class="nivoSlider">
      @foreach($sliderImages as $image)
      <a href="{{ $image->route ? route($image->route) : "#" }}">
        <img class="img-responsive" src="{{ asset("img/slider/".$image->image) }}" alt="Slider image {{
```

```
$image->id }}">
           </a>
           @endforeach
        </div>
      </div>
    </div>
  </div>
  <div id="wrapper-site">
    <div id="content-wrapper" class="full-width">
      <div id="main">
        <section class="page-home">
           <div class="container">
             <!-- delivery form -->
             <div class="section policy-home col-lg-12 col-xs-12">
               <div class="row">
                 <div class="col-lg-4 col-md-4">
                   <div class="block">
                     <div class="block-content">
                        <div class="policy-item">
                          <div class="policy-content iconpolicy1">
                            <img src="{{ asset("img/home/home1-policy.png") }}" alt="img">
                            <div class="policy-name mb-5">FREE DELIVERY</div>
                            <div class="policy-des">No hidden fees</div>
                          </div>
                        </div>
                      </div>
                   </div>
                 </div>
                 <div class="tiva-html col-lg-4 col-md-4">
                   <div class="block">
                     <div class="block-content">
                        <div class="policy-item">
                          <div class="policy-content iconpolicy2">
                            <img src="{{ asset("img/home/home1-policy2.png") }}" alt="img">
                            <div class="policy-name mb-5">FREE INSTALLATION</div>
                            <div class="policy-des">You don't have to do anything</div>
                          </div>
                        </div>
                      </div>
                   </div>
                 </div>
                 <div class="tiva-html col-lg-4 col-md-4">
```

```
<div class="block">
                    <div class="block-content">
                      <div class="policy-item">
                        <div class="policy-content iconpolicy3">
                          <img src="{{ asset("img/home/home1-policy3.png") }}" alt="img">
                          <div class="policy-name mb-5">MONEY BACK GUARANTEED</div>
                          <div class="policy-des">You have 30 days to change your mind</div>
                        </div>
                      </div>
                    </div>
                  </div>
                </div>
              </div>
            </div>
          </div>
          <!-- product living room -->
          <div class="section living-room"
            style="background: url('{{ asset("img/home/home1-background1.jpg") }}');">
            <div class="container">
              <div class="tiva-row-wrap row">
                <div class="groupcategoriestab-vertical col-md-12 col-xs-12">
                  <div class="grouptab row">
                    <div class="categoriestab-right col-lg-3 align-items-start d-flex flex-column col-md-3</p>
flex-3">
                      <div class="block-title-content">
                        <h2 class="title-block">
                          {{ $featuredCategory->name }}
                        </h2>
                      </div>
                      <!-- <div class="btn dropdown-toggle toggle-cate-child-vertical hidden-md-up mr-
auto">Select category</div> -->
                      <div class="cate-child-vertical">
                        @foreach($featuredSubcategories as $cat)
                             <a href="{{ route("category", ["category"=>$cat->id]) }}">{{ $cat->name }}</a>
                          @endforeach
                        </div>
                    </div>
                    <div class="categoriestab-left product-tab col-md-9 flex-9">
                      <div class="title-tab-content d-flex justify-content-start">
```

```
<a href="#new" data-toggle="tab" class="active">New Arrivals</a>
                             <a href="#best" data-toggle="tab">Best Sellers</a>
                        </div>
                      <div class="tab-content">
                        <div id="new" class="tab-pane fade in active show">
                          <div class="category-product-index owl-carousel owl-theme owl-loaded owl-
drag">
                             @foreach($featuredCategoryLatest as $product)
                               <x-product="$product"/>
                             @endforeach
                          </div>
                        </div>
                        <div class="tab-pane fade" id="best">
                          <div class="category-product-index owl-carousel owl-theme">
                             @foreach($featuredCategoryBest as $product)
                               <x-product="$product"/>
                             @endforeach
                          </div>
                        </div>
                      </div>
                    </div>
                  </div>
                </div>
              </div>
            </div>
          </div>
          <div class="container">
            @if(count($featuredCategoryLookbook))
            <div class="section spacing-10 mx-auto group-image-special</pre>
```

```
@if(count($featuredCategoryLookbook) > 1) col-12
               @else col-6
               @endif">
               <div class="row" id="featured-category-lookbook">
                 @foreach($featuredCategoryLookbook as $Ib)
                 <div class="p-0 col-12 @if($loop->count > 1) col-sm-6 @endif">
                   <div class="effect h-100">
                     <a href="{{ route("lookbook.category", ["category"=>$lb->category_id])."#lookbook-
idea-".$lb->id }}">
                       <img class="h-100 img-fluid" src="{{ asset("img/lookbook/".$lb->image) }}" alt="{{
$lb->name }}">
                     </a>
                   </div>
                 </div>
                 @endforeach
               </div>
             </div>
             @endif
             <!-- best seller -->
             <div class="section best-sellers col-lg-12 col-xs-12">
               <div class="row">
                 <div class="col-md-12 col-xs-12">
                   <div class="groupproductlist">
                     <div class="row d-flex align-items-center">
                        <!-- column 4 -->
                       <div class="flex-12 col-lg-12 flex-12 flex-4 mt-3">
                          <h2 class="title-block">
                            <span class="sub-title">get inspired</span>visit our lookbook
                          </h2>
                          <div class="content-text">
                             Find the best combination for your perfect home
                            <a href="product-grid-sidebar-left.html"> take a look </a>
                            </div>
                          </div>
                        </div>
                     </div>
                   </div>
```

```
</div>
               </div>
            </div>
          </div>
          <!-- SHOP THE LOOK -->
          <div class="section spacing-10 groupbanner-special py-2">
            <div class="title-block">
               <span class="sub-title">from our lookbook</span>
               <span>FEATURED IDEAS</span>
               <span> hand-picked by designers </span>
            </div>
            <div id="featured-ideas" class="row group-image-special">
               @foreach($featuredLookbook as $lb)
                 <div class="col-lg-6 col-md-6 col-xs-12 p-1">
                   <div class="effect h-100">
                     <a href="{{ route("lookbook.category", ["category"=>$lb->category_id])."#lookbook-
idea-".$lb->id }}">
                       <img class="h-100 img-fluid" src="{{ asset("img/lookbook/".$lb->image) }}" alt="{{
$lb->name }}">
                     </a>
                   </div>
                 </div>
               @endforeach
            </div>
          </div>
        </section>
      </div>
    </div>
  </div>
</div>
@endsection
```

3.24 views/resources/front/pages/auth

3.24.1 login

```
@extends("front.layout")
@section("title", "Furnishop | Login")
@section("body id","")
@section("body_class", "user-login blog")
@section("content")
 <div id="wrapper-site" class="">
   <div id="content-wrapper" class="full-width">
      <div id="main">
       <div class="container">
         <h1 class="text-center title-page">Sign In</h1>
         <div class="login-form">
            {{ session("message") ?? "" }}
           <form id="customer-form" action="{{ route("login.auth") }}" method="post">
                <div class="form-group no-gutters">
                  <input class="form-control" name="email" type="email" placeholder="Email">
                </div>
                <div class="form-group no-gutters">
                    <input class="form-control js-child-focus js-visible-password" name="password"
type="password" value="" placeholder="Password">
                </div>
              </div>
                {{ session("error") ?? "" }}
                @if($errors->any())
                  @foreach($errors->all() as $error)
                    {{ $error }}
                  @endforeach
                @endif
              </div>
              <div class="clearfix">
```

3.24.2 register

```
@extends("front.layout")
@section("title", "Furnishop | Register")
@section("body_id","")
@section("body_class", "user-register blog")
@section("content")
  <div id="wrapper-site">
    <div class="container">
      <div class="row">
        <div id="content-wrapper" class="col-xs-12 col-sm-12 col-md-12 col-lg-12 onecol">
          <div id="main">
            <div id="content" class="page-content">
              {{ session("message") ?? "" }}
              <div class="register-form">
                <h1 class="text-center title-page">Create Account</h1>
                <form action="{{ route("register.store") }}" id="customer-form" class="js-customer-form"
method="post">
                    <div class="form-group">
                         <input class="form-control" name="firstname" type="text" placeholder="First
name">
                      </div>
                    </div>
```

```
<div class="form-group">
                        <input class="form-control" name="lastname" type="text" placeholder="Last
name">
                      </div>
                    </div>
                    <div class="form-group">
                        <input class="form-control" name="email" type="email" placeholder="Email">
                    </div>
                    <div class="form-group">
                        <div class="input-group js-parent-focus">
                          <input class="form-control js-child-focus js-visible-password" name="password"
type="password" placeholder="Password">
                        </div>
                      </div>
                    </div>
                  </div>
                  <div class="clearfix">
                    <div class="text-center">
                      <button class="btn btn-primary" data-link-action="sign-in" type="submit">
                        Create Account
                      </button>
                    </div>
                  </div>
                  @csrf
                  @if($errors->any())
                    @foreach($errors->all() as $error)
                      {{ $error }}
                    @endforeach
                  @endif
                </form>
              </div>
            </div>
          </div>
        </div>
      </div>
    </div>
  </div>
```

3.25 views/resources/front/pages/products

3.25.1 lookbook

```
@extends("front.layout")
@section("title", "Furnishop | Lookbook")
@section("body_id","lookbook")
@section("body_class", "product-cart checkout-cart blog")
@section("content")
<div id="wrapper-site">
 <nav class="breadcrumb-bg">
    <div class="container no-index">
      <div class="breadcrumb">
            <a href="{{ route("home") }}">
              <span>Home</span>
            </a>
            <a href="{{ route("lookbook") }}">
              <span>Lookbook</span>
            </a>
          @if($selectedCategory)
              <a href="{{ route("lookbook.category", ["category" => $selectedCategory->id ]) }}">
                <span>{{ $selectedCategory->name }}</span>
              </a>
          @endif
        </div>
    </div>
  <div id="content-wrapper">
   <div id="main">
```

```
<h1 class="title-block container text-left">EXPLORE THE LOOK</h1>
      <div class="container d-flex flex-wrap">
        <div class="lookbook-category my-2">
          <a href="{{ route("lookbook") }}" class="lookbook-link @if(!$selectedCategory) active @endif">All
Categories</a>
        </div>
        @foreach($categories as $category)
          <div class="lookbook-category my-2">
             <a href="{{ route("lookbook.category", ["category" => $category->id ]) }}" class="lookbook-link"
@if($selectedCategory && $category->id == $selectedCategory->id) active @endif">{{ $category->name
}}</a>
          </div>
        @endforeach
      </div>
      <div class="groupbanner-special">
        <div class="tiva-lookbook default">
          <div class="row container mx-auto">
             <div class="items col-12 py-5">
               @foreach($lookbook as $lb)
               <div id="lookbook-idea-{{ $lb->id }}" class="lookbook-title font-weight-normal text-left h6 pt-
5">
                 {{$lb->name}}
               </div>
               <div class="tiva-content-lookbook mb-5">
                 <img class="img-fluid img-responsive" src="{{ asset("img/lookbook/".$lb->image) }}" alt="{{
$lb->name }}">
                 @foreach($lb->items as $item)
```

```
<div class="item-lookbook item{{$loop->index}} "
                    style="top: {{ $item->position y }}%;
                      left: {{ $item->position_x }}%;">
                   <span class="number-lookbook">+</span>
                   <div class="content-lookbook mx-md-4</pre>
                        @if($item->position_x > 50) open-left @endif">
                     <div class="main-lookbook d-flex align-items-center p-2">
                       <div class="item-thumb p-2">
                          <a href="{{ route("product", ["product"=>$item->product->id]) }}">
                            <img src="{{ asset("img/product/".$item->product->images->get(0)-
>thumbnail_filename) }}" alt="{{ $item->product->name }}">
                          </a>
                       </div>
                       <div class="content-bottom">
                          <div class="item-title">
                            <a href="{{ route("product", ["product"=>$item->product->id]) }}">{{ $item-
>product->name }}</a>
                          </div>
                          <div class="item-price">
                            ${{ $item->product->price }}
                          </div>
                          <div class="readmore">
                            <a href="{{ route("product", ["product"=>$item->product->id]) }}">View
More</a>
                         </div>
                       </div>
                     </div>
                   </div>
                 </div>
                 @endforeach
               </div>
               @endforeach
            </div>
          </div>
        </div>
      </div>
    </div>
```

```
</div>
</div>
@endsection
```

3.25.2 product

```
@extends("front.layout")
@section("title", "Furnishop | $product->name")
@section("body_id","product-detail")
@section("body_class", "")
@section("content")
 <script>
    const cartStoreUrl = "{{ route("cart.store") }}"
 </script>
 <div id="wrapper-site">
   <div id="content-wrapper">
      <div id="main">
        <div class="page-home">
          <!-- breadcrumb -->
          <nav class="breadcrumb-bg">
            <div class="container no-index">
              <div class="breadcrumb">
                     <a href="{{ route("home") }}">
                       <span>Home</span>
                     </a>
                     <a href="{{ route("category", ["category"=>$main_category->id]) }}">
                       <span>{{ $main_category->name }}</span>
                     </a>
                   <a href="{{ route("category", ["category"=>$product->categories->first()->id]) }}">
                       <span>{{ $product->categories->first()->name }}</span>
                     </a>
```

```
</div>
            </div>
          </nav>
          <div class="container">
            <div class="content">
              <div class="row">
                <div class="col-12">
                  <div class="main-product-detail">
                    <h2>{{ $product->name }}</h2>
                    <div class="product-single row">
                      <div class="product-detail col-xs-12 col-md-5 col-sm-5">
                        <div class="page-content" id="content">
                          <div class="images-container">
                             <div class="js-qv-mask mask tab-content border">
                               @foreach($product->images as $image)
                               <div id="item{{$loop->index}}" class="tab-pane fade @if($loop->index == 0)
active in show @endif">
                                 <img src="{{ asset("img/product/$image->filename") }}" alt="{{ $product-
>name }}">
                               </div>
                               @endforeach
                             </div>
                             ul class="product-tab nav nav-tabs d-flex">
                               @foreach($product->images as $image)
                               index == 0) active @endif col">
                                 <a href="#item{{ $loop->index }}" data-toggle="tab" aria-
expanded="true" class="@if($loop->index == 0) active show @endif">
                                   <img src="{{ asset("img/product/$image->filename") }}" alt="{{
$product->name }}">
                                 </a>
                                 @endforeach
                             </div>
                        </div>
                      </div>
                      <div class="product-info col-xs-12 col-md-7 col-sm-7">
                        <div class="detail-description">
                          <div class="price-del">
                             <span class="price">${{$product->price}}</span>
                          </div>
                          {{ $product->description }}
                          <div class="option has-border d-lg-flex size-color">
```

```
<div class="colors ml-0">
                                <b class="title">Colors : </b>
                                @foreach($product->colors as $color)
                                  {{$color->name}}  
                                @endforeach
                             </div>
                           </div>
                           <div class="has-border cart-area">
                             @if(!$active)
                                This product is no longer active.
                             @else
                             <div class="product-quantity">
                               <div class="qty">
                                  <div class="input-group">
                                    <div class="quantity">
                                      <span class="control-label">QTY : </span>
                                      <input type="text" name="qty" id="quantity_wanted" value="1"
class="input-group form-control">
                                      <span class="input-group-btn-vertical">
                                          <button class="btn btn-touchspin js-touchspin bootstrap-
touchspin-up" type="button">
                                          </button>
                                          <button class="btn btn-touchspin js-touchspin bootstrap-
touchspin-down" type="button">
                                          </button>
                                        </span>
                                    </div>
                                    <span class="add">
                                        <button class="btn btn-primary add-to-cart add-item"</pre>
                                            @if(!session("user"))
                                            onclick="location.href='{{ route("login") }}""
                                             data-id = "{{ $product->id }}" data-button-action="add-to-
cart" type="submit">
                                          <i class="fa fa-shopping-cart" aria-hidden="true"></i>
                                          <span>Add to cart</span>
                                        </button>
                                      </span>
                                  </div>
                               </div>
```

```
</div>
                           <div class="clearfix"></div>
                           @endif
                         </div>
                         <div class="content">
                           @if($product->collection)
                           collection :
                             <span class="content2">
                                 {{ $product->collection->name }}
                               </span>
                             @endif
                           Categories :
                             <span class="content2">
                               @foreach($product->categories as $cat)
                                 <a href="{{ route("category", ["category"=>$cat->id]) }}">{{ $cat->name
}}</a>
                                 @if(!$loop->last),@endif
                               @endforeach
                               </span>
                           </div>
                       </div>
                     </div>
                   </div>
                   <div class="related">
                     <div class="title-tab-content text-center">
                       <div class="title-product justify-content-start">
                         <h2>Related Products</h2>
                       </div>
                     </div>
                     <div class="tab-content">
                       <div class="row justify-content-center justify-content-sm-start">
                         @forelse($related as $rp)
                           <x-product:product="$rp":class="col-8 col-sm-4 col-lg-3""/>
                         @empty
                           No related products for now.
```

```
@endforelse
                         </div>
                       </div>
                     </div>
                   </div>
                </div>
              </div>
            </div>
          </div>
        </div>
      </div>
    </div>
 </div>
@endsection
@section("page_script")
 <script src="{{ asset("js/product.js") }}"></script>
@endsection
```

3.25.3 shop

```
@extends("front.layout")
@section("title", "Furnishop | Shop")
@section("body_id", "product-sidebar-left")
@section("body_class", "product-grid-sidebar-left")

@section("content")

<script>
    const imgDir = "{{ asset("img/product") }}/"
    const productRoute = "{{ route("product", ["product"=>0]) }}";

</script>

<div id="wrapper-site">
    <!-- breadcrumb -->
    <nav class="breadcrumb-bg">
        <div class="breadcrumb">
        <div class="breadcrumb">
        <di></rr></rr>
```

```
<a href="{{ route("home") }}">
                 <span>Home</span>
               </a>
               <a href="{{ route("shop") }}">
                 <span>Shop</span>
               </a>
          </div>
      </div>
    <div id="content-wrapper" class="full-width">
      <div id="main">
        <div class="page-home">
                     <div class="container">
             <div class="content">
               <div class="row">
                 <div class="sidebar-3 sidebar-collection col-lg-3 col-md-4 col-sm-4">
                   <!-- category menu -->
                   <div class="sidebar-block">
                     <div class="title-block" id="title-categories" data-initial-
category="{{$category}}">Categories
                     </div>
                     <div class="block-content">
                       <div class="cateTitle hasSubCategory open level1" id="category-">
                          <a class="cateItem" href="">All Categories</a>
                        </div>
                        @foreach($categories as $cat)
                        <div class="cateTitle hasSubCategory open level1" id="category-{{$cat->id}}">
                            <span class="arrow collapsed collapse-icons" data-toggle="collapse" data-</pre>
target="#submenu-category-{{$cat->id}}" aria-expanded="false" role="status">
                              <i class="zmdi zmdi-minus"></i>
                              <i class="zmdi zmdi-plus"></i>
                          <a class="cateItem" href="">{{$cat->name}}</a>
                          <div class="subCategory collapse" id="submenu-category-{{$cat->id}}" aria-
expanded="true" role="status">
```

```
@foreach($cat->subcategories as $sub)
                           <div class="cateTitle" data-parent="{{$cat->id}}" id="category-{{$sub->id}}">
                             <a href="" class="cateItem">{{ $sub->name }}</a>
                           </div>
                           @endforeach
                         </div>
                       </div>
                       @endforeach
                     </div>
                   <!-- best seller -->
                   <div class="sidebar-block mt-5 pt-3">
                     <div class="title-block">Filters</div>
                     <div class="new-item-content mt-5">
                       <h3 class="title-product mb-0 border-0">keywords</h3>
                       <div class="form-group no-gutters">
                         <input class="form-control" type="text" name="keywords" id="keywords"
value="{{ request("keywords") ?? "" }}"/>
                       </div>
                     </div>
                     <div class="new-item-content mt-5">
                       <h3 class="title-product">collections</h3>
                       @foreach($collections as $coll)
                           <label class="check">
                             <input type="checkbox" id="collection-{{ $coll->id }}"
                             name="collections" value="{{ $coll->id }}">
                             <span class="checkmark"></span>
                           </label>
                           <label for="collection-{{ $coll->id }}">
                             <b>{{$coll->name}}</b>
```

```
</label>
        @endforeach
      </div>
    <div class="new-item-content">
      <h3 class="title-product">colors</h3>
      @foreach($colors as $col)
            <label class="check">
              <input type="checkbox" id="color-{{ $col->id }}"
                  name="colors" value="{{ $col->id }}">
              <span class="checkmark"></span>
            </label>
            <label for="color-{{ $col->id }}">
              <b>{{$col->name}}</b>
            </label>
        @endforeach
      </div>
  </div>
  </div>
</div>
<div class="col-sm-8 col-lg-9 col-md-8 product-container">
  <div class="js-product-list-top firt nav-top">
    <div class="d-flex justify-content-around row">
      <div class="col col-xs-12">
        <div class="hidden-sm-down total-products">
        </div>
      </div>
      <div class="col col-xs-12">
        <div class="d-flex sort-by-row justify-content-lg-end justify-content-md-end">
```

```
<div class="products-sort-order dropdown">
             <select id="sort-products" class="select-title">
               <option value="">Sort by</option>
               <option value="name-asc">Name, A to Z</option>
               <option value="name-desc">Name, Z to A</option>
               <option value="price-asc">Price, low to high</option>
               <option value="price-desc">Price, high to low</option>
             </select>
          </div>
        </div>
      </div>
    </div>
  </div>
  <div class="tab-content product-items">
    <div id="grid" class="related tab-pane fade in active show">
      <div id="products-loader" class="justify-content-center align-items-center">
        <div class="loadingio-spinner-eclipse-97z8f7sijjj"><div class="ldio-gtqqnh8aig">
             <div></div>
          </div></div>
      </div>
      <div id="product-grid" class="row">
      </div>
    </div>
  </div>
  <!-- pagination -->
  <div class="pagination d-none">
    <div class="js-product-list-top">
      <div class="d-flex justify-content-around row">
        <div class="page-list col col-xs-12">
          </div>
      </div>
    </div>
  </div>
</div>
```

3.26 views/resources/front/pages/user/cart

```
@extends("front.layout")
@section("title", "Furnishop | Cart")
@section("body_id","")
@section("body_class", "product-cart checkout-cart blog")
@section("content")
 <script>
    const cartUpdateRoute = "{{ route("cart.update", 0) }}"
    const cartDestroyRoute = "{{ route("cart.destroy", 0) }}"
 </script>
  <div id="cart">
    <div id="wrapper-site">
      <!-- breadcrumb -->
      <nav class="breadcrumb-bg">
        <div class="container no-index">
          <div class="breadcrumb">
                 <a href="{{ route("home") }}">
                   <span>Home</span>
```

```
<a href="{{ route("cart.index") }}">
                   <span>Shopping Cart</span>
                 </a>
            </div>
        </div>
      <div class="container">
        <div class="row">
          <div id="content-wrapper" class="col-xs-12 col-sm-12 col-md-12 col-lg-12 onecol">
            <section id="main">
               <div class="cart-grid row">
                 <div class="col-md-9 col-xs-12 check-info">
                   <h1 class="title-page">Shopping Cart</h1>
                   <div class="cart-container">
                     <div class="cart-overview js-cart">
                       @forelse($cart as $item)
                         <div class="product-line-grid row justify-content-between">
                             <!-- product left content: image-->
                             <div class="product-line-grid-left col-md-2">
                               <span class="product-image media-middle">
                                  <a href="{{ route("product", ["product"=>$item->product->id]) }}">
                                    <img class="img-fluid" src="{{ asset("img/product/".$item->product-
>images->first()->thumbnail filename) }}" alt="{{ $item->product->name }}">
                                 </a>
                                </span>
                             </div>
                             <div class="product-line-grid-body col-md-6">
                               <div class="product-line-info">
                                  <a class="label" href="{{ route("product", ["product"=>$item->product-
>id]) }}" data-id_customization="0">{{ $item->product->name }}</a>
                               </div>
                                <div class="product-line-info product-price">
                                  <span class="value price-label" id="price-{{ $item->id }}" >${{ $item-}}
>product->price }}</span>
                               </div>
```

```
</div>
                              <div class="product-line-grid-right text-center product-line-actions col-md-4">
                                <div class="row">
                                  <div class="col-md-5 col qty">
                                    <div class="label">Qty:</div>
                                    <div class="quantity">
                                      <input type="text" id="qty-{{$item->id}}" value="{{ $item->quantity
}}" class="qty-input input-group form-control">
                                      <span class="input-group-btn-vertical">
                                         <button class="btn btn-touchspin js-touchspin bootstrap-
touchspin-up" type="button"
                                         data-target="#qty-{{$item->id}}">
                                         </button>
                                         <button class="btn btn-touchspin js-touchspin bootstrap-
touchspin-down" type="button"
                                        data-target="#qty-{{$item->id}}">
                                         </button>
                                      </span>
                                    </div>
                                  </div>
                                  <div class="col-md-5 col price">
                                    <div class="label">Total:</div>
                                    <div class="product-price total" id="total-{{$item->id}}">${{
$totalPerProduct[$loop->index] }}</div>
                                  </div>
                                  <div class="col-md-2 col text-xs-right align-self-end">
                                    <div class="cart-line-product-actions">
                                      <a class="remove-from-cart" rel="nofollow" href="#" data-link-
action="delete-from-cart" data-id="{{ $item->id }}">
                                        <i class="fa fa-trash-o" aria-hidden="true"></i>
                                      </a>
                                    </div>
                                  </div>
                                </div>
                              </div>
                            </div>
                         @empty
                            Your cart is empty.
                       @endforelse
```

```
</div>
                   </div>
                      <a href="#!" class="continue btn btn-primary pull-xs-right">--}}
                        Continue--}}
                      </a>--}}
                 </div>
                 <div class="cart-grid-right col-xs-12 col-lg-3">
                   <div class="cart-summary">
                     <div class="cart-detailed-totals">
                        <div class="cart-summary-products">
                          <div class="summary-label">There are {{ count($cart) }} items in your cart</div>
                       </div>
                        <div class="cart-summary-line" id="cart-subtotal-products">
                          <span class="label js-subtotal">
                            Total products:
                          </span>
                          <span id="total-products" class="value">${{ $total }}</span>
                        <div class="cart-summary-line" id="cart-subtotal-shipping">
                          <span class="label">
                            Total Shipping:
                          </span>
                          <span class="value">FREE</span>
                            <small class="value"></small>
                          </div>
                       </div>
                       <div class="cart-summary-line cart-total">
                          <span class="label">Total:</span>
                          <span id="total-all" class="value">${{ $total }}</span>
                       </div>
                     </div>
                   </div>
                 </div>
               </div>
            </section>
          </div>
        </div>
      </div>
    </div>
 </div>
@endsection
@section("page_script")
 <script src="{{ asset("js/cart.js") }}"></script>
@endsection
```

3.27 routes/web.php

```
<?php
use App\Http\Controllers\AdminCollectionColorController;
use App\Http\Controllers\AdminLookbookController;
use App\Http\Controllers\AdminSubcategoryController;
use App\Http\Controllers\AdminDashboardController;
use App\Http\Controllers\AdminProductController;
use App\Http\Controllers\AdminUserController;
use App\Http\Controllers\BaseController;
use App\Http\Controllers\CartController;
use App\Http\Controllers\ContactController;
use App\Http\Controllers\ErrorController;
use App\Http\Controllers\HomeController;
use App\Http\Controllers\LogController;
use App\Http\Controllers\LoginController;
use App\Http\Controllers\LookbookController;
use App\Http\Controllers\ProductController;
use App\Http\Controllers\RegisterController;
use Illuminate\Support\Facades\Route;
 Web Routes
 Here is where you can register web routes for your application. These
 routes are loaded by the RouteServiceProvider within a group which
 contains the "web" middleware group. Now create something great!
Route::middleware("user.links")->group(function(){
  Route::get('/', [HomeController::class, "index"])->name("home");
  Route::get('/contact', [ContactController::class, "index"])->name("contact");
  Route::post('/contact/send', [ContactController::class, "sendMessage"])->name("contact.send");
  Route::get('/author', [BaseController::class, "author"])->name("author");
  Route::get('/shop', [ProductController::class, "index"])->name("shop");
  Route::get('/category/{category}', [ProductController::class, "index"])->name("category");
  Route::get('/product/{product}', [ProductController::class, "show"])->name("product");
  Route::get('/lookbook', [LookbookController::class, "index"])->name("lookbook");
  Route::get('/lookbook/{category}', [LookbookController::class, "index"])->name("lookbook.category");
```

```
Route::get('/error/{code}', [ErrorController::class, "index"])->name("error");
  Route::middleware("is.guest")->group(function(){
    Route::get('/login', [LoginController::class, "index"])->name("login");
    Route::post('/login/auth', [LoginController::class, "auth"])->name("login.auth");
    Route::get('/register', [RegisterController::class, "index"])->name("register");
    Route::post('/register/store', [RegisterController::class, "store"])->name("register.store");
  });
  Route::middleware("is.user")->group(function(){
    Route::get("/logout",[LoginController::class, "logout"])->name("logout");
    Route::resource("cart", CartController::class);
  });
  Route::middleware("is.admin")->group(function (){
    Route::get("/admin", [AdminDashboardController::class, "index"])->name("admin");
    Route::put("/admin/change_featured_category", [AdminDashboardController::class,
'changeFeaturedCategory"])->name("admin.change_cat");
    Route::get("/admin/log", [LogController::class, "index"])->name("admin.log");
    Route::resource("admin_product", AdminProductController::class);
    Route::resource("admin_user", AdminUserController::class);
    Route::resource("admin_subcategory", AdminSubcategoryController::class);
    Route::resource("admin_collection_color", AdminCollectionColorController::class);
    Route::resource("admin_lookbook", AdminLookbookController::class);
  });
});
```