

PDFSigningSigner{

phoneNo

string

example: +3721234567890

Mobile number for Mobile-ID (EE, LT). Starting with country code starting with '+'

idCode

string

example: 3621234567890

Personal code for Smart-ID (EE, LV, LT)

country

string

example: EE

Country code for signing with Mobile-ID (EE, LT), Smart-ID (EE, LV, LT). Country code in format LV, LT, EE

documentNumber

string

example: 123123123123

Smart-ID document number used for signing identified during authentication process

displayText

string

example: Please sign document

Smart-ID display text (can be longer text if user has new version of Smart-ID mobile App). If not specified used 'displayText'

role

string

example: CEO of Company

Signer role added to xades signatures (asice containers)

delay

integer(\$int32)

example: 3000

Smart-ID app popup delay in milliseconds between returning verification code

callbackUrl

string

example: 3000

Callback url to send process information. Replacements for {documentid}, {sessioncode}, {status} tags performed

hashToSign

string

Internal use only

signatureProfile	string <i>example: PAdES_BASELINE_LT</i> Signature profile to use. (https://ec.europa.eu/digital-building-blocks/DSS/webapp-demo/apidocs/eu/europa/esig/dss/enumerations/SignatureLevel.html)
certInHex	string Certificate in HEX format to use for ID-card signing
signatureLocation	string <i>example: Tallinn, Estonia</i> PDF signature location attribute value
signatureReason	string <i>example: Apporve</i> PDF signature reason attribute value
signatureContactInfo	string <i>example: signer@trustlynx.com</i> PDF signature contact info attribute value
pdfSignaturesIsVisible	boolean <i>example: true</i> Add PDF signature visual representation or not
forcePin	boolean <i>example: false</i> Force confirm eparaksts mobile signing by pin
font	string <i>example: classpath:OpenSansRegular.ttf</i> Signature text font. Reference as available resource to application
signerTextVerticalPosition	string <i>example: BOTTOM</i>

Signature text positioning, possible values: TOP, BOTTOM RIGHT, LEFT

signatureImageScaling

string

example: ZOOM_AND_CENTER

Signature image scaling, possible values: STRETCH, ZOOM_AND_CENTER, CENTER

signatureFieldHeight

integer(\$int32)

example: 100

Visual signature field height

signatureFieldWidth

integer(\$int32)

example: 200

Visual signature field width

pdfSignatureVisuals	PDFSignatureVisuals{	
	signatureImage	<p>string</p> <p><i>example: Digitally signed by: {g} {sn} \nAt date: {date}</i></p> <p>PDF visual text pattern. Possible replacements: {g} - given name, {cn} - common name, {sn} - surname, {date} - date in smple java date formatted, pdf.signature.defaults.dateFormat</p>
	signatureXAxis	<p>integer(\$int32)</p> <p><i>example: 100</i></p> <p>PDF visual signature horizontal position from left side of page. In multiple signature positioning starting point of calculations. Can use negative number for positioning from right side of page minus specified coordinate</p>
	signatureYAxis	<p>integer(\$int32)</p> <p><i>example: 100</i></p> <p>PDF visual signature vertical position from top of page. In multiple signature positioning starting point of calculations. Can use negative number for positioning from bottom of page minus specified coordinate</p>
	signatureZoom	<p>integer(\$int32)</p> <p><i>example: 50</i></p> <p>PDF Visual signature zoom level</p>
	signaturePage	<p>integer(\$int32)</p> <p><i>example: 1</i></p> <p>PDF Visual signature page number. if number is bigger than number of pages of document, last page selected</p>
	sigMod2XIndent	<p>integer(\$int32)</p> <p><i>example: 250</i></p> <p>Next PDF Visual signature position increment. How much next signature is positioned from previous signature</p>

signatureFieldHeight	integer(\$int32) <i>example: 100</i>	Visual signature field height
signatureFieldWidth	integer(\$int32) <i>example: 200</i>	Visual signature field width
textBackgroundColor	string <i>example: #FF0096</i>	Visual signature text background color.
imageBackgroundColor	string <i>example: #FF0096</i>	Visual signature image background color.
signatureTimeZone	string <i>example: Europe/Tallinn</i>	Time zone used in visual signature {date} replacement
numberOfSignaturesInRow	integer(\$int32)	

}

pdfAdditionalText

PDFTextVisuals{

text string

example: This document is digitally signed

Text added to document before first signing (Watermark)

page integer(\$int32)

example: 1

Added text page number

x integer(\$int32)

example: 100

Added text position horizontally from left of page

font string

example: classpath:OpenSansRegular.ttf

Added text font. Reference as available resource to application

fontSize integer(\$int32)

example: 12

Added text font size

colour PDFColour{

description: Added text color.

r integer(\$int32)

g integer(\$int32)

b integer(\$int32)

}

example: "colour": { "r": 0, "g": 0, "b": 0 }

transparency number(\$float)

example: 0.5

Added text transparency.

}

label string

signingInfo {...}

documentName string

phoneNumber string

pin string

}