

PESH HAI NAYI **MAHINDRA SP PLUS SERIES**

POWER KI GUARANTEE



Mahindra SP Plus Series:

275DI SP PLUS 27.6 kW (37 HP) | 275DI TU SP PLUS 29.1 kW (39 HP) |
415DI SP PLUS 31.3 kW (42 HP) | 475DI SP PLUS 32.8 kW (44 HP)

Mahindra
575DI
SP PLUS

35.0 kW (47 HP)

PRESENTING THE NEW POWERFUL SP PLUS SERIES

Introducing the new Mahindra SP PLUS Series. Its powerful Extra-long Stroke (ELS) DI Engine offers superior performance and compatibility with all agricultural applications. Get more back-up torque and maximum torque, thanks to its best-in-class power. For the first time in the industry, the SP PLUS Series offers a 6-year warranty*. The futuristic styling and design cater to the sensibilities of the modern farmer. The Mahindra SP PLUS Series is made for the smart farmer who yearns to do more with his tractor and tools.

Best Styling & Design



The SP PLUS Series offers styling & design that is both, futuristic and functional.

1.4 kW (2 HP) More Power



With the highest power in segment, get more work done even with larger implements.

Best-in-class Mileage



With lowest SFC, SP PLUS series consumes lowest fuel in any application

Best Back-up Torque



The higher back-up torque enables you to reach deeper into the soil than ever before.

Highest Max Torque



With maximum torque, the SP Plus series covers more land at any given time.



For the first time in the industry, 2+4 years of warranty helps you work with complete peace of mind.



mahindra
475DI
SP PLUS
32.8 kW (44 HP)

*2 years of standard warranty on the entire tractor and 4 years of warranty on engine and transmission wear and tear item. This warranty is not applicable on OEM items and wear & tear items.

Multi-application suitability



Rotavator

Higher PTO power, Highest Max torque, Higher back up torque	Excellent soil pulverization Better coverage and faster work completion.
Low SFC	Best-in class fuel efficiency.



Cultivator

Optimum tractor weight	Allows for deep tillage operation and ensures that the implement stays on the ground throughout the operation.
Advanced hydraulics	Gives uniform depth of cut across the entire field.



Reversible Mb Plough

Highest Max torque	Allows for deep tillage operation and ensures that the implement stays on the ground throughout the operation.
ADDC levers	Good depth of cut during ploughing operations.



Puddling

Optimum gear speeds	Give superior performance in soil preparation with wheel cage.
Optimum tractor weight	Leads to less tractor sinkage thereby reducing the load on the tractor.



Seed Drill

Advanced hydraulics	Ensured the right depth and precision in sowing the seeds while using seed drill application.
Optimum gear speeds	Perfect speeds matched with the needs of seeding.



Potato Planter & Digger

Heavy duty hydraulics	Achieves uniform depth in Potato planting & digging operations for no losses.
------------------------------	---



Thresher

Higher PTO power	Gives superior load taking capacity.
Water Cooled Engine	Ensures no overheating & it comes with a thresh guard, that ensures no dust/bhusa enters the radiator thus preventing any kind of choking.



Baler

Higher PTO power	Helps in making compact Bales without any RPM Drop.
Water Cooled Engine	It allows you to work for longer hours.

MAHINDRA
275DI SP PLUSMAHINDRA
275DI TU SP PLUSMAHINDRA
415DI SP PLUSMAHINDRA
475DI SP PLUSMAHINDRA
575DI SP PLUS

Engine Power kW (HP)	27.6 (37)	29.1 (39)	31.3 (42)	32.8 (44)	35.0 (47)
No. of Cylinders	3	3	4	4	4
Maximum Torque (Nm)	136	135	167	172.1	178.6
Torque at Maximum Power (Nm) Rated Torque	117	116	138	142	151
Maximum PTO kW (HP)	24.8 (33.3)	25.3 (34.0)	27.9 (37.5)	29.0 (39)	31.3 (42)
Rated r/min	2000	2000	2000	2000	2000
Max Power SFC (g/hp-hr)	186.7	180.6	174.2	186.0	184.5
Steering Type	Dual Acting Power/ Manual (Optional)				
Rear Tyre	13.6 x 28 / 12.4 x 28 available	13.6 x 28 / 12.4 x 28 available	13.6 x 28 / 12.4 x 28 available	13.6 X 28	14.9 x 28 / 13.6 x 28 available
Engine Cooling	Water Cooled				
Transmission Type	Partial Constant Mesh				
Ground speeds	F - 2.9 to 29.6 R - 4.1 & 11.9	R - 2.9 to 30.9 R - 4.1 & 11.9	F - 2.9 to 29.8 F - 4.1 & 11.9	R - 2.9 to 29.9 R - 4.1 & 11.9	F - 2.9 to 29.9 F - 4.1 & 11.9
No of Gears	8 Forward+2 Reverse				
Clutch	"Single (std) Dual with RCRPTO (opt)"				
Hydraulic Pump Flow (l/min)	29.5	32.4	29.5	29.5	29.5
Hydraulics Lifting Capacity (kg)	1500	1500	1500	1500	1500

*T&C: The accessories and images showed in the creative may deafer or change from time to time

MAHINDRA TRACTORS

Mahindra & Mahindra Ltd., Farm Equipment Sector: Farm Division,
AFS Headquarters, Mahindra Tower, 1st Floor, Akurli Road, Kandivali (E), Mumbai - 400 101, India.

www.mahindratractor.com | [www. mahindra.com](http://www.mahindra.com)

Toll-free number 1800 4256576 | www.mahindratractor.com

[Facebook.com/mahindratractorsindia](https://www.facebook.com/mahindratractorsindia) | twitter.com/tractormahindra

**SPACE FOR
DEALER PANNEL**

