

A Title

An Author¹ and Another Author²

¹An affiliation

²Another affiliation

Abstract

An abstract.

1 Introduction

We consider a variant of the classic Art Gallery problem, where we instead seek to optimize the length of the boundary seen by the guards, not the number of guards themselves. Specifically, given a simple polygon P and $k \in \mathbb{N}$, we want to find the k vertex guards which maximize the length of the boundary of P that is watched. We define the set of vertices of P as V_P , and $L(S)$ as the length of the boundary seen by the set of vertex guards/vertices S . Note that $L(S)$ is necessarily at most the perimeter of P .

MAXIMUM LENGTH VERTEX GUARD

Input: A simple polygon P and a positive integer $k \in \mathbb{N}$.

Task: Find a set of vertices $S \subseteq V_P$ of size at most k such that $L(S)$ is maximized.

We also consider a weighted variant of this problem, where P is a simple polygon composed of possibly collinear weighted line segments. Art galleries contain paintings, and some have more value than others. With limited guards, a realistic task would be to maximize not the total boundary watched, but the total value of paintings watched. In our definition, a weighted segment must be completely seen by our k guards to be considered “watched”. We define $W(S)$ as the weighted analog of $L(S)$, the sum of weights of all segments on the boundary of P that are completely watched by guards in S .

MAXIMUM VALUE VERTEX GUARD

Input: A weighted polygon P and a positive integer $k \in \mathbb{N}$.

Task: Find a set of vertices $S \subseteq V_P$ of size at most k such that $W(S)$ is maximized.

Finally, we consider a dynamic version of MAXIMUM VALUE VERTEX GUARD, which we’ll call DYNAMIC MAXIMUM VALUE VERTEX GUARD. New paintings may arrive in an art gallery, and their arrangement around the gallery may change. Thinking of vertex guards as cameras, it can be costly and time-consuming rearrange and reinstall cameras across the room (at least compared to moving the paintings around). If the segment weights on the weighted polygon change, how can we modify our solution (with minimal changes) to maintain an approximate solution for MAXIMUM VALUE VERTEX GUARD at each timestep?

Obviously this dynamic problem needs to be specified a lot more, but hopefully the general idea of/motivation for the problem is showing through. I am trying to create a dynamic set cover analog for art gallery, where elements are inserted/removed one at a time, and the goal is to maintain a set cover that is still an approximate solution (without simply recalculating a set cover at each change).

1.1 Related Works

Need a paragraph discussing more conventional Art gallery problem literature (authors+results). Klee, O'Rourke, Das

In [3, 5, 4], Fragoudakis et al. pose both MAXIMUM LENGTH VERTEX GUARD and MAXIMUM VALUE VERTEX GUARD. They prove that both problems are APX-complete in [5], meaning these problems are NP-hard and also permit no PTAS unless $P = NP$. In [3], they present a $(1 - 1/e)$ approximation for maximizing the vertex-guarded *interior* of a polygon which runs in $O(k^2n^2)$ and depends on segmenting the polygon into visibility regions.

[1] presents several inapproximability results for art gallery problems, with α -Floodlights.

Need to discuss some more dynamic set cover. Here is the most recent paper I've been able to find.

[2]

1.2 Our Contributions

For MAXIMUM LENGTH VERTEX GUARD and MAXIMUM VALUE VERTEX GUARD, we present an NP-hardness proof from SET COVER

References

- [1] A. Abdelkader, A. Saeed, K. Harras, and A. Mohamed. The inapproximability of illuminating polygons by α -floodlights. *Proceedings of the Canadian Conference on Computational Geometry 2015*, August 2015.
- [2] A. Bukov, S. Solomon, and T. Zhang. Nearly optimal dynamic set cover: Breaking the quadratic-in- f time barrier. pages 824–863, 2025. doi: 10.1137/1.9781611978322.24.
- [3] I. Emiris, C. Fragoudakis, and E. Markou. Maximizing the guarded interior of an art gallery. *European Workshop on Computational Geometry*, pages 165–169, March 2006.
- [4] C. Fragoudakis, E. Markou, and S. Zachos. How to place efficiently guards and paintings in an art gallery. *Lecture Notes in Computer Science*, 3746:145–154, November 2005. doi: 10.1007/11573036_14.
- [5] C. Fragoudakis, E. Markou, and S. Zachos. Maximizing the guarded boundary of an art gallery is apx-complete. *Computational Geometry*, 38:170–180, October 2007.