

Module 10: Infrastructure Security and WAN Technologies

1. 13- A Cisco Catalyst switch connects to what should be individual user PCs. Each port has the same port security configuration, configured as follows: interface range gigabit Ethernet 0/1 - 24 switchport mode access switchport port-security switchport port-security mac-address sticky Which of the following answers describe the result of the port security configuration created with these commands? (Choose two)

Answer: A

Answer: B

3. What is the Administrative Distance of internal EIGRP routes?

Answer: 90

4. When a subnet mask is presented in binary, what do the binary 1s represent?

Answer: The network portion of an associated address

5. Which switch would STP choose to become the root bridge in the selection process?

Answer: 32768: 11-22-33-44-55-66

6. Which of the following devices is used by the service provider to provide WAN services?

Answer: CSU/DSU

7. Your Cisco IOS router is acting as a DHCP server. Which command will display the addresses that have been handed out to clients on the LAN?

Answer: show ip dhcp bindings

8. Which of the following commands would you use to enable EIGRP only on those interfaces with an IP address from 10.1.1.0 through 10.1.1.63?

Answer: network 10.1.1.0 0.0.0.63

9. What command could you use to have R3 advertise an OSPFv3 default route to the internal network?

Answer: default-information originate always in OSPFv3 router configuration mode

10. Which command is used to verify NAT interface roles?

Answer: show ip nat statistics

11. When using the “show EtherChannel summary” command, what does the “u” flag signify?

Answer: In use

12. Which command could you enter to encrypt passwords?

Answer: service password-encryption

13. Which command is used to identify IPv4 addresses in a DHCP pool?

Answer: network

14. Which are true about ACLs on router interfaces? (Choose two)

Answer:

A. Inbound ACLs are processed before routing table lookup

C. Outbound ACLs are processed after routing table lookup

15. Which conditions can prevent OSPFv2 routers from learning routes? (Choose two)

Answer:

A. ACL blocking router advertisements

C. Physical connectivity issues between routers

16. Which statements describe neighbor discovery functionality in IPv6? (Choose two)

Answer:

A. Determines the link layer address of a neighbor

D. Queries for duplicate addresses

17. Which IPv6 prefix will an enterprise network typically receive from a provider?

Answer: /48

18. How should a switch be configured for remote access?

Answer: Assign a password and privilege level

19. A network technician designs a network with hosts in the same VLAN and redundancy. What conclusion is true?

Answer: The connection between switches should be a trunk

20. What command enables EIGRP on a specific IP range?

Answer: network 10.1.1.0 0.0.0.63

21. Which device provides WAN services in a provider network?

Answer: CSU/DSU

22. What is the function of the “u” flag in EtherChannel summary?

Answer: In use

23. Which command encrypts all passwords?

Answer: service password-encryption

24. What command is used to define the address range for a DHCP pool?

Answer: network

25. What are true regarding ACL processing on router interfaces? (Choose two)

Answer:

- A. Inbound ACLs are processed before routing table lookup
- C. Outbound ACLs are processed after routing table lookup

26. Which condition could prevent routers from learning routes in OSPFv2? (Choose two)

Answer:

- A. ACL blocking advertisements
- C. Layer 1 (physical) connectivity issues

27. What are IPv6 neighbor discovery features? (Choose two)

Answer:

- A. Determines link-layer address of a neighbor
- D. Queries for duplicate addresses

28. What IPv6 prefix is generally provided to an enterprise?

Answer: /48

29. How to configure a switch for remote access?

Answer: Assign a password and privilege level

30. What conclusion can be made from a network design with VLAN and redundancy?

Answer: The connection between switches should be a trunk