

Using TensorFlow with Categorical Features to Predict Income Bracket

May 2, 2024

1 Classification Exercise

We'll be working with some California Census Data, we'll be trying to use various features of an individual to predict what class of income they belong in ($>50k$ or $\leq 50k$).

Here is some information about the data:

Column Name

Type

Description

age

Continuous

The age of the individual

workclass

Categorical

The type of employer the individual has (government, military, private, etc.).

fnlwgt

Continuous

The number of people the census takers believe that observation represents (sample weight). This variable will not be used.

education

Categorical

The highest level of education achieved for that individual.

education_num

Continuous

The highest level of education in numerical form.

marital_status

Categorical

Marital status of the individual.

occupation

Categorical

The occupation of the individual.

relationship

Categorical

Wife, Own-child, Husband, Not-in-family, Other-relative, Unmarried.

race

Categorical

White, Asian-Pac-Islander, Amer-Indian-Eskimo, Other, Black.

gender

Categorical

Female, Male.

capital_gain

Continuous

Capital gains recorded.

capital_loss

Continuous

Capital Losses recorded.

hours_per_week

Continuous

Hours worked per week.

native_country

Categorical

Country of origin of the individual.

income_bracket

Categorical

“>50K” or “<=50K”, meaning whether the person makes more than \$50,000 annually.

1.0.1 THE DATA

** Read in the census_data.csv data with pandas**

```
[1]: import tensorflow as tf
from keras.models import Sequential
import pandas as pd
from keras.layers import Dense, Input
from keras.optimizers import SGD
import pandas as pd
import numpy as np
```

```
[2]: df = pd.read_csv('/Users/sandinatatu/Desktop/Tensorflow-Bootcamp-master/
↳02-TensorFlow-Basics/census_data.csv')
```

```
[3]: df.head()
```

```
[3]:   age      workclass  education  education_num  marital_status \
0   39      State-gov   Bachelors             13      Never-married
1   50  Self-emp-not-inc   Bachelors             13  Married-civ-spouse
2   38      Private    HS-grad              9      Divorced
3   53      Private    11th              7  Married-civ-spouse
4   28      Private   Bachelors             13  Married-civ-spouse

      occupation  relationship    race  gender  capital_gain \
0   Adm-clerical  Not-in-family  White   Male         2174
1  Exec-managerial      Husband  White   Male           0
2  Handlers-cleaners  Not-in-family  White   Male           0
3  Handlers-cleaners      Husband  Black   Male           0
4   Prof-specialty      Wife    Black  Female           0

  capital_loss  hours_per_week  native_country  income_bracket
0           0             40  United-States    <=50K
1           0             13  United-States    <=50K
2           0             40  United-States    <=50K
3           0             40  United-States    <=50K
4           0             40         Cuba    <=50K
```

1.1 Convert the Lable Column to 0s and 1s

```
[4]: import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
import tensorflow as tf
from keras.layers import Input, Dense, Concatenate, StringLookup
from keras.models import Model
```

```
[5]: df = pd.read_csv('/Users/sandinatatu/Desktop/Tensorflow-Bootcamp-master/
↳02-TensorFlow-Basics/census_data.csv')
df['income_bracket'] = (df['income_bracket'] == '>=50k').astype(int)
```

1.2 Perform a Train Test Split on the Data

```
[6]: df['income_bracket'] = (df['income_bracket'] == ">=50K").astype('int')
X = df.drop('income_bracket', axis=1)
y = df['income_bracket']

X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
↳ random_state=42)
```

1.3 Scale your numeric features

```
[7]: numeric_features = ['age', 'education_num', 'capital_gain', 'capital_loss',
↳ 'hours_per_week']
categorical_features = ["education", "marital_status", "occupation",
↳ "relationship", "race", "gender", "native_country"]
scaler = StandardScaler()
X_train_numeric = scaler.fit_transform(X_train[numeric_features])
X_test_numeric = scaler.transform(X_test[numeric_features])
```

1.4 Create an input layer which will be used to train your model

```
[8]: import tensorflow as tf
from keras.layers import Input, StringLookup, Embedding, Concatenate, Dense
from keras.models import Model

input_layers = []
input_features = []

for feature in numeric_features:
    input_layer = Input(shape=(1,), name=f'{feature}_input')
    input_layers.append(input_layer)
    input_features.append(input_layer)

from keras.layers import Flatten

for feature in categorical_features:
    input_layer = Input(shape=(1,), dtype='string', name=f'{feature}_input')
    lookup = StringLookup(output_mode='int', num_oov_indices=1)
    lookup.adapt(X_train[feature])

    num_tokens = lookup.vocabulary_size()
    embedding_dim = int(num_tokens**0.5)
    embedding = Embedding(input_dim=num_tokens, output_dim=embedding_dim,
↳ name=f'{feature}_embedding')(lookup(input_layer))

    flatten = Flatten()(embedding)
```

```
input_layers.append(input_layer)
input_features.append(flatten)
```

1.5 Build and compute model accuracy on training set. Use 10 epochs, and a batch size of 32.

```
[9]: concatenated_features = Concatenate()(input_features)

output = Dense(1, activation='sigmoid')(concatenated_features)

model = Model(inputs=input_layers, outputs=output)
model.compile(optimizer='adam', loss='binary_crossentropy',
              metrics=['accuracy'])

train_inputs = [X_train_numeric[:, i] for i in range(X_train_numeric.shape[1])]
              + [X_train[feature] for feature in categorical_features]
test_inputs = [X_test_numeric[:, i] for i in range(X_test_numeric.shape[1])]
              + [X_test[feature] for feature in categorical_features]

history = model.fit(
    train_inputs,
    y_train,
    validation_data=(test_inputs, y_test),
    epochs=10,
    batch_size=32
)
```

Epoch 1/10

814/814 1s 552us/step -

accuracy: 0.9202 - loss: 0.2086 - val_accuracy: 1.0000 - val_loss: 0.0026

Epoch 2/10

814/814 0s 398us/step -

accuracy: 1.0000 - loss: 0.0019 - val_accuracy: 1.0000 - val_loss: 6.4740e-04

Epoch 3/10

814/814 0s 396us/step -

accuracy: 1.0000 - loss: 5.4252e-04 - val_accuracy: 1.0000 - val_loss:
2.6562e-04

Epoch 4/10

814/814 0s 398us/step -

accuracy: 1.0000 - loss: 2.3224e-04 - val_accuracy: 1.0000 - val_loss:
1.3161e-04

Epoch 5/10

814/814 0s 397us/step -

accuracy: 1.0000 - loss: 1.1776e-04 - val_accuracy: 1.0000 - val_loss:
7.2023e-05

Epoch 6/10

814/814 0s 397us/step -

```
accuracy: 1.0000 - loss: 6.6719e-05 - val_accuracy: 1.0000 - val_loss:
4.1636e-05
Epoch 7/10
814/814          0s 398us/step -
accuracy: 1.0000 - loss: 3.6895e-05 - val_accuracy: 1.0000 - val_loss:
2.4844e-05
Epoch 8/10
814/814          0s 397us/step -
accuracy: 1.0000 - loss: 2.3331e-05 - val_accuracy: 1.0000 - val_loss:
1.5171e-05
Epoch 9/10
814/814          0s 395us/step -
accuracy: 1.0000 - loss: 1.4148e-05 - val_accuracy: 1.0000 - val_loss:
9.4080e-06
Epoch 10/10
814/814          0s 398us/step -
accuracy: 1.0000 - loss: 8.6715e-06 - val_accuracy: 1.0000 - val_loss:
5.8934e-06
```

1.6 Compute model accuracy on test set.

```
[10]: performance = model.evaluate(test_inputs, y_test)
      print('Test Loss and Accuracy:', performance)
```

```
204/204          0s 252us/step -
accuracy: 1.0000 - loss: 5.9458e-06
Test Loss and Accuracy: [5.893413799640257e-06, 1.0]
```