

Annex 162D

(informative)

Cable assemblies and hosts for 100GBASE-CR1, 200GBASE-CR2, and 400GBASE-CR4

162D.1 Overview

This annex describes cable assembly types specified in 162.11 for hosts with 100GBASE-CR1, 200GBASE-CR2, or 400GBASE-CR4 Physical Layers. The six MDI connector receptacles specified are given in Table 162D–1. This enables multiple cable assembly types with different combinations of the plug connectors at each end.

Table 162D–1—Host receptacles and cable assembly plugs

Receptacle/Plugs	Reference
SFP112	162C.2.1
SFP-DD112	162C.2.2
DSFP	162C.2.3
QSFP112	162C.2.4
QSFP-DD800	162C.2.5
OSFP	162C.2.6

162D.1.1 Cable assembly types

Cable assembly types, denoted as 100GBASE-CR1, 200GBASE-CR2, and 400GBASE-CR4, have a common set of electrical parameters specified in 162.11, enabling a 2 m length. Cable assembly types with different combinations of the plug connectors for compatible host receptacles and supportable number of PMDs are given in Table 162D–2 for 100GBASE-CR1, Table 162D–3 for 200GBASE-CR2, and Table 162D–4 for 400GBASE-CR4; other combinations are possible.

Table 162D–2—100GBASE-CR1 cable assembly types and supportable number of PMDs

One end		Other end(s)		Supportable PMDs
Receptacle/Plug	Number	Receptacle/Plug	Number	Number
SFP112	1	SFP112	1	1
SFP-DD112	1	SFP112	2	2
DSFP	1	SFP112	2	2
QSFP112	1	SFP112	4	4

Table 162D–2—100GBASE-CR1 cable assembly types and supportable number of PMDs (*continued*)

One end		Other end(s)		Supportable PMDs
Receptacle/Plug	Number	Receptacle/Plug	Number	Number
QSFP-DD800	1	SFP112	8	8
OSFP	1	SFP112	8	8
SFP-DD112	1	SFP-DD112	1	2
DSFP	1	DSFP	1	2
QSFP112	1	QSFP112	1	4
QSFP-DD800	1	QSFP-DD800	1	8
OSFP	1	OSFP	1	8

Table 162D–3—200GBASE-CR2 cable assembly types and supportable number of PMDs

One end		Other end(s)		Supportable PMDs
Receptacle/Plug	Number	Receptacle/Plug	Number	Number
SFP-DD112	1	SFP-DD112	1	1
SFP-DD112	1	DSFP	1	1
QSFP112	1	SFP-DD112	2	2
QSFP-DD800	1	112	4	4
OSFP	1	SFP-DD112	4	4
DSFP	1	DSFP	1	1
QSFP112	1	DSFP	2	2
QSFP-DD800	1	DSFP	4	4
OSFP	1	DSFP	4	4
QSFP112	1	QSFP112	1	2
QSFP-DD800	1	QSFP-DD800	1	4
QSFP-DD800	1	OSFP	1	4
OSFP	1	OSFP	1	4

Table 162D-4—400GBASE-CR4 cable assembly types and supportable number of PMDs

One end		Other end(s)		Supportable PMDs
Receptacle/Plug	Number	Receptacle/Plug	Number	Number
QSFP112	1	QSFP112	1	1
QSFP-DD800	1	QSFP112	2	2
OSFP	1	QSFP112	2	2
QSFP-DD800	1	QSFP-DD800	1	2
QSFP-DD800	1	OSFP	1	2
OSFP	1	OSFP	1	2