



ENERGYLINE 65

SPECIFICATION

Energyline 65 1135mm wire suspended with uplight white luminaire with 1700lm/m microprism diffuser tuneable white CRI90 direct lighting and 1700lm/m tuneable white CRI90 ceiling wash indirect lighting complete with fully internal casambi wireless control gear, 7 year warranty, light leak prevention, L80 B10 72000hrs and IP5x protection

Product ID:	ELA-00674
-------------------------------	-----------

• Profile: 65

• Fitting Width: 65mm

• Fitting height: 86mm

• Total Fitting length: 1135mm

(includes end caps)

• Direct Distribution: Microprism Diffuser

• Direct Output: 1700lm/m

• Direct CRI: 90

• Direct CCT: Tuneable White

• Indirect Distribution: Ceiling Wash

• Indirect Output: 1700lm/m

• Indirect CRI: 90

Indirect CCT: Tuneable WhiteControl: casambi wireless


• Driver: Internal

• Lifetime: L80 B10 72,000h

Mounting Supplied with a minimum of two wires

per fitting section.

IP Rating IP5xFinish: White



PRODUCT FEATURES

- Accu-join for light-tight seamless joins
- Concealed fixing, light-tight end caps
- Factory finished for rapid and low risk installation
- Efficacy up to 121lm/W
- Utilises microprism direct component with a diffuse appearance, possible for UGR 19 glare control
- Excellent horizontal illumination across the ceiling





INDICATIVE IMAGES ONLY

FACTORY NOTES

* Luminaire Output estimated at 121 lm/W

Lumen maintenance values are calculated by IEC 62717:2014 incorporating (L) and (B). Allow 5% reduction in luminous flux for 3000K.

Custom luminous fluxes available, contact Energyline factory. Polarcurve is indicative only, does not reflect selected lumen outputs.









Product Drawing

Product Code: ELA-00674 Total Length: 1135mm Energyline 65 Suspended with uplight

KEY
----: Join

■ : Mounting

Cable Entry 120mm from end		1		
	•		•	
		1135mm		

Drawing not to scale Luminaire length includes 6mm end cap at each end Drawing based on product installation in NZL