

misc stuff I will find another place for passwords

/etc/passwd is a bit long in the tooth. /etc/master.passwd is where the action is now kept. if you look at that and need to, for example, change the login shell you need to run `pwd_mkdb /etc/master.passwd` afterwards

Edit these files to contain the following. In `.bashrc` put these statements.

```
# .bashrc - Bourne Again Shell configuration file # for interactive shells. # file permissions: rwxr-xr-x
umask 022 BLOCKSIZE=K; export BLOCKSIZE EDITOR=pico; export EDITOR PAGER=/usr/bin/more;
export PAGER
```

```
# some useful aliases alias h='fc -l' alias j=jobs alias m=$PAGER alias ll='ls -laFo' alias ls='ls -la
-G' alias g='egrep -i' alias ll='ls -laFo' alias ls='ls -la -G' alias g='egrep -i'
```

```
# set prompt PS1="u@ w $> "
```

Now for `.bash_profile` put the following statements:

```
# .bash_profile - Bourne Again Shell configuration file # for login shells. PATH=/sbin:/bin:/usr/sbin:/usr/bin:/usr/ga
# file permissions: rwxr-xr-x umask 022 BLOCKSIZE=K; export BLOCKSIZE EDITOR=pico; export
EDITOR PAGER=/usr/bin/more; export PAGER
```

```
# set ENV to a file invoked each time bash is started # for interactive use. ENV=$HOME/.shrc;
export ENV # some useful aliases alias h='fc -l' alias j=jobs alias m=$PAGER alias ll='ls -laFo' alias
ls='ls -la -G' alias g='egrep -i'
```

```
# set prompt PS1="u@w $> "
```

```
http://www.freeos.com/articles/4040/
```

```
href="http://www.cyberciti.biz/tips/freebsd-how-to-start-restart-stop-network-service.html"
```

```
# /etc/rc.d/netif restart && /etc/rc.d/routing restart
```