Photopic

A Luminous Efficacy Optimizer for Spectral Power Distributions

User Manual

March 2026

Contents

1 Introduction **3**
- 1.1 Background . . . 3
- 1.2 How it works . . . 3

2 Mathematical Foundations **3**
- 2.1 Planck's law and the blackbody reference . . . 3
- 2.2 Luminous efficacy of radiation . . . 4
- 2.3 Tristimulus values and chromaticity . . . 4
- 2.4 Correlated color temperature . . . 4
- 2.5 Color Rendering Index . . . 4
- 2.6 The optimization problem . . . 5
- 2.7 Parametric spectrum . . . 6

3 Building **6**
- 3.1 Prerequisites . . . 6
- 3.2 Build procedure . . . 7

4 Command-Line Interface **7**
- 4.1 `-run`: Maximize efficacy . . . 7
- 4.2 `-run-maxr9`: Maximize R_9 (inverse problem) . . . 8
- 4.3 `-run-drop`: Multi-run with TCS axis dropping . . . 8

5 Worked Examples **8**
- 5.1 Example 1: Basic run at CRI ≥ 80 . . . 8
- 5.2 Example 2: High CRI at CRI ≥ 95 . . . 9
- 5.3 Example 3: Moderate CRI with R_9 constraint . . . 9
- 5.4 Example 4: Inverse problem—maximize R_9 at efficacy ≥ 350 . . . 9
- 5.5 Example 5: Running the full CRI sweep . . . 9
- 5.6 Example 6: Sweeping the efficacy–R_9 frontier . . . 9
- 5.7 Example 7: Plotting results . . . 9

6 Output Files **10**
- 6.1 File naming convention . . . 10
- 6.2 `.res` files: Optimization results . . . 10
- 6.3 `.dat` files: Spectral data . . . 11

7 Architecture **11**
7.1 Parametric spectrum model . . . 11
7.2 Hierarchical subdivision . . . 11
7.3 COBYLA optimizer . . . 12
7.4 CRI calculation . . . 12
7.5 Constraint convention . . . 12

8 Interactive Use **13**
8.1 Useful interactive commands . . . 13

9 Customization **14**
9.1 Writing new objective functions . . . 14
9.2 What `calc-specs` returns . . . 14
9.3 Accessing individual fields . . . 15
9.4 Example: maximize efficacy subject to $R_9 \geq 50$ . . . 15

10 Reference **15**
10.1 Global variables . . . 15
10.2 Key source files . . . 16
10.3 Physical constants . . . 16

1 Introduction

`photopic` is a constrained optimization tool that finds spectral power distributions (SPDs) maximizing the *luminous efficacy of radiation* (LER) or the R_9 color rendering index, subject to constraints on CRI (Color Rendering Index), CCT (Correlated Color Temperature), D_{uv} (distance from the Planckian locus), and individual color rendering components R_i.

The tool answers questions of the form: "What is the theoretical maximum luminous efficacy achievable at 2700 K with CRI $\geq$ 80?" and, conversely, "What is the best R_9 (saturated red rendering) achievable at 2700 K with CRI $\geq$ 80 and efficacy $\geq$ 350 lm/W?"

1.1 Background

The luminous efficacy of radiation (LER) measures how efficiently a spectrum produces visible light, in lumens per watt of radiated power. The theoretical maximum is 683 lm/W, achieved by monochromatic light at 555 nm—which has a CRI of zero. Real light sources must balance efficacy against color quality: broader spectra render colors more faithfully but waste energy in wavelength regions where the eye is less sensitive.

`photopic` explores this trade-off computationally, using the COBYLA derivative-free constrained optimizer to search a parametric space of spectral shapes. Color rendering is evaluated via the CIE 13.3 test color method with 14 test color samples (TCS).

1.2 How it works

`photopic` starts from a blackbody spectrum at the target CCT and applies a multiplicative modifier of the form $\exp(f(\lambda))$, where $f(\lambda)$ is a piecewise-linear function defined by a parameter vector. The optimizer adjusts these parameters to minimize (or maximize) the objective while satisfying the constraints.

To avoid poor local minima in the high-dimensional space, the optimization uses *hierarchical subdivision*: it begins with 2 parameters (a single linear slope across the visible spectrum), optimizes, then doubles the resolution to 3, 5, 9, 17, 33, 65, and finally 129 parameters (approximately 3 nm spacing across 380–770 nm). At each level, the COBYLA step size is halved.

2 Mathematical Foundations

This section summarizes the physics and colorimetry underlying the optimization. For a full treatment and computational results, see the companion report [1].

2.1 Planck's law and the blackbody reference

The spectral radiance of a blackbody at temperature T is

$$B(\lambda, T) = \frac{2hc^2}{\lambda^5} \cdot \frac{1}{\exp\big(hc/\lambda kT\big) - 1} \tag{1}$$

where h is Planck's constant, c the speed of light, and k Boltzmann's constant. This serves as the starting point for the optimization: the parametric spectrum is a multiplicative perturbation of $B(\lambda, T)$.

2.2 Luminous efficacy of radiation

The luminous efficacy of radiation (LER) measures how effectively a spectral power distribution $S(\lambda)$ produces the sensation of brightness:

$$\eta = K_m \frac{\displaystyle\int_{\lambda_0}^{\lambda_1} S(\lambda)\, V(\lambda)\, d\lambda}{\displaystyle\int_{\lambda_0}^{\lambda_1} S(\lambda)\, d\lambda} \tag{2}$$

where $V(\lambda)$ is the CIE photopic luminous efficiency function (peaking at unity at 555 nm), $K_m = 683\,\mathrm{lm/W}$ is the maximum luminous efficacy, and $[\lambda_0, \lambda_1] = [380, 770]$ nm spans the visible spectrum. For monochromatic light at 555 nm, $\eta = 683\,\mathrm{lm/W}$; for a broadband source, η is necessarily lower. *This is the primary quantity that* `photopic` *maximizes.*

2.3 Tristimulus values and chromaticity

The CIE 1931 tristimulus values of a spectrum $S(\lambda)$ are

$$X = \int_{\lambda_0}^{\lambda_1} S(\lambda)\, \bar{x}(\lambda)\, d\lambda, \quad Y = \int_{\lambda_0}^{\lambda_1} S(\lambda)\, \bar{y}(\lambda)\, d\lambda, \quad Z = \int_{\lambda_0}^{\lambda_1} S(\lambda)\, \bar{z}(\lambda)\, d\lambda \tag{3}$$

where $\bar{x}$, $\bar{y}$, $\bar{z}$ are the CIE 1931 2° standard observer color matching functions, tabulated at 1 nm resolution in `CieXyz.i3`. The chromaticity coordinates are

$$x = \frac{X}{X+Y+Z}, \qquad y = \frac{Y}{X+Y+Z} \tag{4}$$

and the CIE 1960 UCS coordinates used for CCT determination are

$$u = \frac{4X}{X+15Y+3Z}, \qquad v = \frac{6Y}{X+15Y+3Z}. \tag{5}$$

2.4 Correlated color temperature

The correlated color temperature (CCT) of a source is the temperature T of the Planckian radiator whose chromaticity is nearest in (u, v) space:

$$\mathrm{CCT} = \arg\min_T \left\| (u_{\mathrm{source}}, v_{\mathrm{source}}) - (u_{\mathrm{Planck}}(T), v_{\mathrm{Planck}}(T)) \right\| \tag{6}$$

The signed distance from the Planckian locus is D_{uv}, constrained to $D_{uv} \leq 0.012$ to ensure the source chromaticity lies acceptably close to the blackbody locus. `photopic` determines the CCT by Brent's method search over a precomputed temperature-to-uv lookup table (`TempUv.m3`).

2.5 Color Rendering Index

The CIE General Color Rendering Index R_a quantifies how faithfully a test illuminant renders colors compared to a reference illuminant (a blackbody at the same CCT). For each of 14 test color samples (TCS) with reflectance $\rho_i(\lambda)$, the reflected spectrum under the test illuminant is

$$S_i^{\mathrm{test}}(\lambda) = \hat{S}(\lambda) \cdot \rho_i(\lambda) \tag{7}$$

where $\hat{S}$ is the Y-normalized test spectrum ($Y = 100$). The reflected spectrum is converted to CIE 1964 $U^*V^*W^*$ coordinates with von Kries chromatic adaptation:

$$W^* = 25\,Y^{1/3} - 17 \tag{8}$$

$$U^* = 13\,W^* \cdot (u' - u_0) \tag{9}$$

$$V^* = 13\,W^* \cdot (v' - v_0) \tag{10}$$

where (u_0, v_0) is the adapted white point. The color difference between test and reference renderings is

$$\Delta E_i = \sqrt{(\Delta U_i^*)^2 + (\Delta V_i^*)^2 + (\Delta W_i^*)^2} \tag{11}$$

and the special color rendering index for sample i is

$$R_i = 100 - 4.6\,\Delta E_i. \tag{12}$$

The general index averages the first eight (unsaturated pastel) samples:

$$R_a = \frac{1}{8}\sum_{i=1}^{8} R_i. \tag{13}$$

Notably, R_9 (saturated red) through R_{14} are *not* included in R_a. This is the well-known "CRI loophole": a spectrum can score $R_a \geq 80$ while rendering saturated reds poorly ($R_9 < 0$), which is precisely the scenario explored by the inverse problem mode of `photopic`.

2.6 The optimization problem

In the forward mode (`-run`), `photopic` solves:

$$\boxed{\max_{\mathbf{p}}\ \eta\big(S(\lambda;\mathbf{p})\big) \quad \text{subject to} \quad \begin{cases} R_a \geq R_a^{\min} \\ \min_{i\in 1..8} R_i \geq R_a^{\min} - 10 \\ R_9 \geq R_9^{\min} \\ |\mathrm{CCT} - T_{\mathrm{target}}| \leq 50\,\mathrm{K} \\ D_{uv} \leq 0.012 \end{cases}} \tag{14}$$

In the inverse mode (`-run-maxr9`):

$$\boxed{\max_{\mathbf{p}}\ R_9\big(S(\lambda;\mathbf{p})\big) \quad \text{subject to} \quad \begin{cases} R_a \geq R_a^{\min} \\ \min_{i\in 1..8} R_i \geq R_a^{\min} - 10 \\ \eta \geq \eta_{\min} \\ |\mathrm{CCT} - T_{\mathrm{target}}| \leq 50\,\mathrm{K} \\ D_{uv} \leq 0.012 \end{cases}} \tag{15}$$

Both are solved by COBYLA, Powell's derivative-free constrained optimizer [2], which constructs linear approximations to the objective and constraint functions within a shrinking trust region.

2.7 Parametric spectrum

The spectrum is parameterized as

$$S(\lambda; \mathbf{p}) = B(\lambda, T) \cdot \exp\left(\sum_j p_j \, \phi_j(\lambda) \right) \tag{16}$$

where $\phi_j(\lambda)$ are hat functions (piecewise-linear basis functions) centered at uniformly spaced nodes $\lambda_j = \lambda_0 + j \cdot \Delta\lambda$ with $\Delta\lambda = (\lambda_1 - \lambda_0)/(n-1)$. The exponent $f(\lambda) = \sum_j p_j \phi_j(\lambda)$ is the linear interpolant of the parameter values p_j at the nodes. At $\mathbf{p} = \mathbf{0}$, $S = B$: the unperturbed blackbody. The exponential ensures $S(\lambda) > 0$ for all $\mathbf{p}$.

The hierarchical subdivision doubles the number of nodes at each stage, interpolating the coarse solution onto the fine grid:

$$n \in \{2,\ 3,\ 5,\ 9,\ 17,\ 33,\ 65,\ 129\} \tag{17}$$

$$\Delta\lambda \in \{390,\ 195,\ 97.5,\ \ldots,\ 3.05\} \text{ nm.} \tag{18}$$

References

[1] M. Nyström, *Theoretical Limits of Luminous Efficacy under Color Rendering Constraints: A Computational Study*, Technical Report, 2026. Available at https://github.com/IntelLabs/async-toolkit, branch `claude_edits`.

[2] M. J. D. Powell, "A direct search optimization method that models the objective and constraint functions by linear interpolation," in *Advances in Optimization and Numerical Analysis*, S. Gomez and J.-P. Hennart, eds., pp. 51–67, Kluwer, 1994.

[3] W. A. Thornton, "Luminosity and color-rendering capability of white light," *J. Opt. Soc. Am.*, vol. 61, no. 9, pp. 1155–1163, 1971.

[4] W. Walter, "An optimization approach to the computation of luminous efficacy bounds for sources with color rendering constraints," *Color Res. Appl.*, vol. 3, no. 2, pp. 83–90, 1978.

3 Building

3.1 Prerequisites

- A working CM3 (Critical Mass Modula-3) compiler, installed and in your `PATH` (or referenced by absolute path).
- The `m3utils` tree built—`photopic` depends on several libraries within the tree including `mscheme`, `modula3scheme`, `parseparams`, `integrate`, `cobyla`, `minimize`, `mpfr`, and `cit_util`.
- The `sstubgen` tool must also be available, since the build generates Scheme stubs for the Modula-3 interfaces.

3.2 Build procedure

Build the entire `m3utils` tree first (if not already done), then build `photopic`:

```
# Build the full m3utils tree (from the m3utils root)
cd m3utils
export CM3=yes
gmake

# Or build just photopic (after dependencies are built)
cd photopic/src
cm3 -override
```

The binary is placed in a target-specific directory alongside the source, e.g., `photopic/ARM64_DARWIN/photopic` on Apple Silicon macOS or `photopic/AMD64_LINUX/photopic` on x86-64 Linux.

If `sstubgen` is not in your default `PATH`, prefix the build command:

```
env PATH="/path/to/cm3/install/bin:${PATH}" cm3 -override
```

4 Command-Line Interface

`photopic` is a Modula-3 program that embeds MScheme, a Scheme interpreter. The main optimization logic lives in `photopic.scm`, which is loaded at startup via the `-scmfile` flag. All command-line invocations require the Scheme mode flags:

```
photopic <mode> <args...> -scm -scmfile photopic.scm
```

The `-scm` flag activates the embedded Scheme interpreter. The `-scmfile` flag specifies a Scheme source file to load (the path to `photopic.scm` relative to the working directory or as an absolute path).

4.1 `-run`: Maximize efficacy

```
photopic -run <cct> <min-cri> <min-r9> -scm -scmfile photopic.scm
```

Maximizes luminous efficacy of radiation (LER, in lm/W) subject to:

- CRI (Ra) $\geq$ `<min-cri>`
- $R_9 \geq$ `<min-r9>`
- Worst individual R_i ($i \in 1..8$) $\geq$ `<min-cri>`-10
- CCT within $\pm 50\,\mathrm{K}$ of `<cct>`
- $D_{uv} \leq 0.012$

The optimizer runs 8 hierarchical levels (2 to 129 parameters). Set `<min-r9>` to `-100` to leave R_9 effectively unconstrained.

4.2 `-run-maxr9`: Maximize R_9 (inverse problem)

```
photopic -run-maxr9 <cct> <min-cri> <min-efficacy> \
         -scm -scmfile photopic.scm
```

Maximizes the R_9 color rendering index subject to:

- CRI (Ra) $\geq$ `<min-cri>`
- Worst individual $R_i \geq$ `<min-cri>`-10
- Efficacy $\geq$ `<min-efficacy>` lm/W
- CCT within ± 50 K of `<cct>`
- $D_{uv} \leq 0.012$

This is the inverse of `-run`: instead of finding how efficient a spectrum can be, it finds how well saturated reds can be rendered at a given efficiency floor.

4.3 `-run-drop`: Multi-run with TCS axis dropping

```
photopic -run-drop <cct> <min-cri> -scm -scmfile photopic.scm
```

Performs multiple rounds of efficacy maximization. After each round, the test color sample axis with the worst R_i is removed from the CRI average, and the optimizer re-runs against the remaining axes. This explores how much additional efficacy can be gained by sacrificing individual color rendering dimensions.

5 Worked Examples

All examples assume you are in the `report-runs/` directory with the `photopic` binary at `../ARM64_DARWIN/photopic` (adjust the path for your platform) and `photopic.scm` at `../src/photopic.scm`.

For brevity, we define:

```
PHOTOPIC=../ARM64_DARWIN/photopic
SCMFILE=../src/photopic.scm
```

5.1 Example 1: Basic run at CRI $\geq$ 80

```
$PHOTOPIC -run 2700 80 -100 -scm -scmfile $SCMFILE
```

This maximizes efficacy for a 2700 K source with CRI $\geq$ 80 and no R_9 constraint. Expect the optimizer to produce a spectrum with efficacy around 400–420 lm/W, achieved by concentrating power in spectral regions where the eye is most sensitive while maintaining adequate color rendering. Output files are written to the current directory (see Section 6).

5.2 Example 2: High CRI at CRI $\geq$ 95

```
$PHOTOPIC -run 2700 95 -100 -scm -scmfile $SCMFILE
```

With a tighter CRI constraint, the optimizer has less freedom to reshape the spectrum. Expect efficacy around 350–370 lm/W—a significant penalty compared to CRI $\geq$ 80, because the spectrum must remain closer to a blackbody shape to render all 8 primary test colors faithfully.

5.3 Example 3: Moderate CRI with R_9 constraint

```
$PHOTOPIC -run 2700 82 50 -scm -scmfile $SCMFILE
```

This adds an $R_9 \geq 50$ constraint, requiring decent saturated red rendering. Without this constraint, the optimizer often sacrifices deep red content (which the eye is insensitive to) for higher efficacy. The R_9 floor forces retention of spectral power near 630 nm, reducing achievable efficacy.

5.4 Example 4: Inverse problem—maximize R_9 at efficacy $\geq$ 350

```
$PHOTOPIC -run-maxr9 2700 80 350 -scm -scmfile $SCMFILE
```

Asks: given a 2700 K source that must achieve CRI $\geq$ 80 and efficacy $\geq$ 350 lm/W, what is the best R_9 possible? This traces the Pareto frontier between efficacy and red rendering quality.

5.5 Example 5: Running the full CRI sweep

The script `run-optimizations.sh` automates running at multiple CRI levels:

```
./run-optimizations.sh            # all levels: 60 70 80 82 85 90 95 98
./run-optimizations.sh 90         # only CRI >= 90
./run-optimizations.sh 80 85 90   # specific levels
```

5.6 Example 6: Sweeping the efficacy–R_9 frontier

The script `run-maxr9-sweep.sh` sweeps efficacy from 300 to 430 lm/W in steps of 10, maximizing R_9 at each level:

```
./run-maxr9-sweep.sh
```

5.7 Example 7: Plotting results

After running optimizations, generate publication-quality figures:

```
python3 plot_spectra.py
```

This produces PDF and PNG files for:

- Blackbody vs. optimized spectrum comparison
- Multi-panel CRI comparison
- Convergence across resolution levels

- Overlay of all CRI-constrained spectra
- Efficacy vs. CRI trade-off curve
- R_9 vs. efficacy scatter plot

6 Output Files

All output is written to the current working directory.

6.1 File naming convention

Output files follow the pattern:

`<cct>_CRI<min-cri>_<suffix>_<dims>.<ext>`

where:

- `<cct>` is the target CCT (e.g., `2700`)
- `<min-cri>` is the minimum CRI constraint (e.g., `82`)
- `<suffix>` encodes run parameters (`R9=-100` for unconstrained R_9; `_maxR9_eff350` for the inverse problem)
- `<dims>` is the parameter count at the subdivision level (2, 3, 5, 9, 17, 33, 65, or 129)

One file is produced *at each subdivision level*, so a complete run at 8 levels generates 8 `.res` and 8 `.dat` files.

6.2 `.res` files: Optimization results

Each `.res` file is an S-expression on two lines.

Line 1: Computed specifications. A flat list with the following fields:

Position	Field	Description
1	CRI (Ra)	Average of $R_1 \dots R_8$
2	Worst R_i	Minimum of $R_1 \dots R_8$
3	Efficacy	Luminous efficacy of radiation (lm/W)
4	CCT	Correlated color temperature (K)
5	D_{uv}	Distance from Planckian locus
6–19	$R_1 \dots R_{14}$	Individual color rendering indices
20	CRI-14	Average of all 14 R_i values
21	Worst-14	Minimum of all 14 R_i values
22	Sel-CRI	CRI over selected TCS subset
23	Sel-worst	Worst R_i over selected subset
24	Worst axis	Index of the worst TCS axis

Example (from `2700_CRI82_R9=-100_129.res`):

```
(83.22 72.01 408.61 (2650.00 0.012) (93.16 87.51
 72.01 92.19 80.80 75.68 92.36 72.02 28.67 57.20
 83.54 16.30 90.87 80.46) 73.06 16.30 73.06 16.30 12)
```

This result achieves 408.6 lm/W at CRI = 83.2 with CCT = 2650 K and $R_9 = 28.7$.

Line 2: Parameter vector. The optimized parameter values for the piecewise-linear log-modifier. These can be used to reconstruct the spectrum or as a warm-start for further optimization.

6.3 `.dat` files: Spectral data

Two types of `.dat` files are produced:

- `w_<name>_<dims>.dat` — the Y-normalized optimized spectrum
- `base_<cct>.dat` — the unmodified blackbody reference at temperature `<cct>`

Both are two-column text files (wavelength in meters, spectral power density), with 391 data points at 1 nm resolution spanning 380–770 nm:

```
3.8e-7 5.366289953705953e6
3.8195e-7 5.7351389943960775e6
3.839e-7 6.1250440250444e6
...
```

To convert wavelengths to nanometers, multiply the first column by 10^9.

7 Architecture

7.1 Parametric spectrum model

The optimized spectrum is defined as:

$$S(\lambda) = B(\lambda, T) \cdot \exp\big(f(\lambda)\big)$$

where $B(\lambda, T)$ is the Planck blackbody spectrum at the target CCT, and $f(\lambda)$ is a piecewise-linear function defined by a parameter vector $\mathbf{p} = (p_0, p_1, \ldots, p_{n-1})$.

The parameter nodes are uniformly spaced across 380–770 nm. Between nodes, f is linearly interpolated. At $\mathbf{p} = \mathbf{0}$, the spectrum equals the unmodified blackbody. The exponential ensures the spectrum remains strictly positive for all parameter values.

This representation is implemented in `ParametricSpectrum.m3`. The function `GetFunc` returns an `LRFunction.T` that evaluates $S(\lambda)$ given a parameter vector; `EvalFunction` performs the interpolation lookup and exponential multiplication.

7.2 Hierarchical subdivision

Optimization begins at 2 parameters and proceeds through the sequence:

$$2 \to 3 \to 5 \to 9 \to 17 \to 33 \to 65 \to 129$$

At each level, the number of parameters follows $n_{k+1} = 2n_k - 1$ (inserting a midpoint between every adjacent pair). The `Subdivide` procedure interpolates the old parameter vector into the new, higher-resolution grid. The COBYLA initial step size (`rhobeg`) is halved at each level.

This hierarchical approach is essential: starting directly at 129 parameters would produce poor results because COBYLA would get trapped in a local minimum near the blackbody starting point. The low-dimensional stages identify the dominant spectral features (which wavelength regions to emphasize or suppress), and the subsequent stages refine the details.

At 129 parameters, the node spacing is $(770 - 380)/128 \approx 3.05$ nm, providing spectral features as narrow as approximately 6 nm (two nodes per feature).

7.3 COBYLA optimizer

COBYLA (Constrained Optimization BY Linear Approximation) is a derivative-free optimizer by M. J. D. Powell. It is well suited to this problem because:

- The CRI computation involves color adaptation and nonlinear coordinate transforms that are not easily differentiable.
- The constraint functions are nonlinear and involve search (CCT is found by minimizing distance in MacAdam uv space).
- The number of function evaluations per optimization step scales linearly with the number of parameters.

The Modula-3 binding (`COBYLA_M3.Minimize`) accepts the state vector, number of constraints, an objective/constraint evaluation function, `rhobeg` (initial trust-region radius), `rhoend` (convergence tolerance), and a maximum iteration count.

7.4 CRI calculation

Color rendering is evaluated following CIE 13.3:

1. Normalize the test spectrum so $Y = 100$.
2. Determine the CCT by minimizing distance in MacAdam 1960 uv space to the Planckian locus (Brent's method via `search-T`).
3. Generate the reference illuminant: a blackbody at the CCT.
4. For each of 14 test color samples (TCS), compute the reflected spectrum under both the test and reference illuminants.
5. Convert to CIE 1964 $U^*V^*W^*$ coordinates with von Kries chromatic adaptation.
6. $R_i = 100 - 4.6\,\Delta E_i$ where ΔE_i is the Euclidean distance between adapted and reference $U^*V^*W^*$ values.
7. CRI (Ra) $= \frac{1}{8}\sum_{i=1}^{8} R_i$.

The test color sample reflectance spectra are tabulated at 1 nm resolution in `Tcs.i3` (14 samples, covering pastels R_1–R_8 and saturated colors R_9–R_{14}). CIE $\bar{x}$, $\bar{y}$, $\bar{z}$ color matching functions are tabulated in `CieXyz.i3`; the photopic luminous efficiency function (683 lm/W peak) is in `CieSpectrum.i3`.

7.5 Constraint convention

In the objective/constraint function returned to COBYLA, the first element of the returned vector is the quantity to *minimize* (e.g., negative efficacy to maximize efficacy, or negative R_9 to maximize R_9). Subsequent elements are constraint values where **positive means satisfied**:

$$c_i \geq 0 \quad \Longleftrightarrow \quad \text{constraint } i \text{ is met}$$

For example, the CRI constraint returns CRI − min_cri, and the CCT constraint returns two values: CCT − (target − 50) and (target + 50) − CCT.

8 Interactive Use

When invoked with `-scm -scmfile photopic.scm` but *without* a `-run`, `-run-maxr9`, or `-run-drop` flag, `photopic` drops into an interactive MScheme read-eval-print loop (REPL). This is useful for exploration, debugging, and prototyping new objective functions.

```
$PHOTOPIC -scm -scmfile ../src/photopic.scm
```

8.1 Useful interactive commands

Setting up a problem

```
;; Create a parametric spectrum problem at 3000K with 5 parameters
(setup-problem!
  (ParametricSpectrum.MakeBlackbodyInWavelength 3000 l0 l1)
  5)
```

Inspecting the current spectrum

```
;; Compute full specs of the current spectrum
(calc-specs w)
;; => (cri-ra worst-ri efficacy (cct duv) (R1..R14) ...)

;; Get just the efficacy
(total-lumens-per-watt w)
```

Running one optimization pass

```
;; Run COBYLA with rhobeg=2 using the efficacy target
(run 2 specs->target)

;; Subdivide and run again at finer resolution
(subdivide-problem!)
(run 1 specs->target)
```

Evaluating a specific spectrum

```
;; CRI of a 4000K blackbody
(calc-cri (make-Bl 4000))

;; Efficacy of a fluorescent illuminant
(total-lumens-per-watt (FL 4))
```

Plotting

```
;; Write the current optimized spectrum to a gnuplot-compatible file
(plot (normalize-spectrum w) l0 l1 "my_spectrum.dat" 391)

;; Write the 14 TCS reflectance spectra
(plot-the-samples)
```

Modifying optimization parameters

```
;; Change target CCT
(set! *target-cct* 4000)

;; Change minimum CRI
(set! *min-cri-ra* 90)

;; Change minimum R9
(set! *min-r9* 50)

;; Change minimum efficacy (for -run-maxr9 mode)
(set! *min-efficacy* 350)
```

Reloading after edits

```
;; Reload photopic.scm after editing it
(reload)
```

9 Customization

9.1 Writing new objective functions

The optimizer calls a *spec-evaluator* function that takes the output of `calc-specs` and returns a vector for COBYLA. The existing evaluators follow this pattern:

```
(define (specs->my-target specs)
  (let ((lpm    (caddr specs))        ;; efficacy (lm/W)
        (r9     (nth (car (cddddr specs)) 8))  ;; R9
        (cri    (car specs))          ;; CRI (Ra)
        (crmin  (cadr specs))         ;; worst Ri (i in 1..8)
        (cct    (caar (cdddr specs))) ;; CCT (K)
        (Duv    (cadar (cdddr specs)));; Duv
        )
    (list <objective>        ;; minimize this (negate to maximize)
          <constraint-1>     ;; positive = satisfied
          <constraint-2>
          ...
          )))
```

The return value is a list whose first element is the objective to minimize and whose remaining elements are constraint values (positive means feasible). Update `*num-constraints*` if you change the number of constraints from the default 6.

9.2 What `calc-specs` returns

The `calc-specs` function evaluates a spectrum and returns a list with the following structure:

```
(cri-ra              ;; (car specs)      -- CRI average R1..R8
 worst-ri            ;; (cadr specs)     -- min of R1..R8
 efficacy            ;; (caddr specs)    -- lm/W
 ((cct duv)          ;; (cadddr specs)   -- CCT and Duv
  (R1 R2 ... R14))   ;; individual Ri values
 cri-14              ;; average of all 14 Ri
```

```
    worst-14            ;; min of all 14 Ri
    sel-cri             ;; CRI over selected subset
    sel-worst           ;; worst over selected subset
    worst-axis)         ;; index of worst TCS axis
```

9.3 Accessing individual fields

```
;; Given: (define s (calc-specs w))
(car s)                          ;; CRI (Ra)
(cadr s)                         ;; worst Ri
(caddr s)                        ;; efficacy
(caar (cdddr s))                 ;; CCT
(cadar (cdddr s))                ;; Duv
(nth (car (cddddr s)) 8)         ;; R9 (9th of 14, 0-indexed)
(nth (car (cddddr s)) 0)         ;; R1
```

9.4 Example: maximize efficacy subject to $R_9 \geq 50$

```
(define (specs->eff-r9floor specs)
  (let ((lpm  (caddr specs))
        (r9   (nth (car (cddddr specs)) 8))
        (cri  (car specs))
        (cct  (caar (cdddr specs)))
        (Duv  (cadar (cdddr specs))))
    (list (- lpm)                        ;; maximize efficacy
          (- cri 80)                     ;; CRI >= 80
          (- r9 50)                      ;; R9  >= 50
          (- cct (- *target-cct* 50))    ;; CCT in range
          (- (+ *target-cct* 50) cct)
          (* 1000 (- 0.012 Duv)))))      ;; Duv limit

;; Run it:
(set! *num-constraints* 5)
(run-example-iters! 2700 80 50 7 specs->eff-r9floor "_custom")
```

10 Reference

10.1 Global variables

Variable	Default	Purpose
`*target-cct*`	2700	Target correlated color temperature (K)
`*min-cri-ra*`	82	Minimum CRI (Ra) constraint
`*min-r9*`	-100	Minimum R_9 constraint
`*min-efficacy*`	300	Minimum efficacy (lm/W, for `-run-maxr9`)
`*num-constraints*`	6	Number of COBYLA constraints
`l0`	380×10^{-9}	Blue limit of visible spectrum (m)
`l1`	770×10^{-9}	Red limit of visible spectrum (m)

10.2 Key source files

File	Contents
`src/photopic.scm`	Main optimization logic (Scheme)
`src/Main.m3`	Program entry point; Scheme REPL setup
`src/ParametricSpectrum.i3`	Parametric spectrum interface
`src/ParametricSpectrum.m3`	Parametric spectrum implementation
`src/CieSpectrum.i3`	Photopic luminous efficiency data
`src/CieXyz.i3`	CIE $\bar{x}\bar{y}\bar{z}$ color matching functions
`src/Tcs.i3`	Test color sample reflectance spectra (1–14)
`src/TempUv.m3`	Temperature-to-uv lookup table
`src/Blackbody.m3`	Planck blackbody radiance
`src/m3makefile`	Build dependencies and Scheme stub generation

10.3 Physical constants

Symbol	Value	Defined as
c	299 792 458 m/s	Speed of light
h	$6.626\,070\,15 \times 10^{-34}$ J s	Planck's constant
k	$1.380\,649 \times 10^{-23}$ J/K	Boltzmann's constant