

# A Distributed, Non-Oscillatory Ideal Magnetohydrodynamics Framework



Neil Baker<sup>1</sup>, C. Michael Haynes<sup>2</sup>, A. Corinne Hill<sup>3</sup>, Eden Schapera<sup>1</sup>, Kenneth Thompson<sup>3</sup>

<sup>1</sup>School of Physics, Georgia Institute of Technology, Atlanta, GA, USA

<sup>2</sup>School of Earth and Atmospheric Sciences, Georgia Institute of Technology, Atlanta, GA, USA

<sup>3</sup>George W. Woodruff School of Mechanical Engineering: Nuclear and Radiological Engineering, Georgia Institute of Technology, Atlanta, GA, USA

## Introduction

**Magnetohydrodynamics** (MHD) is a mathematical framework that predicts the behavior of plasmas within certain physical limits. Our goal was to build a **one-dimensional MHD solver** based on the work of Balbas, et al (2004). The **computational significance** of Balbas's model is that it minimizes numerical diffusion and **without** relying on **Jacobian matrices**, thanks to a **staggered, predictor central differencing scheme**. We validate the model's accuracy by verifying our results against prior work and have gained significant physical insight into MHD wave propagation and confinement.

### Scientific Questions:

- How does plasma behave in a quasi-1D Slow Shock? (Falle et al., 1998)
- How are slow shock plasma dynamics modified for a fast Shock Tube? (Brio & Wu, 1988)
- How do rarefaction waves propagate in a MHD plasma? (e.g., Falle et al., 1998)
- What is the mechanism for plasma confinement in the Tokamak reactor torus? (e.g., Chance et al., 1982)

## Model

Our solver tracks the evolution of the following variables: **density**, **velocity**, **magnetic field**, and **energy**. We update the values of these quantities on the staggered mesh according to the following equation:

$$\bar{Z}_{j+\frac{1}{2}}^{n+1} = \frac{1}{\Delta x} \int_{I_{j+\frac{1}{2}}} Z(x, t_n) dx - \frac{1}{\Delta x} \left[ \int_{t^n}^{t^{n+1}} f(Z(x_{j+1}, t)) dt - \int_{t^n}^{t^{n+1}} f(Z(x_j, t)) dt \right]$$

Key features of our code include:

- The **MinMod** function, which selects the minimum choice from centered, upwind and downwind methods of computing derivatives to ensure stability. MinMod relies on a parameter  $\alpha$ , which we vary (see right) to investigate its influence on the propagation of physical quantities


$$\text{MinMod}(a, b, c) = \text{sign}(a) \min(|a|, |b|, |c|) \quad w'_j = \text{MinMod}(zA_+ \bar{w}_j, A_0 \bar{w}_j, zA_- \bar{w}_j), \quad 1 \leq \alpha < 4.$$

- A single array object containing quantities of all variables on *both meshes* (staggered and un-staggered) over the whole domain
- Using the fluxes of quantities at the *gridpoints*, a ( $n^{\text{th}}$ -order) polynomial is used to reconstruct the values of the quantities at the *midpoints* (i.e., on the staggered grid)
- An **Animate** function that allows us to post-process the output, generating plots for a variety of test cases
- Integration with joblib's Parallel library, drastically decreasing runtime

## Validation: Sod Shock Tube

A **shock tube** is the name for a class of systems in which a sharp change in the value of one of the parameters generates a force which drives evolution in a fluid. The **Sod Shock Tube** is such a system in which the magnetic field is zero, i.e., we are treating the plasma as a **hydrodynamic (unmagnetized) fluid**.

In our setup, the initial density jumps sharply, and this pressure gradient drives flow. This shock tube a helpful in validating the model, as it relies on simple initial conditions produces a variety of features.



## Other Test Cases

### The Slow Shock Wave

The **slow shock wave**: a propagating surface across which all physical parameters jump- the shock front converts kinetic energy into thermal energy, generating entropy  
Sharp gradients are slow to propagate outward => this specific shock causes the model to diverge, no matter the value of the stability parameter  $\alpha$ .

Left State ( $x < 0$ ):


$$\rho_L = 1.386, p_L = 1.769, \vec{u}_L = (0.269, 1.0, 0.0), \vec{B}_L = (1.0, 1.0, 0.0)$$

Right State ( $x \geq 0$ ):

$$\rho_R = 1.0, p_R = 1.0, \vec{u}_R = (0.0, 0.0, 0.0), \vec{B}_R = (1.0, 1.0, 0.0)$$

Two solutions for future consideration are:

- Introducing an adaptive timestep
- A second-order polynomial reconstruction



### The Rarefaction Wave


The **Rarefaction Wave**: the progression of particles being accelerated away from a compressed/shocked zone  
Propagates *away* from the direction of the acceleration of the particles  
Unlike shocks: wave mode disperses over space & time

Left State ( $x < 0$ ):

$$\rho_L = 1.0, p_L = 2.0, \vec{u}_L = (0.0, 0.0, 0.0), \vec{B}_L = (1.0, 0.0, 0.0)$$

Right State ( $x \geq 0$ ):

$$\rho_R = 0.2, p_R = 0.1368, \vec{u}_R = (1.186, 2.967, 0.0), \vec{B}_R = (1.0, 1.6405, 0.0)$$



## Alpha – Time Evolution Study

### Brio-Wu Shock Tube


The Brio & Wu shock tube initializes the system in the same state as in the sod shock tube, only this time the magnetic field is nonzero. We test the evolution for many  $\alpha$  values, demonstrating how lower values increase stability.

Left State ( $x < 0$ ):

$$\rho_L = 1.0, p_L = 1.0, \vec{u}_L = (0.0, 0.0, 0.0), \vec{B}_L = (0.75, 1.0, 0.0)$$

Right State ( $x \geq 0$ ):

$$\rho_R = 0.125, p_R = 0.1, \vec{u}_R = (0.0, 0.0, 0.0), \vec{B}_R = (0.75, -1.0, 0.0)$$



## Future Work

In addition to the those presented, we also have promising results for a comparison to another Riemann problem (Dai & Woodward, 1998). Our next task from the proposed work involves applying this MHD model to investigate plasma dynamics in a Tokamak nuclear reactor. Other improvements include:

- Experimenting with different types of boundary conditions
- Addressing numerical diffusion near discontinuities
- Extending the model to higher dimensions

## References

- Balbas, J., Tadmor, E., & Wu, C.-C. (2004, November). Non-oscillatory central schemes for one- and two-dimensional MHD equations: I. Journal of Computational Physics, 201 (1), 261-285. doi: 10.1016/j.jcp.2004.05.020
- Brio, M., & Wu, C. (1988). An upwind differencing scheme for the equations of ideal magnetohydrodynamics. Journal of Computational Physics, 75 (2), 400-422. Retrieved from https://www.sciencedirect.com/science/article/pii/0021999188901209 doi:https://doi.org/10.1016/0021-9991(88)90120-9
- Chance, M., Furth, H., Glasser, A., & Seibel, H. (1982, feb). Ideal- and resistive-mhd stability of one-dimensional tokamak equilibria. Nuclear Fusion, 22 (2), 187. Retrieved from https://dx.doi.org/10.1088/0029-551522/001 doi: 10.1088/0029-551522/001
- Falle, S. A. E. G., Komissarov, S. S., & Joarder, P. (1998, 06). A multidimensional upwind scheme for magnetohydrodynamics. Monthly Notices of the Royal Astronomical Society, 297 (1), 265-277. Retrieved from https://doi.org/10.1046/j.1365-8711.1998.01506.x doi: 10.1046/j.1365-8711.1998.01506.x
- Nakazawa, S., Nakajima, N., Okamoto, M., & Ohyabu, N. (2000, April). One-dimensional simulation stability of detached plasma in a tokamak divertor. Plasma Physics and Controlled Fusion, 42 (4), 401-413. doi: 10.1088/0741-333542/4/303