

1. DocumentSetADO/DocumentSetXML	2
2. ChargesGetADO / ChargesGetXML	3
3. ChargesSetADO / ChargesSetXML	4
4. ChargesDebitsLinkGetADO/ChargesDebitsLinkGetXML	5
5. ChargesDebitsLinkSetADO/ChargesDebitsLinkSetXML	6
6. Charges Data Table	7
7. Charges Debits Link Data Table	8
8. Client Documents Data Table	9
9. Errors Data Table	10
10. META_INFO Data Table	11

DocumentSetADO/DocumentSetXML

<https://websvc.globalclientsolutions.com/v3.0/webservices.asmx?op=DocumentSetADO/https://websvc.globalclientsolutions.com/v3.0/webservices.asmx?op=DocumentSetXML>

The **DocumentSet** Web Service returns the **ClientDocumentsWSDS** DataSet containing **Client Documents Data Table**, **Errors Data Table** and **META_INFORMATION Data Table**. It provides the ability to upload documents to the consumer's Global account. This step is not required when creating a consumer, but it is recommended since some documents are required for validation and completeness.

These are the parameters available:

Method Parameters				
Parameter	Description	Field Type	Required	Max Length
<i>userName</i>	User name	String	Y	20
<i>password</i>	Password associated with user name	String	Y	20
<i>accountId</i>	16-digit Global account number for consumer	String	N	16
<i>docType</i>	Type of Document	String	N	8
<i>documentName*</i>	Name of Document (including extension)	String	Y	255
<i>document</i>	Document to be uploaded	Base64Binary	Y	N/A

***Note:** documentName requires an extension (ex: Client Agreement.pdf).

ChargesGetADO / ChargesGetXML

<https://websvc.globalclientsolutions.com/v3.0/webservices.asmx?op=ChargesGetADO>/<https://websvc.globalclientsolutions.com/v3.0/webservices.asmx?op=ChargesGetXML>

The **ChargesGet** Web Service returns the **ChargesWSDS** DataSet containing [Charges Data Table](#), [Errors Data Table](#), and [META_INFO Data Table](#), and allows DSPs to separate Optional Product Charges from other program transactions.

Note: This call requires configuration for data to be available. For setup, please email integrationsupport@ghllc.com.

These are the parameters available:

Method Parameters				
Parameter	Description	Field Type	Required	Max Length
<i>userName</i>	User name	String	Y	20
<i>password</i>	Password associated with user name	String	Y	20
<i>chargeID</i>	Unique Identifier for charge	Decimal	N	16
<i>accountID</i>	16-digit Global account number for consumer	String	N	16
<i>transactionType</i>	How transaction was executed-code	String	N	3
<i>effectiveDateGte</i>	> or = date charge will be effective	DateTime	N	8
<i>effectiveDateLte</i>	< or = date charge will be effective	DateTime	N	8
<i>amountGte</i>	> or = the charge amount	Decimal	N	9
<i>amountLte</i>	< or = the charge amount	Decimal	N	9
<i>drcTransactionId</i>	Identifier DSP gives charge	String	N	20
<i>activeFlag</i>	Indicates if charge record is active	String	N	1
<i>status</i>	Status of charge	String	N	20
<i>creationDateGte</i>	> or = date record was added to database	DateTime	N	8
<i>creationDateLte</i>	< or = date record was added to database	DateTime	N	8
<i>modifiedDateGte</i>	> or = date record was modified	DateTime	N	8
<i>modifiedDateLte</i>	< or = date record was modified	DateTime	N	8
<i>modifiedBy</i>	Identifies who last modified record	String	N	20
<i>pageSize</i> [†]	Number of rows on each page	Integer	N	3
<i>pageNumber</i> [†]	The page to return desired rows (leave null to return <i>pageCount</i> and <i>rowCount</i>)	Integer	N	3
<i>rowCount</i> [†]	Total count of rows for specified parameters	Integer	N	3
<i>pageCount</i> [†]	Total count of pages for specified parameters	Integer	N	3
[†] Note for Java Developers: <i>pageSize</i> , <i>pageCount</i> , <i>pageNumber</i> , and <i>rowCount</i> are nullable "int" data types and are not supported by Java. Refer to Java section for additional information.				

ChargesSetADO / ChargesSetXML

<https://websvc.globalclientsolutions.com/v3.0/webservices.asmx?op=ChargesSetADO>/<https://websvc.globalclientsolutions.com/v3.0/webservices.asmx?op=ChargesSetXML>

The **ChargesSet** Web Service returns the **ChargesWSDS** DataSet containing [Charges Data Table](#), [Errors Data Table](#), and [META_INFO Data Table](#), and allows DSPs to separate Optional Product Charges from other program transactions.

Note: This call requires configuration for data to be available. For setup, please email integrationsupport@ghllc.com.

These are the parameters available:

Method Parameters				
Parameter	Description	Field Type	Required	Max Length
<i>userName</i>	User name	String	Y	20
<i>password</i>	Password associated with user name	String	Y	20
<i>chargesDataADO/chargesNodeIn (XML)</i>	See Charges Data Table	Dataset	Y	N/A

Values that can be returned for the Active Flag field:

Code	Description
Y	Yes (Active)
N	No (Inactive)

Values that can be returned for the Status field:

Description
Queued (Processing)
Exception (Not approved)
Approved

ChargesDebitsLinkGetADO/ChargesDebitsLinkGetXML

<https://websvc.globalclientsolutions.com/v3.0/webservices.aspx?op=ChargesDebitsLinkGetADO/https://websvc.globalclientsolutions.com/v3.0/webservices.aspx?op=ChargesDebitsLinkGetXML>

The **ChargesDebitsLinkGet** Web Service method returns the **ChargesDebitsLinkGetWSDS** DataSet containing **Charges Debits Link** , **Errors** and **Meta Info** Data Tables.

These are the parameters available:

Parameter	Description	Field Type	Required	Max Length
<i>userName</i>	Username	String	Y	20
<i>password</i>	Password associated with username	String	Y	20
<i>linkId</i>	Unique identifier for settlement link	String	N	22
<i>chargeId</i>	Identifies the Charge being linked	String	N	22
<i>debitId</i>	Identifies the Debit being linked	String	N	22
<i>createdBy</i>	Identifies who created the record	String	N	20
<i>createdDateGte</i>	> or = date record was added to database	DateTime	N	25
<i>createdDateLte</i>	< or = date record was added to database	DateTime	N	25
<i>modifiedBy</i>	Identifies who last modified record	String	N	20
<i>modifiedDateGte</i>	> or = date record was modified	DateTime	N	25
<i>modifiedDateLte</i>	< or = to date record was modified	DateTime	N	25
<i>pageSize</i> [†]	Number of rows on each page	Integer	N	3
<i>pageNumber</i> [†]	The page to return desired rows (leave null to return <i>pageCount</i> and <i>rowCount</i>)	Integer	N	3
<i>rowCount</i> [†]	Total count of rows for specified parameters	Integer	N	3
<i>pageCount</i> [†]	Total count of pages for specified parameters	Integer	N	3

[†]Note for Java Developers: *pageSize*, *pageCount*, *pageNumber*, and *rowCount* are nullable "int" data types and are not supported by Java. Refer to [Java](#) section for additional information.

ChargesDebitsLinkSetADO/ChargesDebitsLinkSetXML

<https://websvc.globalclientsolutions.com/v3.0/webservices.asmx?op=ChargesDebitsLinkSetADO>/<https://websvc.globalclientsolutions.com/v3.0/webservices.asmx?op=ChargesDebitsLinkSetXML>

The **ChargesDebitsLinkSet** Web Service method returns the **ChargesDebitsLinkSetWSDS** DataSet containing **Charges Debits Link, Errors** and **Meta Info** Data Tables.

These are the parameters available:

Method Parameters				
Parameter	Description	Field Type	Required	Max Length
<i>Username</i>	Username	String	Y	20
<i>Password</i>	Password associated with username	String	Y	20
ChargesDebitsLinkSetADO(ADO)	See Charges Debits Link Data Table	DataSet	Y	N/A
ChargesDebitsLinkSetNodeIn(XML)				

Charges Data Table

Part of the **ChargesWSDS** DataSet and used in the [ChargesGet](#) and [ChargesSet](#) operations.

Charges Data Table				
Field Name	Description	Field Type	Permissions	Max Length
<u>CHARGE_ID</u>	Unique identifier for charge	String	Read	22
<u>ACCOUNT_ID</u>	Consumer's 16-digit Global account number	String	Read/Write	16
<u>TRANSACTION_CLASS</u>	Charge – code	String	Read	1
<u>TRANSACTION_TYPE</u>	Type of charge	String	Read/Write	1
<u>EFFECTIVE_DATE</u>	Date charge is to become effective	DateTime	Read/Write	10
<u>AMOUNT</u>	Amount of charge	Decimal	Read/Write	9
<u>DRC_TRANSACTION_ID</u>	Company's identifier for this charge	String	Read/Write	20
<u>ACTIVE_FLAG</u>	Indicates whether charge is active	String	Read/Write	1
<u>STATUS</u>	Status of charge	String	Read	20
<u>CREATED_BY</u>	Identifies who created the record	String	Read/Write	20
<u>CREATED_DATE</u>	Date charge was added to database	DateTime	Read	10
<u>MODIFIED_BY</u>	Identifies who last modified the record	String	Read/Write	20
<u>MODIFIED_DATE</u>	Date charge record was last modified	DateTime	Read	10

Charges Debits Link Data Table

Part of the **ChargesDebitsLinkWSDS** DataSet and used in the [ChargesDebitsLinkGet](#), and [ChargesDebitsLinkSet](#), operations.

Charges Debits Link Data Table				
Field Name	Description	Field Type	Permissions	Max Length
LINK_ID	Unique Identifier for link	String	Read	22
CHARGE_ID	Identifies the Charge being linked	String	Read	22
DEBIT_ID	Identifies the Draft being linked	String	Read	22
CREATED_BY	Identifies who created the record	String	Read	20
CREATED_DATE	Date debt was added to database	DateTime	Read	25
MODIFIED_BY	Identifies who last modified record	String	Read	40
MODIFIED_DATE	Date debt record was modified	DateTime	Read	25

Client Documents Data Table

Part of the **ClientDocumentsWSDS** DataSet and used in the [DocumentListGet](#) and [DocumentSet](#) operations.

Client Documents Data Table				
Field Name	Description	Field Type	Permissions	Max Length
<u>DOC_TYPE</u>	Type of document	String	Read	8
<u>DOC_NAME</u>	Name of the document	String	Read/Write	255
<u>DOC_STATUS</u>	Status of the document	String	Read	8
<u>ACCOUNT_ID</u>	16-digit Global account number for consumer	String	Write	16
<u>CREATED_DATE</u>	Date document was added to database	DateTime	Read	25
<u>MODIFIED_DATE</u>	Date document was last modified	DateTime	Read	25
<u>TAGS</u>	Concatenated list of Tag Name & Tag Value associated with Document, separated by commas	String	Read	200
<u>LAST_VIEWED_DATE</u>	Date document was last viewed	DateTime	Read	25

Errors Data Table

The table layout below applies to all DataSets that contain an **Errors** Data Table. This table will be empty if there are no errors to report.

Errors Data Table			
Field Name	Description	Field Type	Max Length
<u>ERROR_ID</u>	Identifier for error	Decimal	28
<u>TABLE_NAME</u>	Identifier of data table that error applies to	String	75
<u>TABLE_ID</u>	Identifier of data row that error applies to	String	10
<u>ROW_ID</u>	Row number of error	Decimal	10
<u>COLUMN_ID</u>	Field name of error	String	5
<u>ERROR_TYPE</u>	E-Error or W-Warning	String	1
<u>ERROR_CODE</u>	Code for error type	String	20
<u>ERROR_TEXT</u>	Text printed for error	String	4,000

META_INFO Data Table

The META_INFO data table returns information such as *pageSize* and *pageCount*. This can provide an operation for automating page generation.

The table layout below applies to all DataSets that contain a **META_INFO** Data Table.

META_INFO Data Table			
Field Name	Description	Field Type	Max Length
<u>INFO_CLASS</u>	Class of the META_INFO entry	String	75
<u>INFO_TYPE</u>	Type of the META_INFO entry	String	75
<u>INFO_CODE</u>	Code of the META_INFO entry	String	75
<u>VALUE</u>	Value of the META_INFO entry	String	4,000

NOTE: The RequestID is sent back in the **META_INFO** table. This RequestID is helpful when troubleshooting an issue with Global.