Introduction to Compiler Construction

or

How to Construct a Self-compiling Compiler in One Semester

Christoph Kirsch

University of Salzburg

Based on Niklaus Wirth's "Compiler Construction", A-W 1996

---

what is a compiler?

a program that translates a program written in a programming language P (source code) into a program written in a machine language M (machine code)

source code → | compiler | → machine code

the compiler is self-compiling if it is written in P

P: structured, imperative language (C, Java, Pascal...); we use C
M: unstructured machine instructions (x86, ARM...); we use (virtualized) RISC

the compiler and the semantics of M determine the semantics of P

writing a compiler is difficult:
1956 Fortran compiler took 18 person-years!

We will do it in one semester!

Mind the Gap!

P (source code)

determines

semantical gap

compiler

precise definitions

M (machine code)

determines

interpreter   CPU

Java!

P — source code

compiler — javac

M_{JVM} — bytecode

semantical gap

interpreter — JVM

compiler — gcc

M_{CPU} — machine code

interpreter — CPU

What Do We Do?

P — source code

compiler — your compiler (yc)

M_{RISC} — RISC code

semantical gap

interpreter — your emulator (ye)

written in C or any other language

check out qemu.org

compiler — gcc

M_{CPU} — machine code

interpreter — CPU

Separate Compilation

P — source code (.c)

partial
description of
a program,
refers to items
(variables, code, etc.)
defined elsewhere

compiler — gcc

M — object code (.o)

object code:
   machine code + symbolic references (named)

M — .o, ..., .o

(static)
linker:

resolves
symbolic references
into
direct references

linker — gcc

M — .o

not
necessarily
executable

executable:
   machine code without symbolic references
   (only direct references, i.e., addresses)

What Do We Really Do?

P — source code (.y)

single pass!

semantical gap

compiler — your compiler (yc)

M_{RISC} — RISC code (.yo)

M_{RISC} → linker — your linker (yl)

M_{RISC} — RISC code (.yo)

if .yo is executable →

interpreter — your emulator (ye)

— specify
— implement

interpreter — CPU

Intermediate Summary:

Specify:

Source code: .y
Object code: .yo

Implement:

your compiler: yc (in .y for self compilation)
your linker: yl (for separate compilation)
your emulator: ye (for controlling the gap!)

Motivation:

Self Compilation:

your compiler needs to be able to compile everything you use in
the implementation of the compiler

this will teach you the semantics of programming languages
in full detail and thus make you a better programmer!

separate compilation:

modularity and thus scalability

semantical gap:

understanding the trade-off between compilation and
interpretation

Covered Topics

constants:
- natural numbers
- strings (arrays of characters)

data:
- integer ⎫
- character ⎬ basic
- boolean ⎭
- record ⎫
- array ⎬ composite
- type-safe assignment (imperative language!)
- type-safe arithmetic and boolean expressions

no pointers!
just references
~> no dot,
just ->, []

control:
- if then else
- while loop

possibly nested!

structure:
- procedure with arguments and return value
- call by value (for basic types)
- call by reference (for arrays, records)
- local variables

- module that may import procedures, variables, and constants from other modules

no tools other than a compiler!

Systems Engineering

- bootstrapping:
  - use language for which there is a compiler
  - identify a subset that covers all topics
  - make subset "easily" parseable through grammar engineering and preprocessing (as last resort)
  - implement compiler in that subset

	compiler	output
time	compilation performance	execution performance
space	code size data size	code size data size

- optimizations:
  - only basics are covered, e.g. constant folding!
  - advanced topics if time permits

- error handling:
  - report as many actual errors as possible
  - always terminate, never crash

Advanced Topics

not covered:

— multi-pass compilation:
    ⤳ creates internal representation (IR)

— cross compilation:
    ⤳ generated output targets other machine than the one on which the compiler executes

— incremental compilation:

⤳ only compile local change δ_P, only considering local depend ency context γ, only generating δ_M

⤳ compilation complexity independent of program size!

— just-in-time (JIT) compilation

we only do ahead-of-time (AOT) compilation

Just-in-Time (JIT) Compilation

P — source code

compiler — javac

M_{JVM} — bytecode

semantical gap

incremental!

JIT

compiler

interpreter

Java! metacircular

M_{CPU}

compiler — gcc

M_{CPU}

bootstrapping C!

semantical gap

bytecode 2 machine code

interpreter

CPU

Summary:

- we construct:
  - a self-compiling, single-pass compiler
  - a static linker
  - a RISC emulator

- understand covered topics
- systems vs. software engineering

  performance   reuse

- more things to do now:
  - play with existing systems (gcc, javac, qemu, ...)
  - set up your development environment
  - read books, papers, articles on compilers!