

The Author
Li Mingming

The Small Book of

L^AT_EX

Introduction to L^AT_EX and
how to use to write articles and books

Sep 24, 2020

Dedication

This book is dedicated to summerize the knowledge I learned about \LaTeX .

Meanwhile, I record the experience of using \LaTeX to write article and books.

Contents

Dedication	iii
Contents	v
List of Tables	ix
List of Figures	xi
1 Environment	1
2 What is L ^A T _E X	3
2.1 What is L ^A T _E X	3
2.2 L ^A T _E X's Properties	3
2.3 Reason to Use It	4
3 L ^A T _E XBase	5
3.1 Hello World in L ^A T _E X	5
3.2 Document Structure	6
3.3 L ^A T _E XCommand	7
3.4 Comment	7
3.5 Create Your Own Commands	7
3.5.1 With No Arguments	7

3.5.2	With Arguments	7
3.5.3	With Optional Arguments	7
3.6	Breaking Lines	8
3.7	Breaking Pages	8
3.8	Get Help	8
4	Font	11
4.1	Shape	11
4.2	Family	13
4.3	Size	14
5	Box	15
6	Justification	17
7	Designing Pages	19
7.1	Defining the Overall Layout	19
7.2	Creating a Table of Contents	21
7.3	Designing Headers and Footers	21
8	Footnotes	23
9	Lists	25
9.1	Bulleted Lists	25
9.2	Numbered Lists	25
9.3	Definition Lists	26
10	Tables	29
11	Figure	31

12 Cross Referencing	33
13 Content	35
14 Math	37
14.1 Basic Formula	37
14.2 Expressions within Text	38
14.3 Displaying Formula	39
14.4 Numbering Equations	40
15 Larger Document	41
16 French	43
16.1 Phonetic Symbols	43

List of Tables

4.1	Font Command	11
4.2	Font Declaration	12
4.3	Font Emphasized	12
4.4	Font Family	13
4.5	Font Size	14
13.1	Content	35

List of Figures

3.1 Example	6
-----------------------	---

Chapter 1

Environment

The operating system is Ubuntu 20.04.1 LTS.

The text editor is Emacs.

The installation of Emacs is as follows:

```
1 sudo apt install emacs
```

The installation of LaTeX and some packages is as follows:

```
1 sudo apt install texlive-latex-base
2 sudo apt install texlive-xetex
3 sudo apt install texlive-full
```


Chapter 2

What is L^AT_EX

2.1 What is L^AT_EX

L^AT_EX is a document markup language.

2.2 L^AT_EX's Properties

1. L^AT_EX is portable in three ways:
 - (a) The source code is open.
 - (b) The implementation is in plain text.
 - (c) The output is in multiple format: PDF, DVI, PostScript, HTML.
2. Protect your work:
 - (a) compatibility (plain text)
 - (b) no viruses (plain text)

2.3 Reason to Use It

Because L^AT_EX is a markup language, you should learn it before you can use it. So why should you spend so much time to learn it while there is so much document creator like Word, Pages?

There are several reasons that push me to select it:

powerful: L^AT_EX provides powerful edit ability. You can almost get whatever you want to show, especially the mathematical equations. Other document editor is less powerful in equations editing.

easy to alter: Because L^AT_EX separates the format and the content, it is easy to do format alteration in the full document domain, for example change the style of the chapter.

one for all: Once you create your own template, it is easy to create a document with the template applied, saving so much time in format. The disadvantage is that you spend more time in the first time.

Chapter 3

LaTeX Base

3.1 Hello World in LaTeX

```
1 \documentclass[a4paper,11pt]{article} % specify the document
   class, different class for different purpose.
2 \begin{document}
3 \title{Example}
4 \author{Mike Chyson}
5 \date{Thu Jan 3 16:22:11 CST 2019}
6 \maketitle % make a title according to the title and author etc.
7 \section{What's this?}
8 This is simple document. It contains a title and a section with
   text.
9 \end{document}
```

The output is as follows:

Because the separation of the format and the content, you do not specify the font size, font color, font family and so on. Instead, you tell LaTeX it is a **title**, or **author** or **date** and so on. LaTeX formats them for you. As if there is a logical layer between the appearance




Figure 3.1: Example

and the content.

3.2 Document Structure

A *L*^AT_EX document doesn't stand alone — commonly the document is based on a versatile template. Such a fundamental template is called a class. It provides customizable features, usually built for a certain purpose.

This first part of the document is called the preamble of the document. This is where we choose the class, specify properties, and in general, make document-wide definitions.

The first line starts with `\documentclass`. This word begins with a backslash; such a word is called a **command**. We used commands to specify the class and to state document properties: `title` , `author` , and `date`.

```
preamble
body
```

3.3 **LaTeX** Command

```
1 \command
2 \command{argument}
3 \command[optional argument]{argument}
```

3.4 Comment

The percent sing(%) introduces a **comment**.

3.5 Create Your Own Commands

3.5.1 With No Arguments

```
1 \newcommand{\TUG}{TeX Users Group}
2 \TUG
```

3.5.2 With Arguments

```
1 \newcommand{\keyword}[1]{\textbf{#1}}
2 \keyword{declarations}
```

3.5.3 With Optional Arguments

```
1 \newcommand{\keyword2}[2][\bfseries]{\#1\#2}
2 \keyword2[\itshape]{declarations}
```

3.6 Breaking Lines

```
1  \\ % end a line
2  \newline % has the same effect with \\
3  \linebreak % tells LATEX to end the line but to keep the full
      justification
4  \\[3mm] % insert additional vertical space after the break
      depending on the value
5  \linebreak[4] % can be used to influence the line break slightly
      or strongly:
6  %% If number is 0, a line break is allowed, 1 means it's desired, 2
      and 3 mark more
7  %% insistent requests, and 4 will force it. The latter is the default
      behavior if no number
8  %% was given.
9  \nolinebreak
```

3.7 Breaking Pages

```
1  \pagebreak
2  \newpage
3  \nopagebreak
```

3.8 Get Help

Three ways to get help about the package:

- Use the `texdoc` command:

```
1 texdoc <package>
```

- Use the `kpsewhich` command:

```
1 kpsewhich <package>.sty
```

- Visit the website: <http://ctan.org/pkg>

Chapter 4

Font

4.1 Shape

Table 4.1: Font Command

Command	Explanation	Output
<code>\textbf</code>	bold font	Example
<code>\textit</code>	italic	<i>Example</i>
<code>\textsl</code>	slated	<i>Example</i>
<code>\textsc</code>	small caps	EXAMPLE
<code>\textup</code>		Example
<code>\textmd</code>	medium	Example
<code>\textnormal</code>		Example

Table 4.2: Font Declaration

Declaration	Explanation	Output
<code>\itshape</code>	italic	<i>Example</i>
<code>\bfseries</code>	bold font	Example
<code>\slshape</code>	slated	<i>Example</i>
<code>\scshape</code>	small caps	EXAMPLE
<code>\upshape</code>		Example
<code>\mdseries</code>	medium	Example
<code>\normalfont</code>		Example

Table 4.3: Font Emphasized

Command	Explanation	Output
<code>\emph</code>	emphasized	<i>Example</i>

4.2 Family

Table 4.4: Font Family

Command or Declariation	Explanation	Output
<code>\textsf</code>	sans-serif	Example
<code>\texttt</code>	typewriter	Example
<code>\textrm</code>	Roman	Example

4.3 Size

Table 4.5: Font Size

Command	Output
<code>\tiny</code>	Example
<code>\scriptsize</code>	Example
<code>\footnotesize</code>	Example
<code>\small</code>	Example
<code>\normalsize</code>	Example
<code>\large</code>	Example
<code>\Large</code>	Example
<code>\LARGE</code>	Example
<code>\huge</code>	Example
<code>\Huge</code>	Example

Chapter 5

Box

1 `\quad\parbox[b]{1.8cm}{this parbox is aligned at its bottom
line}`

this parbox
is aligned at
its bottom
line

1 `\quad\parbox{1.5cm}{center-aligned parbox}`

center-
aligned
parbox

1 `\quad\parbox[t]{2cm}{another parbox aligned at its top line}`

another par-
box aligned
at its top line

1 `\mbox{Hello World}`

Hello World

Chapter 6

Justification

```
1 \parbox{3cm}{\raggedright hello} % \raggedright
2 {\centering hello} % \centering
3 \begin{center} % environment
4   hello
5 \end{center}
```


Chapter 7

Designing Pages

7.1 Defining the Overall Layout

```
1 \usepackage[a4paper, inner=1.5cm, outer=3cm, top=2cm,  
   bottom=3cm, bindingoffset=1cm, landscape]{geometry}  
2 %% paper=name  
3 %% paperwidth=7in  
4 %% paperheight=10in  
5 %% papersize={7in,10in}  
6 %% landscape  
7 %% portrait  
8 %% textwidth=140mm  
9 %% textheight=180mm  
10 %% lines=25  
11 %% includedhead % cause the header of the page to be included  
   into the body area  
12 %% includefoot  
13 %% left=2cm  
14 %% right=2cm
```

```

15  %% bindingoffset % reserves space on the left margin (one—size),
    % respectively the inner margin (two—sided) for the binding
16
17  %% default margin ratio:
18  %% top:bottom = 2:3
19  %% left:right = 1:1 for one—side documents
20  %% inner:outer = 2:3 for two—side documents

```

```

1  \usepackage[onehalfspacing]{setspace}
2  %% singlespacing, onehalfspacing, doublespacing
3  %% \begin{spacing}{2.4}
4  %% This text is stretched by a factor of 2.4.
5  %% \end{spacing}

```

```

1  \documentclass[a4paper,12pt,twocolumn]{book} % the
    % document class book, suitable for book—like documents
2  %% book, report, article, slides, letter
3  %% oneside or twoside
4  %% openright or openany % only support book and report
5  %% titlepage or notitlepage
6  %% final or draft: If draft is set, then LaTeX will mark overfull
    % lines with a black box, which is helpful in reviewing and
    % improving the output.
7  %% openbib : When this option is set, a bibliography would be
    % formatted in open style instead of compressed style.
8  %% fleqn : Causes displayed formulas to be left—aligned.
9  %% leqno : For numbered displayed formulas, the number would
    % be put to the left side. The right side is the default.

```


7.2 Creating a Table of Contents

```
1 \tableofcontents
```

7.3 Designing Headers and Footers

```
1 \usepackage{fancyhdr}  
2 \fancyhf{}  
3 \fancyhead[LE]{\leftmark}  
4 \fancyhead[RO]{\nouppercase{\rightmark}}  
5 \fancyfoot[LE,RO]{\thepage}  
6 \pagestyle{fancy}
```


Chapter 8

Footnotes

```
1 \footnote{hello world}
2 \section[title without footnote]{This is a section\protect\
   footnote{section footnote}}
3
4 \footnote[number]{text}
5
6 \footnotemark[number] % produces a superscripted number in
   the text as a
7 % footnote mark. If the optional argument wasn't given, it's also
   stepping and using
8 % the internal footnote counter. No footnote will be generated.
9
10 \footnotetext[number]{text} % generates a footnote without
   putting a
11 % footnote mark into the text without stepping the internal
   footnote counter.
12
13 \footnoterule % used to alter the footnote line
14
```

```

15 \renewcommand{\footnoterule}{\noindent\smash{\rule[3pt]{\textwidth}{0.4pt}}}
16 % \rule[raising]{width}{height} draws a line, here 0.4 pt thick,
    and as wide as the text, raised a bit by 3 pt.
17 % \smash , let the line pretend to have a height and a depth of
    zero, so it's occupying no vertical space at all.

```

Example:

```

1 Hello World\footnote{hello world}

```

Hello World^a.

^ahello world

Chapter 9

Lists

9.1 Bulleted Lists

```
1 \begin{itemize}
2 \item geometry
3 \item amsmath
4 \end{itemize}
```

- geometry
- amsmath

9.2 Numbered Lists

```
1 \begin{enumerate}
2 \item geometry
3 \item amsmath
4 \end{enumerate}
```

1. geometry
2. amsmath

9.3 Definition Lists

```
1 \begin{description}
2 \item[paralist] provides compact lists and list versions that
3   can be used within paragraphs, helps to customize labels and
4   layout
5 \item[enumitem] gives control over labels and lengths
6   in all kind of lists
7 \item[mdwlist] is useful to customize description lists, it
8   even allows multi—line labels. It features compact lists and
9   the capability to suspend and resume.
10 \item[desclist] offers more flexibility in definition list
11 \item[multenum] produces vertical enumeration in multiple
12   columns
13 \end{description}
```

paralist provides compact lists and list versions that can be used within paragraphs, helps to customize labels and layout

enumitem gives control over labels and lengths in all kind of lists

mdwlist is useful to customize description lists, it even allows multi-line labels. It features compact lists and the capability to suspend and resume.

desclist offers more flexibility in definition list

multenum produces vertical enumeration in multiple columns

Chapter 10

Tables

```
1 \newcommand{\head}[1]{\textnormal{\textbf{#1}}}  
2 \begin{tabular}{ccc}  
3 \hline  
4 \head{Command} & \head{Declaration} & \head{Output} \\  
5 \hline  
6 \verb|\textrm| & \verb|\rmfamily| & \rmfamily Example text  
7 \\\br/>7 \verb|\textsf| & \verb|\sffamily| & \sffamily Example text \\  
8 \verb|\texttt| & \verb|\ttfamily| & \ttfamily Example text \\  
9 \hline  
10 \end{tabular}
```

Command	Declaration	Output
<code>\textrm</code>	<code>\rmfamily</code>	Example text
<code>\textsf</code>	<code>\sffamily</code>	Example text
<code>\texttt</code>	<code>\ttfamily</code>	Example text

```

1
2 \usepackage{booktabs} % toprule, midrule, bottomrule
3
4 \begin{tabular}{ccc}
5   \toprule[1.5pt] % British typesetters call a line a rule
6   \head{Command} & \head{Declaration}& \head{Output}\\
7   \midrule %
8   \verb|\textrm| & \verb|\rmfamily| & \rmfamily Example text
9   \\
10  \verb|\textsf| & \verb|\sffamily| & \sffamily Example text \\
11  \verb|\texttt| & \verb|\ttfamily| & \ttfamily Example text \\
12  \bottomrule[1.5pt] %
13 \end{tabular}

```

Command	Declaration	Output
<code>\textrm</code>	<code>\rmfamily</code>	Example text
<code>\textsf</code>	<code>\sffamily</code>	Example text
<code>\texttt</code>	<code>\ttfamily</code>	Example text

To avoid the table exceed out the page:

```

\resizebox{\textwidth}{!}{
  ...
}

```

Chapter 11

Figure

```
1 \usepackage{graphicx}
2 \begin{figure}
3   \centering
4   \includegraphics[width=0.8\textwidth]{zm.jpg} % include
5   picture
6 \end{figure}
```



Chapter 12

Cross Referencing

```
1 \label % mark the label
2 \ref % refer after marking
3 \pageref
4 % notice, typeset twice to produce the current reference
5
6 % If the \label command appeared in ordinary text, then the
   % current sectional unit,
7 % like the chapter or the section, would be assigned.
8 % If the \label would be placed within a numbered environment,
   % that environment
9 % would be assigned to the key.
10
11 \newcommand{\fullref}[1]{\ref{#1} on page~\pageref{#1}}
```

For example:

```
1 Hello World\label{hello-label}
2
3 Refer to \ref{hello-label}
```

Hello World

Refer to 12

Chapter 13

Content

Table 13.1: Content

Command	Level
<code>\part</code>	-1 (book and report class)
<code>\chapter</code>	0 (not available in article)
<code>\section</code>	1
<code>\subsection</code>	2
<code>\subsubsection</code>	3
<code>\paragraph</code>	4
<code>\subparagraph</code>	5

Chapter 14

Math

14.1 Basic Formula

```
1 \section*{Quadratic equations}
2 \begin{equation}
3 \label{quad}
4 ax^2 + bx + c = 0,
5 \end{equation}
6 where ( a, b ) and ( c ) are constants and ( a \neq 0 ),
7 has two solutions for the variable ( x ):
8 \begin{equation}
9 \label{root}
10 x_{1,2} = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}.
11 \end{equation}
12 If the \emph{discriminant} ( \Delta ) with
13 [ \Delta = b^2 - 4ac ]
14 is zero, then the equation ( \ref{quad} ) has a double solution:
15 ( \ref{root} ) becomes
16 [ x = - \frac{b}{2a} . ]
```

Quadratic equations

$$ax^2 + bx + c = 0, \quad (14.1)$$

where a, b and c are constants and $a \neq 0$, has two solutions for the variable x :

$$x_{1,2} = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}. \quad (14.2)$$

If the *discriminant* with

$$\Delta = b^2 - 4ac$$

is zero, then the equation (14.1) has a double solution: (14.2) becomes

$$x = -\frac{b}{2a}.$$

14.2 Expressions within Text

LaTeX provides the math environment in-text formulas:

```
1 \begin{math}
2   expression
3 \end{math}
```

LaTeX offers an alias that's doing the same:

```
1 \(\ expression \)
```

A third way is by using a shortcut, coming from TeX:

```
1 $expression$
```

For example:

```
1 This is an equation: $x^2 + x = 10$
```

This is an equation: $x^2 + x = 10$

14.3 Displaying Formula

```
1 \begin{displaymath}
2   expression % displayed formula, centered
3 \end{displaymath}
```

There are shortcuts:

```
1 \[
2   expression
3 \]
```

```
1 $$
2   expression
3 $$
```

For example:

```

1 \begin{displaymath}
2   x^2 + x = 10
3 \end{displaymath}

```

$$x^2 + x = 10$$

14.4 Numbering Equations

```

1 \begin{equation}
2   \label{newton}
3   F = ma^2
4 \end{equation}
5 Newton's law: \eqref{newton}.

```

$$F = ma^2 \tag{14.3}$$

Newton's law: (14.3).

Chapter 15

Larger Document

If you are writing a book, it is better to split the book into several parts.

For example:

```
\documentclass{book}
\input{preamble}

\hypersetup{pdfauthor={Li Mingming},
  pdftitle={The Big Book of \LaTeX},
  pdfsubject={Introduction to \LaTeX and how to use it},
  pdfkeywords={latex}}

\begin{document}

\frontmatter
\include{title}
\include{dedication}
\tableofcontents
\listoftables
\listoffigures
```

```
\mainmatter
\include{environment}
\include{what-is-latex}
\include{latex-base}
\include{font}
\include{box}
\include{justification}
\include{designing-pages}
\include{footnote}
\include{list}
\include{table}
\include{figure}
\include{cross-referencing}
\include{content}
\include{math}
\include{large-document}
\backmatter
\bibliographystyle{plainnat}
\bibliography{tex}

\end{document}
```

Chapter 16

French

16.1 Phonetic Symbols

Use **TIPA** package to input phonetic symbols.

```
1 \usepackage{tipa}
2 \usepackage{tipx}
```

```
1 Consonants: \\
2 \textipa{b d f k l m n p s t v z g K S Z dZ tS N \textltailn}
3
4 Semivowels: \\
5 \textipa{j w 4}
6
7 Oral vowels: \\
8 \textipa{a e i o u y \textcolor{blue}{o} \textcolor{blue}{oe} \textcolor{blue}{O} @ E}
9
10 Nasal vowels: \\
11 \textipa{\textcolor{blue}{~}a \textcolor{blue}{~}o \textcolor{blue}{~}e}
```

Consonants:

b d f k l m n p s t v z ʁ ʒ dʒ tʃ ɲ ɲ

Semivowels:

j w ɥ

Oral vowels:

a e i o u y ø œ ɔ ə ɛ

Nasal vowels:

ã õ ĕ