

# CSC 211: Computer Programming

## Introducing loops (for)

Michael Conti

Department of Computer Science and Statistics  
University of Rhode Island

Summer 2025



## Administrative Announcements

- Exam#01 ~ Thursday 10/10
  - ✓ Same time / place as lecture
  - ✓ One 11x8 notes sheet
  - ✓ Calculator allowed
- A01 Due 09/29 (only 20 submissions?)
- MC02 Due 09/29


2

## Administrative Announcements

- Exam#01 ~ Tuesday 02/21
  - ✓ Same time / place as lecture
  - ✓ One 11x8 notes sheet
  - ✓ Calculator allowed
- A01 Due 02/19
- MC03 due 02/21

3

## Basic building blocks



<https://introcs.cs.princeton.edu/java/lectures/>

4

## Flowchart of if statements




Figure: Flowchart of if Statement

```

// ...
// statements above
// ...

if (test_expression) {
    // body of if
}

// ...
// statements below
// ...
  
```

## Flowchart of if statements

```

// ...
// statements above
// ...

if (test_expression) {
    // body of if
} else {
    // body of else
}

// ...
// statements below
// ...
  
```





Figure: Flowchart of if...else Statement


## if statement examples

Example: `if (x < 0) x = -x;`



## if statement examples

Example: `if (x > y) max = x;`  
`else max = y;`



## The increment/decrement operators

- Increment (**++**) and decrement (**--**) are **unary** operators that add or subtract one, to or from their operand, respectively
  - pre-increment** and **pre-decrement** operators increment (or decrement) their operand by 1, and the value of the expression is the resulting incremented (or decremented) value
  - post-increment** and **post-decrement** operators increase (or decrease) the value of their operand by 1, but the value of the expression is the operand's original value prior to the increment (or decrement) operation

from: wikipedia

9

## The increment/decrement operators

- Example:

```
int a = 5;
```

```
std::cout << 5 + ++a
```

v.s

```
int a = 5;
```

```
std::cout << 5 + a++;
```

10

## Trace the code

```
int x;  
int y;  
x = 1;  
y = ++x;  
// Checkpoint a (status of x and y?)  
y = x++;  
// Checkpoint b (status of x and y?)  
x = 5;  
y = x--;  
// Checkpoint c (status of x and y?)  
y = --x;  
// Checkpoint d (status of x and y?)
```

from: wikipedia

11

the for loop

## Flowchart of for statement




Figure: Flowchart of for Loop

<https://www.programiz.com/cpp-programming/for-loop>

13

1. initialization                      4. update

2. boolean

```

for (int i = 0 ; i < 3 ; i++) {
    std::cout << i << ' ' ;
}
  
```

3. statement

then go back to step 2

14

### A for Statement

```

//Illustrates a for loop.
#include <iostream>
using namespace std;

int main()
{
    int sum = 0;
    for (int n = 1; n <= 10; n++) //Note that the variable n is a local
        sum = sum + n;           //variable of the body of the for loop!

    cout << "The sum of the numbers 1 to 10 is "
         << sum << endl;
    return 0;
}
  
```

*Initializing action* (points to `int n = 1`)  
*Repeat the loop as long as this is true.* (points to `n <= 10`)  
*Done after each loop body iteration* (points to `n++`)

### Output

The sum of the numbers 1 to 10 is 55

from: Problem Solving with C++, 10th Edition, Walter Savitch

15

## What is the output?

```

int value = 0;

for (int i = 0 ; i < 5 ; i++) {
    value += (i * 10);
}


std::cout << value << std::endl;
  
```

16

### for Loop with a Multistatement Body

#### Syntax

```
for (Initialization_Action; Boolean_Expression; Update_Action)
{
    Statement_1
    Statement_2
    .
    .
    Statement_Last
}
```



#### Example

```
for (int number = 100; number >= 0; number--)
{
    cout << number
        << " bottles of beer on the shelf.\n";
    if (number > 0)
        cout << "Take one down and pass it around.\n";
}
```

from: Problem Solving with C++, 10th Edition, Walter Savitch

17

## Examples

```
int n = 1;
```

```
for ( ; n <= 10 ; n = n + 2)
    std::cout << n << std::endl;
```

```
for (n = 10 ; n > 0 ; n -= 2) std::cout << n << std::endl;
```

```
for (n = 0 ; n > -30 ; n = n - 7) {
    std::cout << n << std::endl;
}
```

```
for (double x = 16.0 ; x >= 2.0 ; x = sqrt(x)) {
    std::cout << x;
    std::cout << std::endl;
}
```

18

## What is the output?

```
for (int count = 1 ; count <= 10 ; count++);
    std::cout << "Hello\n";
```

19

## Careful with the semi-colon

- Semi-colon is used to end statements
- Placing it after the parenthesis of a for loop creates an **empty statement**

20

## Different output?

```
for (int count = 1 ; count <= 10 ; count++){  
    std::cout << count << std::endl;  
}
```

V.S

```
for (int count = 1 ; count <= 10 ; ++count){  
    std::cout << count << std::endl;  
}
```

21

## Question

- Write a single for loop to print the first 50 even numbers

22

## Question

- Write a single for loop to print the average of the first 25 multiples of 3

23