

## Exercises for Data Visualisation with Matlab

### Obtaining the Examples

1. The course examples are available under the CIC6007 course on the online learning system, see matlab examples under the course content

The matlab examples zip file can also be downloaded from

[http://rcg.group.shef.ac.uk/courses/cic6007/matlab\\_examples.zip](http://rcg.group.shef.ac.uk/courses/cic6007/matlab_examples.zip)

Iceberg users may extract the examples from a tgz archive in the directory /usr/local/courses on iceberg.

On ShARC, use cd to change directory to a working directory of your choice then use the cp and tar commands to obtain and extract the examples.

The required commands are

```
cd ~/myworkingdirectory
```

```
tar -zxvf /usr/local/courses/matlab_examples.tgz
```

## Practice Session 1

### Exercises : Importing Data and Plotting in MATLAB

In the exercise directory you will find a data file named *field.dat* .

- 1 Read it into MATLAB and store columns 1 to 3 of the data as; temperature, pressure and density respectively

```
%Use Import Data from the home bar or Start -> Import Wizard . This should read all the data
%pres = FIELD(:,2) ; dens = FIELD(:,3);
field=readtable('field.dat');
[frows,fcols]=size(field)
temp=field.Var1
pres=field.Var2
dens=field.Var3
```

- 2 Using the PLOT command plot temperature variation
- 3 Using the PLOT command plot pressure variation

4 By making use of the HOLD command, plot both temperature and pressure in the same graph.

```
plot(temp) ;  
plot(pres) ;  
hold on ; plot(temp , 'g' ) ;
```

5 Fit a 5th degree polynomial to the data, display the equation on the graph and save the fitting parameters into the workspace via the Tools > Basic Fitting menu of the Figure window

```
%for help use  
%e.g. use [p,S] = polyfit(x,y,n)  
help polyfit  
[p,S] = polyfit(1:frows,temp,5)
```

6 Compute the max, min, mean and median values of the plot variables

7 Plot the mean value of y as a line on the current plot ( Hint: contract two end points of a line using values from the basic statistics and use them in a call to line command but don't forget to use the hold command first)

8 Using the edit-plot icon from the figure window toolbar edit this graph to change the colour of the mean-value line and the legend for it.

```
% eg. use  
field=temp;  
y = [mean(field),median(field),max(xfield),min(field)]
```

9 Using the SUBPLOT command. Plot three separate plots of all three variables on the same screen. Experiment with editing other aspects of the plot.

```
subplot(2,2,1); plot(temp)  
subplot(2,2,2); plot(dens)  
subplot(2,2,3); plot(pres)
```

Warning: MATLAB has disabled some advanced graphics rendering features by switching to software OpenGL. For more information, [click here](#).

## Exercise 2: Basic graphics

TASK 1 - edit trend.txt in the data folder ( by double clicking on it in matlab folder to view ) to see what it contains.

It is possible to read well constructed data files such as trend.txt into matlab by using the load command.

type: DOC LOAD and investigate help on using the LOAD command.

Read in this trend.txt into MATLAB using the LOAD command.

```
Y=load('..\data\trend.txt')
```

```

Y =
    264.7920    300.7650
    276.0750    304.8550
    256.7200    290.1760
    272.8350    282.6810
    290.9010    271.0990
    308.8470    263.7020
    333.2470    248.6270
    322.3900    264.0210
    353.2540    210.7080
    349.7380    190.8140
    ⋮

```

## TASK 2

Save each column as a separate variable by using vector assignments calling them y1 and y2

Plot Y1 using the PLOT command.

```

plot (Y) ;
y1=Y(:,1);
y2=Y(:,2);

```

Construct a vector called x that is the same length and shape as y1

and contains numbers from 1 to 100 ( or scaled by 100 so that it runs from 0.01 to 1.00

HINT you can either use notation the : notation. I.e start:interval:stop or Linspace function .



Plot y1 against x

HINT: type help plot to find out about the use of plot command.

```

x=1:100;
plot(x,y1);

```




TASK 3: Plotting multiple curves in one graph.

Open another graphics window. HINT: use `FIGURE` command.

Plot  $y_1$  against  $x$  and  $y_2$  against  $x$  on the same plot using a single `PLOT` command.

```
figure;  
plot(x,y1,x,y2);
```




#### TASK 4: Overlaying Plots

Plot  $y_1$  against  $x$  and  $y_2$  against  $x$  on the same plot but this time use two PLOT commands.

HINT: use hold command.

```
figure
plot(x,y1);
hold on
plot(x,y2);
hold off;
```



#### TASK 5 : Using subplots

Split your graphics window into two sections and plot  $y_1$  in one section and scattered values of  $y_1$  in another section.

HINT: Use SUBPLOT and SCATTER commands.

```
subplot(2,1,1)
plot(x,y1)
subplot(2,1,2)
scatter(x,y1)
```

#### TASK 6 : Properties of Graphical objects

Draw a scatter plot of  $y_1$

Fill the data markers with red colour.

HINT: Save the handle of the scatter plot while creating it.

Redefine the MarkerFaceColor property of the plot to be red ( i.e. 'r' )

HINT : assign a value to object.PropertyName

```
subplot(1,1,1);
s1=scatter(x,y1,[],'rs','filled','MarkerFaceAlpha',0.2)
```

## TASK 6 : Decorating a graph

Use the commands `TITLE` , `XLABEL` , `YLABEL` to label the graph.

```
title('trends')
xlabel('time')
ylabel('trend value')
```

Inspect the values for axes properties

```
ax=get(gca )
```

```
ALim: [0 1]
ALimMode: 'auto'
ActivePositionProperty: 'position'
AmbientLightColor: [1 1 1]
BeingDeleted: 'off'
Box: 'off'
BoxStyle: 'back'
BusyAction: 'queue'
ButtonDownFcn: ''
CLim: [0 1]
CLimMode: 'auto'
CameraPosition: [50 300 17.3205]
CameraPositionMode: 'auto'
CameraTarget: [50 300 0]
CameraTargetMode: 'auto'
CameraUpVector: [0 1 0]
CameraUpVectorMode: 'auto'
CameraViewAngle: 6.6086
CameraViewAngleMode: 'auto'
Children: [1x1 Scatter]
Clipping: 'on'
ClippingStyle: '3dbox'
Color: [1 1 1]
ColorOrder: [7x3 double]
ColorOrderIndex: 2
CreateFcn: ''
CurrentPoint: [2x3 double]
DataAspectRatio: [50 300 1]
DataAspectRatioMode: 'auto'
DeleteFcn: ''
FontAngle: 'normal'
FontName: 'Helvetica'
FontSize: 10
FontSmoothing: 'on'
FontUnits: 'points'
FontWeight: 'normal'
GridAlpha: 0.1500
GridAlphaMode: 'auto'
GridColor: [0.1500 0.1500 0.1500]
GridColorMode: 'auto'
GridLineStyle: '-'
HandleVisibility: 'on'
HitTest: 'on'
Interruptible: 'on'
LabelFontSizeMultiplier: 1.1000
Layer: 'bottom'
Legend: [0x0 GraphicsPlaceholder]
LineStyleOrder: '-'
LineStyleOrderIndex: 1
```

```

        LineWidth: 0.5000
        MinorGridAlpha: 0.2500
        MinorGridAlphaMode: 'auto'
        MinorGridColor: [0.1000 0.1000 0.1000]
        MinorGridColorMode: 'auto'
        MinorGridLineStyle: ':'
        NextPlot: 'replace'
        OuterPosition: [0 0.0568 1 0.4146]
        Parent: [1x1 Figure]
        PickableParts: 'visible'
        PlotBoxAspectRatio: [1 0.3295 0.3295]
        PlotBoxAspectRatioMode: 'auto'
        Position: [0.1300 0.1100 0.7750 0.3412]
        Projection: 'orthographic'
        Selected: 'off'
        SelectionHighlight: 'on'
        SortMethod: 'childorder'
        Tag: ''
        TickDir: 'in'
        TickDirMode: 'auto'
        TickLabelInterpreter: 'tex'
        TickLength: [0.0100 0.0250]
        TightInset: [0.0506 0.0532 0.0205 0.0202]
        Title: [1x1 Text]
TitleFontSizeMultiplier: 1.1000
        TitleFontWeight: 'bold'
        Type: 'axes'
        UIContextMenu: [0x0 GraphicsPlaceholder]
        Units: 'normalized'
        UserData: []
        View: [0 90]
        Visible: 'on'
        XAxis: [1x1 NumericRuler]
        XAxisLocation: 'bottom'
        XColor: [0.1500 0.1500 0.1500]
        XColorMode: 'auto'
        XDir: 'normal'
        XGrid: 'off'
        XLabel: [1x1 Text]
        XLim: [0 100]
        XLimMode: 'auto'
        XMinorGrid: 'off'
        XMinorTick: 'off'
        XScale: 'linear'
        XTick: [0 10 20 30 40 50 60 70 80 90 100]
        XTickLabel: {11x1 cell}
        XTickLabelMode: 'auto'
        XTickLabelRotation: 0
        XTickMode: 'auto'
        YAxis: [1x1 NumericRuler]
        YAxisLocation: 'left'
        YColor: [0.1500 0.1500 0.1500]
        YColorMode: 'auto'
        YDir: 'normal'
        YGrid: 'off'
        YLabel: [1x1 Text]
        YLim: [0 600]
        YLimMode: 'auto'
        YMinorGrid: 'off'
        YMinorTick: 'off'
        YScale: 'linear'
        YTick: [0 200 400 600]
        YTickLabel: {4x1 cell}
        YTickLabelMode: 'auto'
        YTickLabelRotation: 0

```





```

YTickMode: 'auto'
ZAxis: [1x1 NumericRuler]
ZColor: [0.1500 0.1500 0.1500]
ZColorMode: 'auto'
ZDir: 'normal'
ZGrid: 'off'
ZLabel: [1x1 Text]
ZLim: [-1 1]
ZLimMode: 'auto'
ZMinorGrid: 'off'
ZMinorTick: 'off'
ZScale: 'linear'
ZTick: [-1 0 1]
ZTickLabel: ''
ZTickLabelMode: 'auto'
ZTickLabelRotation: 0
ZTickMode: 'auto'

```

---



```

% Use the set command to change the range of the y axis limits by filling
% in the missing two parameters of the following set command;
% set ( gca , '.....' , '.....' )

```

## Practice Session 2

### Exercise 3

Create a filled scatter plot that plots the data.Windspeedvalues at sea, i.e., values not on land (~onland), along the x-axis and the corresponding data.Pressure values along the y-axis. Use circular markers with blue color. Make sure the marker faces are semitransparent and have blue color.

```
% create a new variable named data.HurrCat that contains the
% hurricane category of the observation based on data.Windspeed.
data = readtable('..\data\hurricaneData1990s-v2.txt','HeaderLines',5);

%if any windspeeds are NaN set to zero
idwindnan = find(isnan(data.Windspeed));
data.Windspeed(idwindnan)=0;


sz=size(data);
a=data.Country;
for i=1:sz(1)
    if isequal(a{i},'N/A' )
        data.Location{i} = 'Sea';
        onland(i)=0;
    else
        data.Location{i} = 'Land';
        onland(i)=1;
    end
end

data.Location;

figure
hold on
%TODO Create a filled scatter plot that plots the data.Windspeedvalues at sea, i.e., values not
% along the x-axis and the corresponding data.Pressure values along the y-axis. Use circular markers
scatter(data.Windspeed(~onland),data.Pressure(~onland),'b','filled','MarkerFaceAlpha',0.5)
scatter(data.Windspeed(onland==1),data.Pressure(onland==1),'r','filled','MarkerFaceAlpha',0.5)
hold off
```

Change the x-axis limits to go from 15 to 60 and add minor grid lines to the scatter plot.

```
%TODO change limit and grid
xlim([15 60])
grid('minor') %add minor states
```



Plotting bargraphs and binning data and using discretization

```
% Find index of on-land and on-sea observation index
SSscale = [0 39 74 96 111 130 157 Inf];
catnames = {'TD','TS','1','2','3','4','5'};
data.HurrCat = discretize(data.Windspeed,SSscale,'Categorical',catnames)
```

data = 51x7 table

...

	Number	Timestamp	Country	Windspeed	Pressure	Location
1	1	29-Jun-1991...	'N/A'	23	1012	'Sea'
2	1	29-Jun-1991...	'N/A'	23	1012	'Sea'
3	1	30-Jun-1991...	'N/A'	0	1012	'Sea'

	Number	Timestamp	Country	Windspeed	Pressure	Location
4	1	30-Jun-1991...	'United Sta...	23	1012	'Land'
5	1	30-Jun-1991...	'United Sta...	23	1012	'Land'
6	1	30-Jun-1991...	'N/A'	23	1012	'Sea'
7	1	01-Jul-1991...	'N/A'	23	1012	'Sea'
8	1	01-Jul-1991...	'United Sta...	23	1012	'Land'
9	1	01-Jul-1991...	'United Sta...	23	1012	'Land'
10	1	01-Jul-1991...	'United Sta...	23	1012	'Land'
11	1	02-Jul-1991...	'United Sta...	23	1012	'Land'
12	2	19-Aug-1991...	'N/A'	109	957	'Sea'
13	2	19-Aug-1991...	'N/A'	0	950	'Sea'
14	2	19-Aug-1991...	'N/A'	109	953	'Sea'
15	2	19-Aug-1991...	'N/A'	98	964	'Sea'
16	2	20-Aug-1991...	'N/A'	69	977	'Sea'

```
windBinNo = discretize(data.Windspeed,SSscale);
```

```
sz=size(SSscale)
```


```
SZ =
     1     8
```

```
szw=size(windBinNo)
```

```
szw =
    51     1
```

```
numwindbin=zeros(sz(2)-1,1);
for i=1:szw(1)
    windbin=windBinNo(i);
    numwindbin(windbin)=numwindbin(windbin)+1;
end


%TODO plot the barchart of the number in each bin
bar(numwindbin);
title('Distribution of Hurricane Storm Force in the 1990s');
xlabel('Storm Force');
ylabel('Number of Hurricanes');
set(gca,'XTickLabel',catnames);
```



#### Exercise to Load data and

The file 'fuelEconomy.txt' contains fuel economy data for different models of cars (you can use the command `edit fuelEconomy.txt` to examine its contents).

The goal of this exercise is to divide the combined miles per gallon data into three classes and create a scatter plot of city and highway miles per gallon like the one shown below.



Follow the steps listed below:

Step 1 – Import the data into a table.

Step 2 – The variable CombinedMPG contains missing values represented by NaN. Remove the rows corresponding to these missing values from the imported table.

Step 3 – Discretize the CombinedMPG variable into three classes called 'Low', 'Medium', and 'High' using the bin edges 0, 20, 30, and 70 (values greater than or equal to 0 and less than 20 are classified as 'Low' and so on). Store the discretized result in a variable named MPGClass.

Step 4 – Create a scatter plot with CityMPG on the x-axis and HighwayMPG on the y-axis. Observations with 'Low' combined MPG should be colored red ('r'), 'Medium' should be blue ('b'), and 'High' should be 'black' ('k').

```
%TODO step 1
% Read data
data=readtable(' ../data/fuelEconomy.txt')
```

data = 386x7 table

...

	Class	Make	Model	NumCyl	CityMPG	HighwayMPG
1	'TWO SEATERS'	'ASTON MARTIN'	'DBS COUPE'	12	14.4000	24.7000

	Class	Make	Model	NumCyl	CityMPG	HighwayMPG
2	'TWO SEATERS'	'ASTON MARTIN'	'V8 VANTAGE'	8	15.9375	26.8550
3	'TWO SEATERS'	'AUDI'	'R8'	8	11.0000	25.0451
4	'TWO SEATERS'	'AUDI'	'TT ROADSTER'	4	28.5000	42.2000
5	'TWO SEATERS'	'AUDI'	'TT ROADSTE...	4	27.1619	39.0337
6	'TWO SEATERS'	'AUDI'	'TT ROADSTE...	6	22.3987	33.5729
7	'TWO SEATERS'	'CADILLAC'	'XLR'	8	17.0000	32.3000
8	'TWO SEATERS'	'CADILLAC'	'XLR'	8	18.5000	34.1000
9	'TWO SEATERS'	'CHEVROLET'	'CORVETTE'	8	18.2499	34.3493
10	'TWO SEATERS'	'FERRARI'	'F430'	8	13.7498	22.4000
11	'TWO SEATERS'	'FERRARI'	'FERRARI 59...	12	12.9992	20.9995
12	'TWO SEATERS'	'LAMBORGHINI'	'GALLARDO C...	10	16.1000	25.4000
13	'TWO SEATERS'	'LAMBORGHINI'	'GALLARDO S...	10	16.0000	25.4000
14	'TWO SEATERS'	'LAMBORGHINI'	'MURCIELAGO'	12	10.9000	19.9000
15	'TWO SEATERS'	'LAMBORGHINI'	'MURCIELAGO...	12	10.9000	19.9000
16	'TWO SEATERS'	'MERCEDES-B...	'SL550'	8	16.5000	29.3000

```

%TODO step 2
% Identify the rows containing NaN values and remove them
nanIdx = ismissing(data.CombinedMPG);
data(nanIdx,:) = [];

%TODO step 3 hint use the discretize function
% Discretize Combined MPG
MPGClass = discretize(data.CombinedMPG,[0 20 30 70],{'Low' 'Medium' 'High'});


% Optional - Convert the class into a categorical array
MPGClass = categorical(MPGClass);

%TODO step 4
% Extract observations for various classes and plot them
scatter(data.CityMPG(MPGClass == 'Low'),data.HighwayMPG(MPGClass == 'Low'),...
'r','filled')
hold on
scatter(data.CityMPG(MPGClass == 'Medium'),data.HighwayMPG(MPGClass == 'Medium'),...
'b','filled')
hold on
scatter(data.CityMPG(MPGClass == 'High'),data.HighwayMPG(MPGClass == 'High'),...
'k','filled')
hold off

grid on
xlabel('City MPG')
ylabel('Highway MPG')

```

```
legend('Low Combined MPG','Medium Combined MPG','High Combined MPG');
```



#### Exercise 4: Interpolating Scattered Data

Modify the script for the Australian surface temperature data so that it interpolates the raw data given by lon, lat and T and evaluates the data at the points in the XY grid where the x-data goes from 110 to 155 and the y-data goes from -45 to -10, both in unit steps. The interpolated values should be stored in an array named Tgrid.

```
%% Import data
clf
data=readtable(' ../data/australia_march_temps.csv');

%% Extract data
lon = (data.longitude)';
lat = (data.latitude)';
T = (data.temperature)';

scatter(lon,lat,[],T,'filled')
colorbar
hold on

%TODO
% Create vectors for new longitude and latitude values
lonvec = linspace(110,155,36);
latvec = linspace(-45,-10,36);
```



```


%TODO interpolate temperature data T using griddata function
Tnew = griddata(lon,lat,T,lonvec,latvec);
% Create a grid of longitudes and latitudes
[longrid,latgrid] = meshgrid(lonvec,latvec);

% Interpolate the scattered March temperature data onto the grid
%Tgrid = griddata(lonvec,latvec,T,longrid,latgrid);

id=(isnan(Tnew));
idn=find(id);
Tnew(idn)=0;

scatter(lonvec,latvec,[],Tnew,'filled')

```



## Exercise: Visualising Surfaces

Use meshgrid to create a grid of x-, y-data using the x- and y-arrays. Store the grid arrays as X and Y.

```

%TODO use meshgrid
[X,Y]=meshgrid(x,y);

```

Create an array named Z which contains the calculation below for each x-y point in the XY grid.

$\sin(x) + \cos(y)$

```
%TODO define Z here
Z=sin(X)+cos(Y);
```

**Info:** You can use the surf function to create a surface plot.

```
>> [X,Y] = meshgrid(0:0.1:1,-2:0.2:2);
>> Z = X*Y
>> surf(X,Y,Z)
```

Create a surface plot of the Z data over the entire XY grid.

```
%TODO
surf(X,Y,Z)
```

Study how the following surface changes

```
X = [ 0  0  0.25
      1  1  0.75 ];
Y = [ 20  21  21
      20  21  21 ];
Z = [ 105  105  105.5
      105  105  105.5 ];

surf(X,Y,Z)
```

Now try the following surface, observe how this changes and how the surface points are linked

```
X = [ 0  0  0.25  0
      1  1  0.75  1 ];
Y = [ 20  21  21  21
      20  21  21  21 ];
Z = [ 105  105  105.5  106
      105  105  105.5  106 ];
surf(X,Y,Z)
```

In the surface below swap 0.25 and 0.75 for the X coordinate and observe how the plot changes

```
X = [ 0      1
      0.25  0.75 ];
Y = [ 0  0
      1  1 ];
Z = [ 1  1
      1  1 ];

surf(X,Y,Z)
```

Create a surface plot of the data in the file data/natick.txt. Make the lines between the patches invisible, and interpolate the face colors of the patches.


```
%% Import data
fid = fopen(' ../data/natick.txt');
data = textscan(fid, '%f%f%f', 'HeaderLines', 1);
fclose(fid);

%% Extract data
x = data{1};
y = data{2};
z = data{3};

%% Create an XY grid from the raw data
xv = min(x):0.01:max(x);
yv = min(y):0.01:max(y);
[X,Y] = meshgrid(xv,yv);

%% Interpolate the raw data and evaluate it on the X,Y grid
Z = griddata(x,y,z,X,Y);

%%TODO modify the properties for the surface hint EdgeColor and FaceColor
%% Create a surface plot of the data
s = surf(X,Y,Z);
s.EdgeColor = 'none';
s.FaceColor = 'interp';
```



In the casestudies/membrane folder study the script membrane. Modify the surf plot so that the faces have transparency, interpolation is used to shade the faces

and so that there are no lines between them. Run the script from the matlab workbench.

The surface plot created by the script displays elevation data.

Modify the script so that:

- The autumn colormap is used
- A colorbar is added to the figure
- The colormap values are in the range 3000 to 4000

```
% Import data
fid = fopen('../data/natick.txt');
data = textscan(fid, '%f%f%f', 'HeaderLines', 1);
fclose(fid);


%% Extract data
x = data{1};
y = data{2};
z = data{3};

%% Create an XY grid from the raw data
xv = min(x):0.01:max(x);
yv = min(y):0.01:max(y);
[X,Y] = meshgrid(xv,yv);

%% Interpolate the raw data and evaluate it on the X,Y grid
Z = griddata(x,y,z,X,Y);

%%TODO
%% Create a surface plot of the data
s = surf(X,Y,Z);
s.EdgeColor = 'none';
s.FaceColor = 'interp';

colormap('autumn');
colorbar;
ax=gca;
ax.CLim=[3000 4000]; %change the c limits
```



Modify the script for the Australian temperatures data so that it creates a pseudocolor image of Tgrid as a function of longitude and latitude.

Customize the appearance of the surface so that the lines between the patches have some transparency.

Create another figure that contains the scaled image of the same data. Make sure that the y coordinates are numbered from bottom-to-top. Also, make sure that the correct x- and y-data is plotted.

```
%% Import data
clf
data=readtable(' ../data/australia_march_temps.csv');

%% Extract data
lon = (data.longitude)';
lat = (data.latitude)';
T = (data.temperature)';

% Create vectors for new longitude and latitude values
lonvec = 110:155;
latvec = -45:-10;

% Create a grid of longitudes and latitudes
[longrid,latgrid] = meshgrid(lonvec,latvec);


% Interpolate the scattered March temperature data onto the grid
```

```

Tgrid = griddata(lon,lat,T,longgrid,latgrid);

%% TODO: Create two images of the temperature data
figure
im = pcolor(longgrid,latgrid,Tgrid);
im.EdgeColor = 0.5*[1 1 1];
im.EdgeAlpha = 0.5;

```



```

figure
im2 = imagesc(lonvec,latvec,Tgrid);
axis xy

```

