

[Explore Sandbox](#)[Partner Portal](#)[Merchant Portal](#)[Home](#) [Guides](#) [Recipes](#) [API Reference](#)

Search

CTRL - K

JUMP TO

CTRL-/

OVERVIEW

[Getting Started with Our APIs](#)[Authentication](#)[Embedded Component Authentication](#)[Testing Methods](#)[Rate Limiting](#)[Pagination](#)[Response Codes](#)

MERCHANT SIGN-UP

[Overview](#)[Authentication](#)[Packages](#)[Applications](#)

Payment API

Copy Page

POST <https://sandbox.nmi.com/api/transact.php>

Never Use Real API Keys

Never use real API Keys when testing. The gateway allows Partners to create Test Merchant Accounts. Testing should always use keys from the Test Accounts and never keys from a Standard Account.

[► Methodology](#)[► Click to see invoice related notes](#)[► Response Code Table](#)

Recent Requests

[Log in to see full request history](#)

TIME

STATUS

USER AGENT

[Make a request to see history.](#)

Form Data

Device Sale (Unencrypted Retail Magnetic Stripe Data)

security_key string **required**

6457Thfj624V5r7Wl

API Security Key assigned to a merchant account.
New keys can be generated from the merchant control panel in Settings > Security Keys

type string **required**

sale

The type of transaction to be processed. Must be one of:
auth , sale , credit , offline , validate

partial_payments string enum

settle_partial : Settles any amount of tender

Webhook Subscriptions	>	collected (captured partial auth's and approved partial sales) at cut off.
		payment_in_full : Required that any split tendered transaction is collected in-full before settlement gets initiated.
		Allowed: settle_partial payment_in_full
		track_1 string required Raw Magnetic Stripe Data.
Webhook Events	>	track_2 string required Raw Magnetic Stripe Data.
		track_3 string Raw Magnetic Stripe Data.
		partial_payment_id string Unique identifier returned when making the original transaction. This should only be used for secondary transactions.
		amount string required 1 Total amount to be charged. Format: x.xx
		payment_token string The tokenized version of the customer's card or check information. This will be generated by Collect.js and is usable only once.
		transaction_session_id string length between 32 and 32 A single use session ID used by Kount to link the transaction and Data Collector information together. • Should be generated every time a payment form is loaded by the cardholder. • Should be random/unpredictable (do not use sequential IDs). • Should not be reused within a 30 day period. This can be used with Collect.js or the Payment API when using the Kount DDC with Gateway.js. Format: alphanumeric
Legal Consent Helper		
ONLINE PAYMENTS		
Payments	>	googlepay_payment_data string The encrypted token created when integration directly to the Google Pay SDK.

Invoicing	>	applepay_payment_data string	
		The encrypted payment data from the Apple Pay SDK. Required when data collected directly from Apple Pay SDK.	
		surcharge string	
		Surcharge amount.	
		Format: x.xx	
Subscriptions	>	convenience_fee string	
		Convenience fee amount.	
		Format: x.xx	
		misc_fee string	
		Miscellaneous fee amount.	
Plans	>	misc_fee_name string	
		Custom miscellaneous fee name.	
		Default: Miscellaneous Fee	
		tip number	
		The final tip amount, included in the transaction, associated with the purchase.	
Customers	>	currency string	
		The transaction currency.	
		Format: ISO 4217	
		processor_id string	
		If using Multiple MIDs, route to this processor (<i>processor_id</i> is obtained under Settings → Transaction Routing in the Control Panel).	
	>	dup_seconds integer ≤ 7862400	
		Sets the time in seconds for duplicate transaction checking on supported processors. Set to 0 to disable duplicate checking.	
	>	descriptor string	
		Set payment descriptor on supported processors.	

Products



descriptor_phone string	
Set payment descriptor phone on supported processors.	
descriptor_address string	
Set payment descriptor address on supported processors.	
descriptor_city string	
Set payment descriptor city on supported processors.	
descriptor_state string	
Set payment descriptor state on supported processors.	
descriptor_postal string	
Set payment descriptor postal code on supported processors.	
descriptor_country string	
Set payment descriptor country on supported processors.	

TXT2PAY (Powered by Authvia)



descriptor_mcc string	
Set payment descriptor mcc on supported processors.	
descriptor_merchant_id string	
Set payment descriptor merchant id on supported processors.	

IN-PERSON PAYMENTS

Devices



billing_method string enum	
Can be set to 'recurring' to mark payment as a recurring transaction or 'installment' to mark payment as an installment transaction.	
Allowed: recurring installment	
billing_number integer 0 to 99	
Specify installment billing number, on supported processors. For use when <code>billing_method</code> is set to "installment".	
billing_total string	
Specify installment billing total on supported	

processors. For use when `billing_method` is set to "installment".

order_template string

Order template ID.

order_description string

Order description.

orderid string

Level III - Order Field: Identifier assigned by the merchant. This defaults to gateway transaction id.

ipaddress string

IP address of cardholder, this field is recommended.

Format: xxx.xxx.xxx.xxx

first_name string

Cardholder's first name.

last_name string

Cardholder's last name

company string

Cardholder's company

address1 string

Card billing address

address2 string

Card billing address, line 2

city string

Card billing city

state string

Card billing state.

Format: CC

zip string

Card billing zip code

country string

Card billing country. Country codes are as shown in ISO 3166-1 alpha-2.

Format: CC

		processors. For use when <code>billing_method</code> is set to "installment".
		order_template string Order template ID.
		order_description string Order description.
		orderid string Level III - Order Field: Identifier assigned by the merchant. This defaults to gateway transaction id.
		ipaddress string IP address of cardholder, this field is recommended. Format: <code>xxx.xxx.xxx.xxx</code>
		first_name string Cardholder's first name.
In-Person Payments Overview	↗	last_name string Cardholder's last name
Customer Present Cloud API	↗	
Download SDK for iOS/Android	↗	company string Cardholder's company
Download SDK for Windows/Linux	↗	
ACCOUNT MANAGEMENT		
Overview		address1 string Card billing address
Affiliates	>	address2 string Card billing address, line 2
		city string Card billing city
Merchants	>	state string Card billing state. Format: <code>CC</code>
		zip string Card billing zip code
		country string Card billing country. <i>Country codes are as shown in ISO 3166-1 alpha-2.</i>
Settlement Time	>	Format: <code>CC</code>

Fee Schedule	>	phone string	
		Billing phone number	
		fax string	
		Billing fax number	
Processors and Services	>	email string	
		Billing email address	
		drivers_license_number string	
		Driver's license number.	
		drivers_license_dob string	
		Driver's license date of birth.	
		drivers_license_state string	
		The state that issued the customer's driver's license.	
Customer Token Vault	>	shipping_firstname string	
		Shipping first name	
		shipping_lastname string	
		Shipping last name	
		shipping_company string	
		Shipping company	
REPORTING	>	shipping_address1 string	
		Shipping address	
		shipping_address2 string	
General		Shipping address, line 2	
Transactions	>	shipping_city string	
		Shipping city	
Billing & Commission	>	shipping_state string	
		Shipping state.	
		Format: CC	
ADMINISTRATION	>	shipping_zip string	
		Shipping zip code	
Users	>		

API Keys



shipping_country string

Level III - Order Field: Shipping country (e.g. US).

Format: CC - ISO 3166-1 alpha-2

Webhooks



shipping_email string

Shipping email address

merchant_defined_field_1 string

Merchant defined field. You can pass custom information in up to 20 fields.

Format: merchant_defined_field_1=Value1 , merchant_defined_field_2=Value2 , etc...

customer_receipt string enum

If set to true, when the customer is charged, they will be sent a transaction receipt.

Allowed: true false

OTHER RESOURCES

Postman Collection

Gateway Emulator



cardholder_auth string enum

Set 3D Secure condition. Value used to determine E-commerce indicator (ECI).

Required for 3D Secure transactions

Allowed: verified attempted

MCP SERVER

MCP



cavv string

Cardholder authentication verification value.

Format: base64 encoded Required for 3D Secure transactions

CLASSIC APIS

Transactions



xid string

Cardholder authentication transaction id.

Format: base64 encoded Required for 3D Secure transactions

Invoices



three_ds_version string enum

3DSecure version. Required for 3D Secure transactions

Allowed: 2.0.0 2.2.0

Plans



directory_server_id string

Directory Server Transaction ID. May be provided as part of 3DSecure 2.0 authentication.

Customers



Format: xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx



source_transaction_id string	
Specifies a payment gateway transaction id in order to associate payment information with a Subscription or Customer Vault record. Must be set with a 'recurring' or 'customer_vault' action.	
pinless_debit_override string	
Set to 'Y' if you have Pinless Debit Conversion enabled but want to opt out for this transaction. Feature applies to selected processors only.	
recurring string enum	
Recurring Field: Recurring action to be processed. Allowed: add_subscription	
plan_id string	
Recurring Field: Create a subscription tied to a Plan ID if the sale/auth transaction is successful. Required when recurring variable is set to <code>add_subscription</code>	
plan_payments integer	
Recurring Field: The number of payments before the recurring plan is complete. Note: Use '0' for until canceled Required when recurring variable is set to <code>add_subscription</code>	
plan_amount number	
Recurring Field: The plan amount to be charged each billing cycle. Format: <code>x.xx</code> Required when recurring variable is set to <code>add_subscription</code>	
month_frequency integer 1 to 24	
Recurring Field: How often, in months, to charge the customer. Cannot be set with 'day_frequency'. Must be set with 'day_of_month'. Required when recurring variable is set to <code>add_subscription</code>	
day_of_month integer 1 to 31	
Recurring Field: The day that the customer will be charged. Cannot be set with 'day_frequency'. Must be set with 'month_frequency'. For months without 29, 30, or 31 days, the charge will be on the last	

day	
Required when recurring variable is set to add_subscription	
day_frequency integer Recurring Field: How often, in days, to charge the customer. Cannot be set with 'month_frequency' or 'day_of_month'. Required when recurring variable is set to add_subscription	
start_date date Recurring Field: The first day that the customer will be charged. Format: YYYYMMDD Required when recurring variable is set to add_subscription	
customer_vault string enum Associate payment information with a Customer Vault record if the transaction is successful. Allowed: add_customer update_customer	
customer_vault_id string Specifies a Customer Vault id. If not set, the payment gateway will randomly generate a Customer Vault id.	
initiated_by string enum Stored Credentials (CIT/MIT): Who initiated the transaction. Allowed: customer merchant	
initial_transaction_id string Stored Credentials (CIT/MIT): Original payment gateway transaction id.	
stored_credential_indicator string enum Stored Credentials (CIT/MIT): The indicator of the stored credential. Use 'stored' when processing the initial transaction in which you are storing a customer's payment details (customer credentials) in the Customer Vault or other third-party payment storage system. Use 'used' when processing a subsequent or follow-up transaction using the customer payment details (customer credentials) you have already	

stored to the Customer Vault or third-party payment storage method.

Allowed:

shipping number

Level II/III - Order Field: Freight or shipping amount included in the transaction amount. Default - 0.00 .

Format: x.xx

tax number

Level II/III - Order Field: The sales tax, included in the transaction amount, associated with the purchase. Setting tax equal to '-1' indicates an order that is exempt from sales tax. Default - 0.00 .

Format: x.xx

ponumber string

Level II/III - Order Field: Purchase order number

shipping_postal string

Level III - Order Field: Postal/ZIP code of the address where purchased goods will be delivered. This field can be identical to the 'ship_from_postal' if the customer is present and takes immediate possession of the goods.

ship_from_postal string

Level III - Order Field: Postal/ZIP code of the address from where purchased goods are being shipped, defaults to merchant profile postal code.

summary_commodity_code string

Level III - Order Field: 4 character international description code of the overall goods or services being supplied. The acquirer or processor will provide a list of current codes.

duty_amount number

Level III - Order Field: Amount included in the transaction amount associated with the import of purchased goods. Default - 0.00 .

Format: x.xx

discount_amount number

Level III - Order Field: Amount included in the transaction amount of any discount applied to complete order by the merchant. Default - 0.00 .

Format: x.xx

national_tax_amount number

Level III - Order Field: The national tax amount included in the transaction amount. Default - 0.00 .

Format: x.xx

alternate_tax_amount number

Level III - Order Field: Second tax amount included in the transaction amount in countries where more than one type of tax can be applied to the purchases. Default - 0.00 .

Format: x.xx

alternate_tax_id string

Level III - Order Field: Tax identification number of the merchant that reported the alternate tax amount.

vat_tax_amount number

Level III - Order Field: Contains the amount of any value added taxes which can be associated with the purchased item. Default - 0.00 .

Format: x.xx

vat_tax_rate number

Level III - Order Field: Contains the tax rate used to calculate the sales tax amount appearing. Can contain up to 2 decimal places, e.g. 1% = 1.00. Default - 0.00 .

Format: x.xx

vat_invoice_reference_number string

Level III - Order Field: Invoice number that is associated with the VAT invoice.

customer_vat_registration string

Level III - Order Field: Value added tax registration number supplied by the cardholder.

merchant_vat_registration string

Level III - Order Field: Government assigned tax identification number of the merchant for whom the goods or services were purchased from.

order_date date

Level III - Order Field: Purchase order date, defaults to the date of the transaction.

Format: YYMMDD

item_product_code_1 string

Level III - Line Item: Merchant defined description code of the item being purchased.

*Up to 99 sets of item_ fields are allowed.**

item_description_1 string

Level III - Line Item: Description of the item(s) being supplied.

item_commodity_code_1 string

Level III - Line Item: International description code of the individual good or service being supplied. The acquirer or processor will provide a list of current codes.

item_unit_of_measure_1 string

Level III - Line Item: Code for units of measurement as used in international trade. Default - EACH .

item_unit_cost_1 number

Level III - Line Item: Unit cost of item purchased, may contain up to 4 decimal places.

item_quantity_1 integer

Level III - Line Item: Quantity of the item(s) being purchased. Default - 1 .

item_total_amount_1 number

Level III - Line Item: Purchase amount associated with the item. Defaults to: 'item_unit_cost_#' x 'item_quantity_#' rounded to the nearest penny.

item_tax_amount_1 number

Level III - Line Item: Amount of sales tax on specific item. Amount should not be included in 'total_amount_#'. Default - 0.00 .

Format: x.xx

item_tax_rate_1 number

Level III - Line Item: Percentage representing the value-added tax applied. Default - 0.00 .

Format: x.xx

item_discount_amount_1 number

Level III - Line Item: Discount amount which can have been applied by the merchant on the sale of

the specific item. Amount should not be included in 'total_amount_#'.

item_discount_rate_1 number

Level III - Line Item: Discount rate for the line item.
Default - 0.00 .

Format: x.xx

item_tax_type_1 string

Level III - Line Item: Type of value-added taxes that are being used.

item_alternate_tax_id_1 string

Level III - Line Item: Tax identification number of the merchant that reported the alternate tax amount.

payment_facilitator_id string

Payment Facilitator: Payment Facilitator/Aggregator/ISO's ID Number

submerchant_id string

Payment Facilitator: Sub-merchant Account ID

submerchant_name string

Payment Facilitator: Sub-merchant's Name

submerchant_address string

Payment Facilitator: Sub-merchant's Address

submerchant_city string

Payment Facilitator: Sub-merchant's City

submerchant_state string

Payment Facilitator: Sub-merchant's State

submerchant_postal string

Payment Facilitator: Sub-merchant's Zip/Postal Code

submerchant_country string

Payment Facilitator: Sub-merchant's Country

submerchant_phone string

Payment Facilitator: Sub-merchant's Phone Number

submerchant_email string

Payment Facilitator: Sub-merchant's Email Address

Format: base64 encoded raw PNG image.
(16kiB maximum)

+

— **200**
Operation response

Click **Try It!** to start a request and see the response here. Or choose an example:

Examples

200 - Credit Card Transaction C **200 - Credit Card Offline Transaction**

RESPONSE

- 200 - Credit Card Transaction Created
- 200 - Credit Card Partial Payment
- 200 - Partial Payment Pay In Full
- 200 - ACH Sale Transaction
- 200 - ACH Transaction Refunded
- 200 - ACH Transaction Voided
- 200 - Cash Sale Transaction
- 200 - Authorize Using Customer Vault
- 200 - Sale Using Customer Vault
- 200 - Validate Using Customer Vault
- 200 - Invoice Created
- 200 - Invoice Updated
- 200 - Invoice Sent
- 200 - Invoice Closed
- 200 - Error - Invoice Closed Already
- 200 - Billing Information Created
- 200 - Billing Information Updated
- 200 - Billing Information Deleted
- 200 - Plan Created
- 200 - Plan Updated
- 200 - Subscription Added
- 200 - Subscription Updated
- 200 - Subscription Deleted
- 200 - Failed To Create Plan



200 - Transaction Updated

200 - Customer Created

200 - Customer Deleted

200 - Customer Update Failed

200 - Product Added

200 - Product Added Fail with Our APIs →

200 - Product Updated

200 - Product Update Failed

200 - Product Deleted

200 - Credential On File - Approved Transaction

Did this page help you?

 Yes

 No