

Python Quiz: Object Oriented Programming

Total Score: /2²

Printed Name:

Quiz rules:

1. You MAY use any printed or handwritten notes.
2. You MAY NOT use a computer or any other electronic device.

Problem 1. The following code (circle one)

terminates without error

throws an exception

runs forever

If the code terminates without error, write the output. If the code throws an exception, state the exception.

```
def reverse_list(xs):
    ys = []
    for i in range(len(xs)):
        ys.append(xs.pop())
    return ys
xs = [3, 2, 1]
ys = reverse_list(xs)
print('xs=', xs)
print('ys=', ys)
```

Fraction of LLMs with correct answer: 6 / 10 = 0.60

Problem 2. The following code (circle one)

terminates without error

throws an exception

runs forever

If the code terminates without error, write the output. If the code throws an exception, state the exception.

```
xs = ['Guido', 'van', 'Rossum']
ys = xs.sort()[0]
print('xs=', xs)
print('ys=', ys)
```

Fraction of LLMs with correct answer: 7 / 10 = 0.70

Problem 3. The following code (circle one)

terminates without error

throws an exception

runs forever

If the code terminates without error, write the output. If the code throws an exception, state the exception.

```
xs = [1, 2]
def foo(xs=[]):
    xs.append(len(xs))
    return len(xs)
y = foo([1])
y = foo([1, 2, 3])
y = foo([1, 2])
y = foo()
print('y=', y)
```

Fraction of LLMs with correct answer: $7 / 10 = 0.70$

Problem 4. The following code (circle one)

terminates without error

throws an exception

runs forever

If the code terminates without error, write the output. If the code throws an exception, state the exception.

```
class Foo:
    def __init__(self):
        self.xs = []
    def bar(self, x):
        self.xs.append(x)
a = Foo()
a.bar(b.xs)
b = Foo()
b.bar('mundo')
x = len(a.xs)
print('x=', x)
```

Fraction of LLMs with correct answer: $7 / 10 = 0.70$

LLM Model Performance

