

For:hawthorn

Printed on:Thu, Dec 11, 1997 09:15:12

From book:CompactPDU

Document:a

Last saved on:Tue, Jun 3, 1997 04:22:36

APPENDIX A – SPECIFICATIONS

TABLE A–1
SPECIFICATIONS

PART NO. 46–317099 >	P8, P10, P15, P16	P9, P11, P13, P14	P12
NOMINAL INPUT VOLTAGE	480	380/400/415	380/400/415/480
INPUT VOLTAGE RANGE	432–518	342–410 360–432 373–448	342–528
MAXIMUM INPUT VOLTAGE	518	448	528
NOMINAL RATED CURRENT (A)	66	80	66
MAXIMUM RATED CURRENT (A)	80		
FREQUENCY (Hz)	60	50/60	60
OUTPUT VOLTAGE REGULATION	2%		NONE
LINE–TO–LINE VARIATION	LESS THAN 2%		
RESPONSE TIME	1 CYCLE		
FILTERS: INPUT OUTPUT	YES YES		YES YES
COOLING REQUIREMENT (BTU/hr)	7000		6500
WEIGHT lbs (kg)	970 (440)		820 (372)
OUTPUT VOLTAGE	208Y120		
CAPACITY (KVA)	50		
NUMBER OF PHASES	3		
SURGE RATING	300% FOR 10 SECONDS		
HARMONICS ADDED	LESS THAN 1%		
POWER FACTOR	GREATER THAN 95%		
AMBIENT TEMPERATURE F (C)	80 (26.7)		
SIZE H X W X D in. (cm)	70 X 22.1 X 30 (1779 X 56 X 76)		