

SECTION 2

TARPED MAGNET DELIVERY

WARNING!

LIFTING / JACKING ANGLES THAT ARE SHIPPED INSTALLED ON MAGNET ARE NOT TO BE USED TO LIFT MAGNET WITH CRANE. SERIOUS PERSONNAL INJURY AND MAGNET DAMAGE COULD RESULT. MAGNET MAY BE LIFTED USING BELLY STRAPS WITH CRANE OR LIFTING / JACKING ANGLES WITH FORKLIFT ONLY. REFER TO THIS MANUAL FOR PROPER LIFTING CONFIGURATIONS / REQUIREMENTS.

2-1 EQUIPMENT / TOOLS FOR TARPED (NO CRATE OR PALLET) MAGNET INSTALLATION

Description:

The following information outlines provisions for filling the magnet with cryogens and performing electrical / temperature checks while magnet is still in shipping tarp. This will enable required service to be performed in transit based upon magnet shipping date.

CAUTION

Review guidelines with Shipper / Riggers prior to transporting magnet.

Shipping and handling guidelines are provided in Tables 2-1, 2-2 and 2-3.

These guidelines must be followed to prevent any potential damage to the magnet during shipping and handling.

2-1 EQUIPMENT / TOOLS FOR TARPED (NO CRATE OR PALLET) MAGNET INSTALLATION (contonued)**2-1-1 Forklift / Crane**

ITEM	QTY.	CAPACITY / RANGE	FURNISHED BY:	INTENDED USE:
Forklift	1	12,000 lbs. (5,450 Kg) at 50" (1,270 mm) to load center Minimum fork length 90" (2,286 mm) Minimum distance between forks 70" (1,778 mm) Top lift minimum fork height 138" (3,505 mm)	Rigger	Unloading or moving magnet
Crane	1	12,000 lbs. (5,450 Kg)	Rigger	Unloading or moving magnet

2-1-2 Crane Lift Using Slings Around Belly of Magnet

Spreader Beam	1	12,000 lbs. (5,450 Kg) 48" – 50" (1,219 mm – 1,270 mm) between lift points	Rigger	Unloading or moving magnet
Single Ended Strap	2	12,000 lbs. (5,450 Kg) Total weight for both straps combined. Minimum 24 ft. (7.32 M) long and 3" (76.2 mm) wide	Rigger	Unloading or moving magnet

2-1 EQUIPMENT / TOOLS FOR TARPED (NO CRATE OR PALLET) MAGNET INSTALLATION (continued)**2-1-3 Miscellaneous Equipment / Tools**

Hydraulic or Toe Jack	2 or 4	Must support one end of magnet on two jacks or both ends of magnet on 4 jacks Total weight 12,000 lbs. (5,450 Kg) 7 1/2" (190 mm) from foot bottom to jacking surface.	Rigger	Raise up magnet for roller dollies or leveling plates
Roller Dollies	2, 3 or 4	12,000 lbs. (5,450 Kg) Total weight for all dollies combined	Rigger	Moving magnet to magnet room
Level	1	4' (1,219 mm) minimum	Rigger	Level the magnet
Magnet Leveling Kit	1	N / A	GE / SYS	46-260888G4 / Level the magnet
Magnet Boltdown / Seismic Kit	1	Apply sufficient torque to provide 2,500 lbs. (1,134 Kg) clamping force per anchor. Torque requirements to be supplied by Screen Room Vendor.	Screen Room Vendor	Bolt down magnet
Torque Wrench and Socket	1	Torque range = 58 to 258 ft. lbs. (.625" bolt x 1.00" long)	Rigger	Bolt down magnet
Socket Wrench	1	3/4" socket size	Rigger	Remove 1/2" crate lag screws
Magnet Interface Drawing	1	N / A	GE / ISS	2183478IDW Identify magnet dimensions and features
Pre-delivery Information Package	1	N / A	GE	Aid in magnet installation
Portable Temperature Meter	1	N / A	GE / FE	2125073 / Check internal temperatures
Digital Volt / Ohm Meter	1	Measurement capability: < 1 mA	GE / FE	Perform magnet electrical checks
Magnet System Components Checks: Tables 3-1 to 3-5	1	N / A	GE / SYS	Confirm electrical check values

2-2 IN-TRANSIT HANDLING AND SERVICE

LIFTING / HANDLING INFORMATION
TABLE 2-1

MAGNET	* MAXIMUM WEIGHT	** MAXIMUM TILT	FORKLIFT CAPABILITY
LCC 1.5T	12,000 lbs. (5,450 kg.)	30 deg.	Yes
LCC 1.0T			



The magnet **CANNOT** be shipped by train as serious damage to the magnet's internal suspension system may occur due to the vibration loads introduced by rail systems.

SHIPPING INFORMATION
TABLE 2-2

MAGNET	ALLOWABLE SHIPPING MODES	SHIPPING CAPABILITY	MAXIMUM TRANSIT TIME	COMMENTS
LCC 1.0T and 1.5T	Airplane, Air ride only trailer, Boat or ocean going ship	Warm or Cold	Cryogen refill for cold shipment = 15 days	See Note for Tie downs

MAXIMUM LOAD INFORMATION
TABLE 2-3

MAGNET	MAXIMUM LONGITUDINAL LOAD	MAXIMUM LATERAL LOAD	MAXIMUM VERTICAL LOAD	MAXIMUM SHOCK LOADS
LCC 1.0T and 1.5T	1.2 G	1.5 G	1.5 G	None Allowed

* Includes weight of BRM Coil – 2,300 lbs. (1,044 kg.) and associated hardware – 126 lbs. (58 kg.) including cryogenics.

** Maximum tilt allowed only when supported by feet for forklift / rigging operations or moving on inclines (base lift).
Tilt allowed when lifted by single ended slings is one deg. (top lift).

Note:

1. Tie downs and lifting points limited per instructions on magnet face.