

The diagram shows a rectangular box labeled "IG Node" in the top right corner. A horizontal line extends from the left side of the box to the text "10/100/1000 Ethernet". At the end of this line, there is a small square icon representing a network port.

GOC – GRE Console Block Diagram

The diagram illustrates the hardware configuration and connections for the GOC (GRE Console) system. It features a central **Linux OS Host Computer** connected to various peripherals and a **Terminators Cent50** unit.

Terminators Cent50 Components:

- DVD-RAM**
- MOD**

Linux OS Host Computer Components and Connections:

- USB 2.0**
- AC97 Audio**
- PS/2**
- Parallel Port**
- Serial Port**
- 10/100/1000 Ethernet Port**
- IEEE 1394 / Firewire Port**
- NVIDIA 980XGL** (AGP 8x)
- OPEN** (64bit / 66MHz PCI)
- OPEN** (64bit / 133MHz PCI)
- INTEL PRO 10/100/1000** (64bit / 133MHz PCI)
- OPEN** (32bit / 33MHz PCI)
- ULTRA160 DUAL SCSI**

Peripheral Devices and Connections:

- Rx Monitor** and **Display Monitor** connected to the Terminators Cent50.
- SCIM** (Human Interface Device) connected to the Terminators Cent50.
- KEYBOARD** connected to the Terminators Cent50.
- Mouse** and **Trackball** connected to the Terminators Cent50.
- Modem** connected to the Terminators Cent50.
- USB Hub** connected to the Terminators Cent50.
- DASM** (Data Acquisition System Module) connected to the Terminators Cent50.

Connections to IG Nodes and Gantry:

- To IG Node #2**
- To IG Node #3**
- To Gantry DAS**
- Loopback to RX for Diags**
- To Gantry**
- Service Key**

The diagram illustrates the internal architecture of a DARC Node. It features a central 'DIP Board' which is connected to several external components via '64bit / 133MHz PCI' interfaces. These components include a '10/100/1000 GbE Card' (which is further connected to two '10/100/1000 Ethernet' ports) and an 'Ultra320 SCSI' interface. The DIP Board also includes internal components labeled 'RX', 'TX', and 'Abort'.

The diagram illustrates the hardware configuration of the SDDA Node. At the top, a box labeled "SDDA Node" contains an "ICPT Board". The ICPT Board is connected to two "Molex 4" connectors, which are in turn connected to a vertical stack of four "Scan Data Disks". Below the ICPT Board, a line labeled "Ultra320 SCSI" connects to another vertical stack of four "Scan Data Disks".